



SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: Not applicable

1. Identification

1.1. Product identifier

Product Name WOOD P212 BOND

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use No information available

Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1(800) 726-7845 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)
Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024



Appearance No information available **Physical state** Paste / Gel Liquid **Odor** Characteristic

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing
If experiencing respiratory symptoms: Call a POISON CENTER or doctor

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Information

No information available.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Limestone	1317-65-3	30 - 60
Propylene carbonate	108-32-7	1 - <5
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene	64742-48-9	1 - <5
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	0.1 - <1
4,4'-Methylenediphenyl diisocyanate	101-68-8	0.1 - <1
Quartz	14808-60-7	0.1 - <1
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - <1

**The exact percentage (concentration) of composition has been withheld as a trade secret*

4. First-aid measures

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. May cause allergic respiratory reaction. Get medical attention immediately if symptoms occur. If breathing is difficult, (trained personnel should) give oxygen. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. May produce an allergic reaction. Call a physician immediately. Small amounts of toxic methanol are released by hydrolysis.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or wheezing. Itching. Rashes. Hives.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical, CO ₂ , alcohol-resistant foam or water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. CAUTION: Use of water spray when fighting fire may be inefficient.
Large Fire	
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by inhalation. May cause sensitization by skin contact.
Hazardous combustion products	Carbon oxides. Carbon dioxide (CO ₂).
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Stop leak if you can do it without risk. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Keep out of drains, sewers, ditches and waterways. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. A vapor suppressing foam may be used to reduce vapors. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up Use personal protective equipment as required. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from water or moist air. Store locked up. Keep out of the reach of children. Keep from freezing.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

7.3 References to other sections

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

Reference to other sections

Section 10: STABILITY AND REACTIVITY
Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.005 ppm	(vacated) Ceiling: 0.02 ppm regulated under Methylene bisphenyl isocyanate (vacated) Ceiling: 0.2 mg/m ³ regulated under Methylene bisphenyl isocyanate Ceiling: 0.02 ppm Ceiling: 0.2 mg/m ³	IDLH: 75 mg/m ³ Ceiling: 0.020 ppm 10 min Ceiling: 0.2 mg/m ³ 10 min TWA: 0.005 ppm TWA: 0.05 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Limestone 1317-65-3	TWA: 10 mg/m ³	-	LPP: 7 mg/m ³ LPP: 5 mg/m ³	-
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.005 ppm	TWA: 0.005 ppm	LPP: 0.004 ppm LPP: 0.05 mg/m ³	TWA: 0.005ppm
Quartz 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	LPP: 0.08 mg/m ³	TWA: 0.025mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.005ppm	TWA: 0.005ppm TWA: 0.051mg/m ³	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	TWA: 0.005 ppm
Quartz 14808-60-7	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	TWA: 0.025 mg/m ³

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Avoid contact with eyes.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Skin and body protection Wear suitable protective clothing.

Respiratory protection Use appropriate respiratory protection.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Do not breathe vapor or mist. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Regular cleaning of equipment, work area and clothing is recommended.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid
Appearance No information available
Color No information available
Odor Characteristic
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	> 93 °C / 199.4 °F	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

9.2. Other information

Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	95	
Softening point	No information available	
Molecular weight	No information available	
VOC content	< 20 g/L	No information available
Density	No information available	
Bulk density	No information available	

10. Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause sensitization in susceptible persons. (based on components).
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

May cause sensitization by skin contact.

Ingestion

Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation".

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) 58,250.30 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapor) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Propylene carbonate 108-32-7	LD50 > 5000 mg/kg (Rattus) OECD 401	> 3000 mg/kg (Oryctolagus cuniculus)	-
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	>6000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	>8500 mg/m ³ (Rattus) 4 h
o-(p-isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50 >2000 mg/Kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (4h) Rat
4,4'-Methylenediphenyl diisocyanate 101-68-8	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (Rattus) 4 h
Quartz 14808-60-7	>2000 mg/kg (Rattus)	-	-
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	=2234 mg/kg (Rattus)	LD 50 (Rattus) > 2000 mg/kg OECD 402	>640 ppm (Rattus) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				irritant

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye	0.1 mL	24 hours	Non-irritant

Respiratory or skin sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
4,4'-Methylenediphenyl diisocyanate 101-68-8	-	Group 3	-	-
Quartz 14808-60-7	A2	Group 1	Known	X

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Limited evidence of a carcinogenic effect

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

12.1. Toxicity

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Propylene carbonate 108-32-7	ErC50 (72h): > 900mg/L (Desmodesmus subspicatus, OECD-201)	LC50 (96) h > 1000 mg/L (Cyprinus carpio, 67/548/EWG, Annex V, C.1.)	EC50 > 10000 mg/L 17 h	EC50 (48h): > 1000mg/L (Daphnia magna, OECD 202)
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	-	LC50: =2200mg/L (96h, Pimephales promelas)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
o-(p-isocyanatobenzyl)phenyl isocyanate 5873-54-1	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	LC50 (96 h) > 1000 mg/l Danio rerio (OECD 203)	-	EC50 (24H) >1000 mg/L Daphnia magna
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9
Propylene carbonate 108-32-7	-0.41
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	0.6

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

Waste from residues/unused products

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Contaminated packaging

Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: Keep from freezing.

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

International Inventories

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	SARA 313 - Threshold Values %
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	1.0
4,4'-Methylenediphenyl diisocyanate	101-68-8	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

SVHC: Substances of Very High Concern for Authorization:

SAFETY DATA SHEET

WOOD P212 BOND
Revision Number 1

Revision date 11-Apr-2024
Supersedes Date: 11-Apr-2024

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Prepared By Product Safety & Regulatory Affairs.

Revision date 11-Apr-2024

Revision Note No information available.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided “as-is” and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. (“Company”) expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user’s application(s). **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN.** The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at <https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet