

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK ALL PURPOSE CLEAR ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Acetone; Methyl ethyl ketone



United Kingdom - BE Page 1 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Signal word

Danger

Hazard statements

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

H225 - Highly flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

EUH208 - Contains 1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing mist/vapours/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye/face protection

P312 - Call a POISON CENTER or doctor if you feel unwell

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU	CAS No	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Acetone	200-662-2	67-64-1	Eye Irrit. 2 (H319)	-	-	-	01-2119471330-
40 - <80 %	(606-001-00-		STOT SE 3 (H336)				49-XXXX
	8)		Flam. Liq. 2 (H225)				
			(EUH066)				
Methyl ethyl ketone	201-159-0	78-93-3	Eye Irrit. 2 (H319)	-	-	-	01-2119457290-
10 - <20 %	(606-002-00-		STOT SE 3 (H336)				43-XXXX
	3)		Flam. Liq. 2 (H225)				
			(EUH066)				
1,4-Benzenediol,	201-222-2	79-74-3	Acute Tox. 4 (H302)	-	-	10	01-2119539460-
2,5-bis(1,1-dimethylprop			Skin Sens. 1A (H317)				43-XXXX
yl)-			Aquatic Acute 1 (H400)				
0.05 - <0.1 %			Aquatic Chronic 1 (H410)				

Full text of H- and EUH-phrases: see section 16

United Kingdom - BE Page 2 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
Methyl ethyl ketone	201-159-0 (606-002-00-3)	78-93-3	-	-	-	-	-
1,4-Benzenediol, 2,5-bis(1,1-dimethylpro pyl)-	201-222-2	79-74-3	1900	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and

persists.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a doctor.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

United Kingdom - BE Page 3 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 **Revision Number** 3

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Carbon oxides. Hazardous combustion products

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

United Kingdom - BE Page 4 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Recommended storage temperature

Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s) Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Acetone	TWA: 500 ppm	TWA: 500 ppm
67-64-1	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³
		STEL: 1500 ppm
		STEL: 3620 mg/m ³
Methyl ethyl ketone	TWA: 200 ppm	TWA: 200 ppm
78-93-3	TWA: 600 mg/m ³	TWA: 600 mg/m ³
	STEL: 300 ppm	STEL: 300 ppm
	STEL: 900 mg/m ³	STEL: 899 mg/m ³
		Sk*
Polyvinyl chloride	-	TWA: 10 mg/m ³
9002-86-2		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
Acetone	-	50 mg/L (urine - Acetone end of	-
67-64-1		shift)	
Methyl ethyl ketone	-	70 µmol/L (urine - Butan-2-one post	70 µmol/L - urine (Butan-2-one) -

United Kingdom - BE Page 5 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

(PNEC)

Revision date 02-Jul-2024 Revision Number 3

78-93-3		shift)	post shift
Derived No Effect Level (DNEL)	No information available		
Derived No Effect Level (DNEL)			
Acetone (67-64-1)			1
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m³	
Long term Systemic health effects worker	Inhalation	1210 mg/m³	
Mothyl othyl kotomo (70 02 2)			
Methyl ethyl ketone (78-93-3)	Eve cours	Dariyad Na Effect Level	Cototy foots
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m ³	
Derived No Effect Level (DNEL)			
Acetone (67-64-1)		<u>_</u>	
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term	Oral	62 mg/kg bw/d	
Systemic health effects			
Methyl ethyl ketone (78-93-3)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m³	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	
Predicted No Effect Concentration	n		

United Kingdom - BE Page 6 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 **Revision Number** 3

Predicted No Effect Concentration (PNEC)				
Acetone (67-64-1)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	10.6 mg/l			
Freshwater - intermittent	21 mg/l			
Marine water	1.06 mg/l			
Microorganisms in sewage treatment	100 mg/l			
Freshwater sediment	30.4 mg/kg dry weight			
Marine water	3.04 mg/kg dry weight			
Soil	29.5 mg/kg dry weight			

Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Tight sealing safety goggles. Face protection shield. Eye protection must conform to Eye/face protection

standard EN 166.

Wear protective gloves. The breakthrough time of the gloves depends on the material **Hand protection**

and the thickness as well as the temperature.

Skin and body protection

In case of inadequate ventilation wear respiratory protection. In case of mist, spray or Respiratory protection

aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Suitable protective clothing.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Liquid **Appearance** Colour Colourless Odour Solvent.

Values Remarks • Method Property

No data available Melting point / freezing point None known 56 °C

Initial boiling point and boiling

range

Flammability No data available Flammable liquid Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

-20 °C Flash point

Autoignition temperature No data available None known None known

Decomposition temperature

No data available Not applicable. Insoluble in water.

No data available None known pH (as aqueous solution) Kinematic viscosity No data available None known

Dynamic viscosity No data available Insoluble in water. Water solubility

United Kingdom - BE Page 7 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressure<110 kPa</th>None knownRelative densityNo data availableNone known

Bulk density

No data available

No data available

No data available

No data available

Relative vapour density

No data available

None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition None under normal use conditions. Stable under recommended storage conditions.

products

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

United Kingdom - BE Page 8 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations

may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >2000
 mg/kg

 ATEmix (dermal)
 >2000
 mg/kg

 ATEmix (inhalation-gas)
 >20000
 ppm

 ATEmix (inhalation-dust/mist)
 >5
 mg/l

 ATEmix (inhalation-vapour)
 >20
 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-	=2 g/kg (Rattus)	> 3160 mg/kg (Rabbit)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion					

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

United Kingdom - BE Page 9 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Acetone	-	LC50 96 h 4.74		EC50 48 h		, ,
67-64-1		- 6.33 mL/L	mg/L 15 min	10294 - 17704		
		(Oncorhynchus		mg/L (Daphnia		
		mykiss)		magna Static)		
Methyl ethyl ketone	EC50=1972 mg/l	LC50: 3130 -	EC50 = 3403	EC50 48 h > 308		
78-93-3	(Pseudokirchner	3320mg/L (96h,	mg/L 30 min	mg/L (Daphnia		
	iella subcapitata)	Pimephales	EC50 = 3426	magna)		
		promelas)	mg/L 5 min	-		
1,4-Benzenediol,	CE50 (72h) 1.2 -	CL50 (96h)	-	CE50 (48h) 0.91		10
2,5-bis(1,1-dimethylpro	1.7 mg/L Algae	0.013 mg/L		Daphnia		
pyl)-		(Lepomis		(Daphnia		
79-74-3		machrochirus)		Magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	91 % Readily biodegradable

United Kingdom - BE Page 10 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Biodegradability: CO2 Evolution Test (TG 301 B)
--

Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready	28 days	biodegradation	98 % Readily biodegradable
Biodegradability: Closed Bottle Test			
(TG 301 D)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Ob antical manage	Doublition of finite	
Chemical name	Partition coefficient	
Acetone	-0.24	
Methyl ethyl ketone	0.3	
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-	2.1	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

threshold of declaration.

Chemical name	PBT and vPvB assessment		
Acetone	The substance is not PBT / vPvB		
Methyl ethyl ketone	The substance is not PBT / vPvB		
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-	The substance is not PBT / vPvB		

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

European Waste Catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information

Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

United Kingdom - BE Page 11 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number UN1133 **14.2 UN proper shipping name** Adhesives

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing group

Description UN1133, Adhesives, 3, II, (D/E)

14.5 Environmental hazards No

14.6 Special precautions for user

Special Provisions 640D
Classification code F1
Tunnel restriction code
Limited quantity (LQ) 5 L
ADR Hazard Id (Kemmler 33

Number)

IMDG

14.1 UN number or ID number14.2 UN proper shipping nameAdhesives

14.3 Transport hazard class(es) 3 14.4 Packing group

Description UN1133, Adhesives, 3, II, (-20°C c.c.)

14.5 Marine pollutant NP

14.6 Special precautions for user

Special Provisions None
Limited Quantity (LQ) 5 L
EmS-No. F-E, S-D

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)

14.4 Packing group

Description UN1133, Adhesives, 3, II

14.5 Environmental hazards No
14.6 Special precautions for user

Special Provisions A3 Limited quantity (LQ) 1 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

United Kingdom - BE Page 12 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

United Kingdom - BE Page 13 / 14

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes date 09-Nov-2022

Revision date 02-Jul-2024 Revision Number 3

H302 - Harmful if swallowed

H317 - May cause an allergic skin reaction H319 - Causes serious eve irritation

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 02-Jul-2024

Indication of changes

Revision note SDS sections updated, 2.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 14 / 14