

Revision date 13-Mar-2025

This safety data sheet was created pursuant to the requirements of: Preparation of safety data sheets for hazardous chemicals Code of Practice June 2023

BOSTIK V60 SILICONE TRANSPARENT

Revision Number 2 Supersedes date 12-Mar-2023

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK V60 SILICONE TRANSPARENT

Product Code(s) 30804561

30610925; 30804561

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Sealant

Uses advised against No information available.

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria

Australia

Tel: 613 9279-9333 Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Skin sensitization	Category 1 - (H317)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

Label elements

Exclamation mark Health hazard



Australia - EN Page 1/9

BOSTIK V60 SILICONE TRANSPARENT

Revision Number 2 Supersedes date 12-Mar-2023

Revision date 13-Mar-2025

Signal word

WARNING

Hazard statements

H317 - May cause an allergic skin reaction

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Contaminated work clothing should not be allowed out of the workplace

Do not breathe dust Wear protective gloves

Precautionary Statements - Response

Get medical advice/attention if you feel unwell IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing.

Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing.

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

May be harmful if swallowed.

May be harmful in contact with skin.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No.	Weight-%
2-Butanone, O,O',O"-(methylsilylidyne)trioxime	22984-54-9	3 - 7
Butan-2-one O,O',O"-(vinylsilylidyne)trioxime	2224-33-1	1 - 5
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

Show this safety data sheet to the doctor in attendance. If medical advice is needed, **General advice**

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin

Australia - EN Page 2/9

BOSTIK V60 SILICONE TRANSPARENT

Revision Number 2 Supersedes date 12-Mar-2023

irritation or allergic reactions see a physician.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

Revision date 13-Mar-2025

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous combustion products Nitrogen oxides (NOx). Silicon oxides.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Australia - EN Page 3 / 9

BOSTIK V60 SILICONE TRANSPARENT

Revision Number 2 Supersedes date 12-Mar-2023

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Revision date 13-Mar-2025

Take off contaminated clothing and wash before reuse.

General hygiene considerations Take off contaminated clothing and wash it before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food,

drink and animal feeding stuffs. Protect from moisture.

Recommended storage

temperature

Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Incompatible materials Strong oxidizing agents.

Section 8: Exposure controls and personal protection

Working area parameters, subject to mandatory control (MAC or TSEL)

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released

upon curing. No special technical protective measures are necessary.

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Lightweight protective clothing. Long sleeved clothing.

Hand protection For operations where prolonged or repeated skin contact may occur, impervious gloves

should be worn. Nitrile rubber.

Respiratory protection Organic gases and vapors filter conforming to EN 14387. White. Brown.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Solid

Appearance Very viscous Paste

ColorClearOdorSlight

Odor threshold No information available

Property Values Remarks • Method

pH No data available Not applicable Insoluble in water

pH (as aqueous solution)

Melting point / freezing point
Initial boiling point and boiling
range

No data available
No data available
No data available

Australia - EN Page 4 / 9

BOSTIK V60 SILICONE TRANSPARENT

Revision Number 2 Supersedes date 12-Mar-2023

Revision date 13-Mar-2025

Flash point > 120 °C CC (closed cup)

Evaporation rate No data available Flammability No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressure No data available Relative vapor density No data available

Relative density 1.023

Water solubility Insoluble in water Solubility(ies) No data available No data available Partition coefficient **Autoignition temperature** No data available No data available **Decomposition temperature** Kinematic viscosity No data available No data available Dynamic viscosity **Explosive properties** No information available **Oxidizing properties** No information available

Other information

Solid content (%)
Liquid Density
No information available
No information available

VOC content No information available

Section 10: Stability and reactivity

Reactivity_

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible materials

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Hazardous decompositionThermal decomposition can lead to release of irritating and toxic gases and vapors.

products

Section 11: Toxicological information

Australia - EN Page 5 / 9

BOSTIK V60 SILICONE TRANSPARENT

Revision date 13-Mar-2025 **Revision Number** 2 Supersedes date 12-Mar-2023

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. Eye contact

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May be harmful in contact with skin.

Ingestion Based on available data, the classification criteria are not met.

Symptoms Itching. Rashes. Hives.

Numerical measures of toxicity - Product Information

The following ATE values have been calculated for the mixture

ATEmix (inhalation-gas) >20000 ATEmix (inhalation-vapor) >20 ATEmix (inhalation-dust/mist) >5

Oral LD50 > 2009 mg/kg (rat) **Dermal LD50** > 2009 mg/kg (rat)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone,	LD50 = 2463 mg/Kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
O,O',O"-(methylsilylidyne)trioxi	(OECD 401)	(OECD 402)	
me			
Butan-2-one	LD50 > 2000 mg/kg (Rattus)	LD50 > 2009 mg/kg (Rattus)	-
O,O',O"-(vinylsilylidyne)trioxime	OECD 425	OECD 402	

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization May cause an allergic skin reaction.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	Not a skin sensitizer

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

Australia - EN Page 6 / 9

BOSTIK V60 SILICONE TRANSPARENT

Revision Number 2 Supersedes date 12-Mar-2023

Revision date 13-Mar-2025

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2-Butanone,	EC50 (72h) = 94 mg/L	EC50 (96h) >120 mg/L	-	EC50 (48h) > 120 mg/L
O,O',O"-(methylsilylidyn		(Oncorhynchus		(Daphnia magna) OECD
e)trioxime	subcapitata) OECD 201	mykiss)Freshwater static		202
22984-54-9		(OECD guideline 203)		
Butan-2-one	EC50 (72h) = 16 mg/L	LC50 (96h)> 120 mg/L	-	EC50 (48h) > 120 mg/L
O,O',O"-(vinylsilylidyne)t	(Pseudokirchneriella	(Oncorhynchus mykiss)		(Daphnia magna) OECD
rioxime	subcapitata) OECD 201	OECD 203		202
2224-33-1				

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
2-Butanone, O,O',O"-(methylsilylidyne)trioxime	1.69
22984-54-9	
Butan-2-one O,O',O"-(vinylsilylidyne)trioxime	1.69
2224-33-1	

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

international regulations as applicable

Australia - EN Page 7 / 9

BOSTIK V60 SILICONE TRANSPARENT

Revision Number 2 Supersedes date 12-Mar-2023

Revision date 13-Mar-2025

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Illicit Drug Precursors/Reagents

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

International Inventories

AIIC Complies
NZIOC Not Listed
ENCS Not Listed
IECSC Not Listed
KECL Not Listed
PICCS Not Listed

Legend:

AIIC - Australian Inventory of Industrial Chemicals

NZIoC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Australia - EN Page 8 / 9

BOSTIK V60 SILICONE TRANSPARENT

Revision date 13-Mar-2025 **Revision Number** 2 Supersedes date 12-Mar-2023

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Directive 2011/65/EU (EU RoHS 2), as amended by the Delegated Directive (EU) 2015/863 (EU RoHS 3)

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Mar-2025

Revision Note

SDS sections updated: 2, 3,

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Skin designation Sk*

С Carcinogen

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Australia - EN Page 9/9