

Revision date 21-Oct-2022

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK SILICONE GX SEALANT IVORY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Joint sealants

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Industries Limited Newtown, Swords Co. Dublin Ireland Tel: +353 (1) 8624900

Tel: +353 (1) 8624900 Fax: +353 (1) 8402186

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650

Europe 11

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Chronic aquatic toxicity Category 3 - (H412)

2.2. Label elements

Hazard statements

H412 - Harmful to aquatic life with long lasting effects

EU Specific Hazard Statements

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] & Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

Ireland - BE Page 1/15

Revision date 21-Oct-2022

Revision Number 3.01

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022

2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics >25 - <40 %	934-956-3	RR-100252-4	Asp. Tox. 1 (H304)	-	-	-	01-2119827000- 58-XXXX
Silica, amorphous 5 - <10 %	231-545-4	7631-86-9	[B]	-	-	-	01-2119379499- 16-XXXX
Triacetoxy(propyl)silane 1 - <2.5 %	241-816-9	17865-07-5	Skin Corr. 1B (H314) (EUH071)	-	-	-	01-2119966899- 07-XXXX
Silanetriol, methyl-, triacetate 1 - <2.5 %	224-221-9	4253-34-3	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)	-	-	-	01-2119962266- 32-XXXX
Titanium dioxide 0.1- <1 %	(022-006-00- 2) 236-675-5	13463-67-7	[C]	-	-	-	01-2119489379- 17-XXXX
Octamethylcyclotetrasilo xane [D4] 0.01 - < 0.05 %	(014-018-00- 1) 209-136-7	556-67-2	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	10	10	01-2119529238- 36-XXXX
4,5-dichloro-2-octyl-2H-is othiazol-3-one [DCOIT] 0.01 - < 0.05 %	(613-335-00- 8) 264-843-8	64359-81-5	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	100	100	-
Dimethylbis[(1-oxoneode cyl)oxy]stannane 0.01 - < 0.05 %	273-028-6	68928-76-7	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Aquatic Chronic 3 (H412)	-	-	-	01-2120770324- 57-xxxx

Substances identified by a number starting "RR-" in the CAS-field are substances for which there is no CAS# used in EU and we use an internal numbering system to track within our SDS software

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU	Weight-%	Classification	Specific	M-Factor M-Factor	REACH
	Index No)		according to	concentration limit	(long-ter	registration

Ireland - BE Page 2/15

EVO-STIK SILICONE GX SEALANT IVORY

Revision date 21-Oct-2022 Supercedes Date: 27-Jan-2022 Revision Number 3.01

			Regulation (EC) No. 1272/2008 [CLP]	(SCL)		m)	number
Acetic acid 64-19-7	(607-002-00 -6) 200-580-7	1 - <2.5	Skin Corr. 1A (H314) Flam. Liq. 3 (H226)	Eye Irrit. 2 :: 10%<=C<25% Skin Corr. 1A :: C>=90% Skin Corr. 1B :: 25%<=C<90% Skin Irrit. 2 :: 10%<=C<25%	-	-	01-211947532 8-30-XXXX

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

- [B] Substance with a Community workplace exposure limit
- [C] Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring
- [G] This substance meets the PBT criteria of REACH, annex XIII

This substance meets the vPvB criteria of REACH, annex XIII

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	-	-	-	-	-
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-
Triacetoxy(propyl)silane	241-816-9	17865-07-5	-	-	-	-	-
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1600	-	-	-	-
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	-	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	(014-018-00-1) 209-136-7	556-67-2	-	-	-	-	-
4,5-dichloro-2-octyl-2H- isothiazol-3-one [DCOIT]	(613-335-00-8) 264-843-8	64359-81-5	567+	-	0.16+	0.16+	0.16+
Dimethylbis[(1-oxoneod ecyl)oxy]stannane	273-028-6	68928-76-7	892	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

SECTION 4: First aid measures

Ireland - BE Page 3/15

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Revision date 21-Oct-2022

Skin contact In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and

water.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Note to doctors

SECTION 5: Firefighting measures

5.1. Extinguishing media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. **Suitable Extinguishing Media**

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead to release of

irritating and toxic gases and vapours.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Ireland - BE Page 4 / 15

Revision date 21-Oct-2022

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

Methods for cleaning upTake up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s) Joint sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium

dioxide is unlikely to occur from exposure to this product Small amounts of acetic acid

(CAS 64-19-7) are formed by hydrolysis and released upon curing

Chemical name	European Union	Ireland	United Kingdom
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics,	TWA/8h	-	
< 0.03% aromatics	5mg/m³		
RR-100252-4	STEL/15 mins 10mg/m ³		
Silica, amorphous	TWA: 0.1 mg/m ³	TWA: 6 mg/m ³	TWA: 6 mg/m ³
7631-86-9		TWA: 2.4 mg/m ³	TWA: 2.4 mg/m ³
		STEL: 18 mg/m ³	TWA: 0.1 mg/m ³
		STEL: 7.2 mg/m ³	STEL: 18 mg/m ³
			STEL: 7.2 mg/m ³
			STEL: 0.3 mg/m ³
Acetic acid	TWA: 25 mg/m ³	TWA: 20 ppm	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 50 mg/m ³	TWA: 25 mg/m ³
	STEL: 50 mg/m ³	STEL: 20 ppm	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m ³	STEL: 50 mg/m ³
Titanium dioxide	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³	TWA: 4 mg/m ³
		STEL: 30 mg/m ³	STEL: 30 mg/m ³
		STEL: 12 mg/m ³	STEL: 12 mg/m ³
Dimethylbis[(1-oxoneodecyl)oxy]stannane	-	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
68928-76-7		STEL: 0.2 mg/m ³	STEL: 0.2 mg/m ³
		_	Sk*

Ireland - BE Page 5/15

Revision date 21-Oct-2022

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

D. C. LIN, Eff., (1) ... (DNEL) ... Als information qualishing

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Titanium dioxide (13463-67-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Local health effects	Inhalation	10 mg/m ³		

Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Туре	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)			
worker	Inhalation	73 mg/m ³			
Long term		_			
Systemic health effects					

Derived No Effect Level (DNEL)				
Titanium dioxide (13463-67-7)				
Туре	Exposure route	Derived No Effect Level	Safety factor	
		(DNEL)		
Consumer	Oral	700 mg/kg bw/d		
Long term				
Systemic health effects				

Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	13 mg/m³			
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d			

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)				
Titanium dioxide (13463-67-7)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Marine water	0.0184 mg/l			
Freshwater sediment	1000 mg/kg			
Freshwater	0.184 mg/l			
Marine sediment	100 mg/kg			
Soil	100 mg/kg			
Microorganisms in sewage treatment	100 mg/l			
Freshwater - intermittent	0.193 mg/l			

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

Ireland - BE Page 6 / 15

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

Revision date 21-Oct-2022

gloves. Gloves must conform to standard EN 374

Skin and body protection None under normal use conditions.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid **Appearance** Paste Colour Off-white Odour Acetic acid.

Odour threshold No information available

Remarks • Method Property Values

No data available Melting point / freezing point None known Initial boiling point and boiling No data available None known

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point > 100 °C None known **Autoignition temperature** No data available None known None known

Decomposition temperature

No data available Not applicable. Insoluble in water. pН

pH (as aqueous solution) No data available None known Kinematic viscosity > 21 mm²/s @ 40°C

No data available Dynamic viscosity

Water solubility No data available. None known Solubility(ies) No data available None known **Partition coefficient** No data available None known Vapour pressure No data available None known Relative density No data available None known

Bulk Density No data available

Density 0.97

Relative vapour density No data available None known

Particle characteristics

No information available **Particle Size Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes Not applicable

Ireland - BE Page 7 / 15

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge

None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

Revision date 21-Oct-2022

sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Ireland - BE Page 8/15

EVO-STIK SILICONE GX SEALANT IVORY

Numerical measures of toxicity

Supercedes Date: 27-Jan-2022

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics,	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus)	LC50 Inhalation(4h) >5266 mg/m³ (Rattus)
< 0.03% aromatics	0202 .0.	OECD 402	g, (. tattae)
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
Silanetriol, methyl-, triacetate	LD50 = 1600 mg/kg (Rattus) OECD 401	•	•
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m³ (Rattus) 4 h
4,5-dichloro-2-octyl-2H-isothiaz ol-3-one [DCOIT]	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h
Dimethylbis[(1-oxoneodecyl)ox y]stannane	LD50 =892 mg/Kg (Rattus) (OECD 401)	LD50 >2000 mg/Kg (rattus)	_

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Revision date 21-Oct-2022

Revision Number 3.01

	Method	Species	Exposure route	Effective dose	Exposure time	Results
ſ		Rabbit	Dermal		6 days	Product score <=1
					-	Non-irritant

Titanium dioxide (13463-67-7)

	,				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

	Method	Species	Exposure route	Effective dose	Exposure time	Results
Г		Rabbit	eye		6 days	Product score <=1
			-			Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed

Titanium dioxide (13463-67-7)

	Method	Species	Exposure route	Results
--	--------	---------	----------------	---------

Ireland - BE Page 9/15

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022

Revision date 21-Oct-2022 Revision Number 3.01

OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser
Sensitisation: Local Lymph Node			
Assay			

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		sensitising
Sensitisation			_

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h)> 3193 mg/l (Acartia tonsa)		
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneri ella subcapitata)	=5000mg/L (96h, Brachydanio	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		

Ireland - BE Page 10 / 15

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022

Revision date 21-Oct-2022 Revision Number 3.01

Triacetoxy(propyl)silane	EC50 (72h):	LC50 (96h) =	-	EC50 (48h) =		
17865-07-5	approx. 24	108.89 mg/L		89.59 mg/L		
	mg/I(Pseudokirc					
	henriella					
	subpicata)					
Silanetriol, methyl-,	EC50 (72h):	LC50 (96h) >500	-	EC50 (48h) >500		
triacetate	>500 mg/l	mg/l		mg/l (Daphnia		
4253-34-3	(Pseudokirchner	(Brachydanio		magna)		
	ella subcapitata)	rerio)				
Titanium dioxide	LC50 (96h)	-	-	-		
13463-67-7	>10000 mg/l					
	(Cyprinodon					
	variegatus)					
	OECD 203					
Octamethylcyclotetrasil	-	LC50:	-	EC50:	10	10
oxane [D4]		>1000mg/L (96h,		=25.2mg/L (24h,		
556-67-2		Lepomis		Daphnia magna)		
		macrochirus)				
		LC50: >500mg/L				
		(96h,				
		Brachydanio				
		rerio)				
4,5-dichloro-2-octyl-2H-		LC50 (96h)	-	EC50 (48h)	100	100
isothiazol-3-one	=0.025 mg/L	0.0078 mg/L		0.0097 mg/L		
[DCOIT]	Algae	(Oncorhynchus		Daphnia magna		
64359-81-5	(Scenedesmus	mykiss)(OECD		(OECD 202)		
	subspicatus)(OE	203)				
	CD 201)					
Dimethylbis[(1-oxoneod	-	-	-	EC50 =39 mg/L		
ecyl)oxy]stannane				(Daphnia		
68928-76-7				magna)		
				(OECD 201)		

12.2. Persistence and degradability

Persistence and degradability

No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining
			biodegradability are not
			applicable to inorganic
			substances

Octamethylcyclotetrasiloxane [D4] (556-67-2)

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)

Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days
Anaerobic Transformation in Aquatic			·
Sediment Systems			

Dimethylbis[(1-oxoneodecyl)oxy]stannane (68928-76-7)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	0%	Not readily biodegradable
Biodegradability: CO2 Evolution Test	-		
(TG 301 B)			
OECD Test No. 301F: Ready	28 days	3%	Not readily biodegradable
Biodegradability: Manometric	-		
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Ireland - BE Page 11 / 15

Revision date 21-Oct-2022

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Triacetoxy(propyl)silane	1.23
Silanetriol, methyl-, triacetate	-2.4
Octamethylcyclotetrasiloxane [D4]	6.49
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03%	The substance is not PBT / vPvB
aromatics	
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does
	not apply
Triacetoxy(propyl)silane	The substance is not PBT / vPvB
Silanetriol, methyl-, triacetate	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does
	not apply
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance	Negative.	
with the criteria set out in Commission		
Delegated Regulation (EU) 2017/2100(3) or		
Commission Regulation (EU) 2018/605(4).		

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

Ireland - BE Page 12/15

Revision date 21-Oct-2022

Revision Number 3.01

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

IMDG

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated

14.5 Marine pollutant NP14.6 Special Provisions None

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains a biocide: Contains DCOIT. May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Ireland - BE Page 13/15

Revision date 21-Oct-2022

EVO-STIK SILICONE GX SEALANT IVORY

Supercedes Date: 27-Jan-2022 Revision Number 3.01

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH014 - Reacts violently with water

EUH071 - Corrosive to the respiratory tract

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eve damage

H330 - Fatal if inhaled

H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

Notes assigned to an entry

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 μm, length > 5 μm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value * Skin designation

Classification procedure

Ireland - BE Page 14/15

EVO-STIK SILICONE GX SEALANT IVORY

Revision date 21-Oct-2022 Supercedes Date: 27-Jan-2022 Revision Number 3.01

Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	On basis of test data
Serious eye damage/eye irritation	On basis of test data
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 21-Oct-2022

Revision note SDS sections updated 2 3 8 11 12 15

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Ireland - BE Page 15/15