

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK SILICONE C SEALANT GREY

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK SILICONE C SEALANT GREY

Form This substance/ mixture contains nanoforms

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name Supplier

Bostik Espana par Compositor Stravinsky, Bostik Industries Limited
12-18 Newtown, Swords
Poligone Industrial Can Jardi Co. Dublin Ireland
08191 Rubi (Barcelona), Spain Tel: +353 (1) 8624900
Tel: +34 93 586 02 00 Fax: +353 (1) 8402186

Fax: +34 93 586 02 01

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment - chronic Category 3 - (H412)

#### 2.2. Label elements

#### **Hazard statements**

H412 - Harmful to aquatic life with long lasting effects.

#### **EU Specific Hazard Statements**

EUH208 - Contains 3-aminopropyltriethoxysilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

Ireland - BE Page 1 / 17

# EVO-STIK SILICONE C SEALANT GREY Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

P501 - Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

#### 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

#### PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	Weight-	REACH	EC No (EU	Classification	Specific	M-Factor	M-Factor	Notes
	%	registration	Index No)	according to	concentration		(long-ter	
		number		Regulation (EC) No.	limit (SCL)		m)	
				1272/2008 [CLP]				
Hydrocarbons,	10 - <20	01-2119552497	932-078-5	Asp. Tox. 1 (H304)	-	-	-	-
C13-C23, n-alkanes,		-29-xxxx						
isoalkanes, cyclics, <								
0.03% aromatics								
RR-100254-6								
Silica, amorphous	5 - <10	01-2119379499	231-545-4	[B]	-	-	-	-
7631-86-9		-16-XXXX						
2-Pentandione,	1 - <2.5	01-2120004323	484-460-1	Acute Tox. 4 (H302)	-	-	-	-
O,O',O"-(methylsilyli		-76-XXXX		Eye Irrit. 2 (H319)				
dyne)trioxime								
37859-55-5								
Titanium dioxide	0.1 - <0.5	01-2119489379	236-675-5	[C]	-	-	-	V,W,10
13463-67-7		-17-XXXX	(022-006-00-2)					
3-aminopropyltrietho	0.1 - <0.5	01-2119480479	213-048-4	Acute Tox. 4	-	-	-	-
xysilane		-24-XXXX	(612-108-00-0)	(H302)				
919-30-2				Skin Corr. 1B				
				(H314)				
				Eye Dam. 1 (H318)				
				Skin Sens. 1 (H317)				
Octamethylcyclotetra	0.036 - <		209-136-7	Repr. 2 (H361f)	-	-	10	-
siloxane [D4]	0.05	-36-XXXX	(014-018-00-1)					
556-67-2				(H410)				
				Flam. Liq. 3 (H226)				
				[G]				
2-octyl-2H-isothiazol		No data		Acute Tox. 3 (H301)		100	100	-
-3-one [OIT]	<0.01	available	(613-112-00-5)	Acute Tox. 3 (H311)				
26530-20-1				Acute Tox. 2 (H330)	C>=0.0015%			

Ireland - BE Page 2 / 17

# EVO-STIK SILICONE C SEALANT GREY Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

	Skin Corr. 1B		
	(H314)		
	Eye Dam 1 (H318)		
	Skin Sens. 1A		
	(H317)		
	Aquatic Acute 1		
	(H400)		
	Aquatic Chronic 1		
	(H410)		
	(EUH071)		

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

- [B] Substance with a Community workplace exposure limit
- [C] Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring
- [G] PBT / vPvB substance

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 μm.

#### Full text of H- and EUH-phrases: see section 16

#### Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
2-Pentanone oxime 623-40-5	484-470-6	Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT RE 2 (H373) Aquatic Chronic 3 (H412)	-	-	-	01-2119980079- 27-XXXX
Ethanol 64-17-5	200-578-6 (603-002-00-5)	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-2119457610- 43-XXXX
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

Ireland - BE Page 3 / 17

**EVO-STIK SILICONE C SEALANT GREY** 

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

#### **Acute Toxicity Estimate**

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	932-078-5	RR-100254-6	-	-	-	-	1
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-
2-Pentandione, O,O',O"-(methylsilylidy ne)trioxime	484-460-1	37859-55-5	1234	-	-	-	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
3-aminopropyltriethoxy silane	213-048-4 (612-108-00-0)	919-30-2	1490	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
2-octyl-2H-isothiazol-3- one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125+	311+	0.27+	0.27+	0.27+

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

**Inhalation** Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

**Skin contact**Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

Effects of Exposure No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

#### **SECTION 5: Firefighting measures**

Ireland - BE Page 4 / 17

**EVO-STIK SILICONE C SEALANT GREY** 

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead

to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

Take up mechanically, placing in appropriate containers for disposal. Methods for cleaning up

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

#### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a cool, well-ventilated place. Keep away from food. **Storage Conditions** 

drink and animal feedingstuffs. Protect from moisture.

Keep at temperatures between 10 and 35 °C. Recommended storage

Ireland - BE Page 5 / 17

# EVO-STIK SILICONE C SEALANT GREY Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

#### temperature

#### 7.3. Specific end use(s)

#### Specific use(s)

Building and construction work. Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Exposure Limits** 

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

Chemical name	European Union	Ireland	United Kingdom
Limestone	-	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
1317-65-3		TWA: 4 mg/m <sup>3</sup>	TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>	STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>	STEL: 12 mg/m <sup>3</sup>
Silica, amorphous	-	TWA: 6 mg/m <sup>3</sup>	TWA: 6 mg/m <sup>3</sup>
7631-86-9		TWA: 2.4 mg/m <sup>3</sup>	TWA: 2.4 mg/m <sup>3</sup>
		STEL: 18 mg/m <sup>3</sup>	STEL: 18 mg/m <sup>3</sup>
		STEL: 7.2 mg/m <sup>3</sup>	STEL: 7.2 mg/m <sup>3</sup>
Ethanol	_	STEL: 1000 ppm	TWA: 1000 ppm
64-17-5		1	TWA: 1920 mg/m <sup>3</sup>
			STEL: 3000 ppm
			STEL: 5760 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>	TWA: 260 mg/m <sup>3</sup>	TWA: 266 mg/m <sup>3</sup>
	*	STEL: 600 ppm	STEL: 250 ppm
		STEL: 780 mg/m <sup>3</sup>	STEL: 333 mg/m <sup>3</sup>
		Sk*	Sk*
Titanium dioxide	-	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
13463-67-7		TWA: 4 mg/m <sup>3</sup>	TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>	STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>	STEL: 12 mg/m <sup>3</sup>

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Titanium dioxide (13463-67	7-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Local health effects	Inhalation	10 mg/m³		

3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m³	
worker Short term Systemic health effects	Inhalation	59 mg/m³	
worker	Dermal	8.3 mg/kg bw/d	

Ireland - BE Page 6 / 17

# EVO-STIK SILICONE C SEALANT GREY Supercedes date 20-May-2022

Consumer

Short term

Consumer

Long term

Consumer

Short term

Systemic health effects

Systemic health effects

Systemic health effects

Revision date 26-Oct-2023 Revision Number 2.01

Long term Systemic health effects			
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	
Octamethylcyclotetrasiloxai	ne ID41 (556-67-2)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m³	
Derived No Effect Level (DN	EI \		
	<u>LL)</u>		
Titanium dioxide (13463-67-		Derived No Effect Level (DNEL)	Safety factor
Titanium dioxide (13463-67- Type  Consumer Long term	7)		Safety factor
Titanium dioxide (13463-67- Type  Consumer  Long term  Systemic health effects	Exposure route Oral	(DNEL)	Safety factor
Titanium dioxide (13463-67- Type  Consumer  Long term  Systemic health effects  3-aminopropyltriethoxysilar	Exposure route Oral  lee (919-30-2)	(DNEL) 700 mg/kg bw/d	·
Titanium dioxide (13463-67- Type  Consumer	Exposure route Oral	(DNEL)	Safety factor  Safety factor

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Inhalation	13 mg/m³	
Systemic health effects			
Consumer	Oral	3.7 mg/kg bw/d	
Long term			
Systemic health effects			

17.4 mg/m<sup>3</sup>

5 mg/kg bw/d

5 mg/kg bw/d

# **Predicted No Effect Concentration** No information available. **(PNEC)**

Inhalation

Dermal

Dermal

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l

Ireland - BE Page 7 / 17

#### **EVO-STIK SILICONE C SEALANT GREY**

Supercedes date 20-May-2022

Revision date 26-Oct-2023 **Revision Number** 2.01

preshwater - intermittent	Freshwater - intermittent	0.193 mg/l
---------------------------	---------------------------	------------

3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	0.0015 mg/l				
Marine water	0.00015 mg/l				
Freshwater sediment	3 mg/kg				
Marine sediment	0.3 mg/kg				
Soil	0.54 mg/kg				
Sewage treatment plant	10 mg/l				

#### 8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. **Engineering controls** 

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166

Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber. Hand protection

> Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

None under normal use conditions. Skin and body protection

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

#### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

**Physical state** Solid Appearance Paste Colour Grev

Odour Characteristic.

Values Remarks • Method Property

Melting point / freezing point No data available None known

Initial boiling point and boiling No data available None known

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point > 100 °C None known **Autoignition temperature** No data available None known

**Decomposition temperature** 

None known No data available Not applicable. Insoluble in water.

pH (as aqueous solution) No data available None known Kinematic viscosity > 20.6 None known

**Dynamic viscosity** No data available

Water solubility No data available. None known

Ireland - BE Page 8 / 17

#### **EVO-STIK SILICONE C SEALANT GREY**

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Bulk density No data available

Liquid Density 1.02

Relative vapour density No data available None known

**Particle characteristics** 

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** Product cures with moisture.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

**Incompatible materials** Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released

upon curing.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Ireland - BE Page 9 / 17

### EVO-STIK SILICONE C SEALANT GREY

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

#### **Product Information**

**Inhalation** Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

**Skin contact** May cause sensitisation in susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Acute toxicity

#### **Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 54,194.50 mg/kg
ATEmix (dermal) 87,879.40 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

#### **Component Information**

Chemical name	Chemical name Oral LD50		Inhalation LC50
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics,	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (Oryctolagus cuniculus)	-
< 0.03% aromatics	7000 (D-41)	OECD 402	0.0// /D-# \ 4  -
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
2-Pentandione, O,O',O"-(methylsilylidyne)trioxi me	LD50 =1234 mg/kg bw (Rattus)(OECD guideline 425)	LD50 > 2000 mg/kg (Rattus) EU Method B.3	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rattus, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rattus, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rattus (Vapour)
Octamethylcyclotetrasiloxane LD50 > 4800 mg/kg (R [D4] OECD 401		LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m³ (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	ctyl-2H-isothiazol-3-one =125 mg/kg (Rattus)		-

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 404:	Rabbit	Dermal			Non-irritant	
Acute Dermal						
Irritation/Corrosion						

Ireland - BE Page 10 / 17

### **EVO-STIK SILICONE C SEALANT GREY**

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 404:	Rabbit	Dermal			Corrosive	
Acute Dermal						
Irritation/Corrosion						

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)								
Method	Species	Exposure route	Effective dose	Exposure time	Results			
OECD Test No. 405:	Rabbit	Eye			Non-irritant			
Acute Eye								
Irritation/Corrosion								

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 405:	Rabbit	Corneal			Eye Damage	
Acute Eye						
Irritation/Corrosion						

Respiratory or skin sensitisation

No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Titanium dioxide (13463-67-7)					
Octamethylcyclotetrasiloxane [D4] (556-67-2)					
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)					
Method	Species	Exposure route	Results		
GPMT - Guinea pig maximisation	Guinea pig	Dermal	Sensitising		
test					

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide	Carc. 2

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Ireland - BE Page 11 / 17

EVO-STIK SILICONE C SEALANT GREY

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

**Aspiration hazard** 

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

11.2.2. Other information

Other adverse effects No information available.

### SECTION 12: Ecological information

12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100254-6	EL50 (72h) > 10 000 mg/L (Skeletonema costatum)	LL50 (96h) > 1028 mg/L (Scophthalmus maximus)	-	LL50 (48h) > > 3193 mg/l (Acartia tonsa)		
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneri ella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
O,O',O"-(methylsilylidy ne)trioxime	EC50 (72h) = 88 mg/L (Pseudokirchner iella subcapitata) OECD 201	mg/L (Oncorhynchus	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD guideline 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
3-aminopropyltriethoxy silane 919-30-2	>1000 mg/Ĺ Green algae	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)		EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Octamethylcyclotetrasil oxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

Ireland - BE Page 12 / 17

### **EVO-STIK SILICONE C SEALANT GREY**

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

#### 12.2. Persistence and degradability

Persistence and degradability No information available.

Silica, amorphous (7631-86-9)					
Method	Exposure time	Value	Results		
			The methods for determining biodegradability are not applicable to inorganic substances		

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)				
Method	Exposure time	Value	Results	
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable	
Mineralization in Surface Water -				
Simulation Biodegradation Test				

#### 12.3. Bioaccumulative potential

#### **Bioaccumulation**

**Component Information** 

Chemical name	Partition coefficient	
2-Pentandione, O,O',O"-(methylsilylidyne)trioxime	1.25	
3-aminopropyltriethoxysilane	1.7	
Octamethylcyclotetrasiloxane [D4]	6.49	
2-octyl-2H-isothiazol-3-one [OIT]	2.92	

### 12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Silica, amorphous	The substance is not PBT / vPvB	
2-Pentandione, O,O',O"-(methylsilylidyne)trioxime	The substance is not PBT / vPvB	
Titanium dioxide	The substance is not PBT / vPvB	
3-aminopropyltriethoxysilane	The substance is not PBT / vPvB	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB	

#### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance	Negative.	
with the criteria set out in Commission		
Delegated Regulation (EU) 2017/2100(3) or		
Commission Regulation (EU) 2018/605(4).		

#### 12.7. Other adverse effects

No information available.

Ireland - BE Page 13 / 17

**EVO-STIK SILICONE C SEALANT GREY** 

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

**Contaminated packaging** Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

### **SECTION 14: Transport information**

Land transport (ADR/RID)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group

Not regulated
Not regulated
Not regulated
Not regulated

14.5 Marine pollutant NP14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user Special Provisions None

#### Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**European Union** 

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

**SVHC: Substances of Very High Concern for Authorisation:** 

Ireland - BE Page 14 / 17

#### **EVO-STIK SILICONE C SEALANT GREY**

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No.	
Toluene	108-88-3	
Dibutyltin diacetate	1067-33-0	
Methyl alcohol	67-56-1	
2-octyl-2H-isothiazol-3-one [OIT]	26530-20-1	

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film. Contains: 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

#### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

#### Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

# REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

#### **National regulations**

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

#### SECTION 16: Other information

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H226 - Flammable liquid and vapour

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H330 - Fatal if inhaled

Ireland - BE Page 15 / 17

EVO-STIK SILICONE C SEALANT GREY

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

### Notes relating to the identification, classification and labelling of substances

Note V - If the substance is to be placed on the market as fibres (with diameter <  $3 \mu m$ , length >  $5 \mu m$  and aspect ratio  $\geq 3.1$ ) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation

#### Notes relating to the classification and labelling of mixtures

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

#### Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value Sk\* Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

#### Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)

European Chemicals Agency (ECHA) (ECHA\_API)

Environmental Protection Agency

Ireland - BE Page 16 / 17

### **EVO-STIK SILICONE C SEALANT GREY**

Supercedes date 20-May-2022

Revision date 26-Oct-2023 Revision Number 2.01

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 26-Oct-2023

Revision Note SDS sections updated 1

Training Advice No information available

Further information No information available

#### Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Ireland - BE Page 17 / 17