



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK FAST ACT SILICONE REMOVER

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cleaning agent

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik GmbH
Niederlassung Schwepnitz
Industriestraße 1-7
D-01936 Schwepnitz
Germany
Tel. +49 (0)35797 646 0
Fax +49 (0)35797 646 190

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland NPIC - National Poison Information Centre
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to
Regulation (EC) No. 1272/2008
[CLP]

Skin corrosion/irritation	Category 1 Sub-category C - (H314)
Serious eye damage/eye irritation	Category 1 - (H318)
Flammable liquids	Category 3 - (H226)

2.2. Label elements

Contains Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01



Signal word
Danger

Hazard statements
H314 - Causes severe skin burns and eye damage
H226 - Flammable liquid and vapour

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe vapour
P280 - Wear protective gloves and eye protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P370 + P378 - In case of fire: Use dry chemical, CO₂, water spray or alcohol-resistant foam to extinguish
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Harmful to aquatic life. In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Hydrocarbons, C11-C12, isoalkanes <2% aromatics 40 - <80 %	918-167-1	RR-99779-5	Asp. Tox. 1 (H304) (EUH066) Flam. Liq. 3 (H226)	-	-	-	01-2119472146-39-XXXX
Benzenesulfonic acid,	287-494-3	85536-14-7	Skin Corr. 1C (H314)	-	-	-	01-2119490234-

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

4-C10-13-sec-alkyl derivatives 10 - <20 %			Acute Tox. 4 (H302) Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)				40-XXXX
Isopropyl alcohol 0.1 - <1 %	200-661-7 (603-117-00-0)	67-63-0	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	-	-	01-2119457558-25-XXXX
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides 0.1 - <1 %	263-081-3	61789-72-8	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 4 (H302) Aquatic Acute 1 (H400)	-	-	-	01-2119970169-28-XXXX
Methyl ethyl ketone 0.1 - <0.3 %	201-159-0 (606-002-00-3)	78-93-3	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	01-2119457290-43-XXXX

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C11-C12, isoalkanes <2% aromatics	918-167-1	RR-99779-5	-	-	-	-	-
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	287-494-3	85536-14-7	1219	-	-	-	-
Isopropyl alcohol	200-661-7 (603-117-00-0)	67-63-0	-	-	-	-	-
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides	263-081-3	61789-72-8	500	-	-	-	-
Methyl ethyl ketone	201-159-0 (606-002-00-3)	78-93-3	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

If medical advice is needed, have product container or label at hand.

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Inhalation	Remove to fresh air. Get immediate medical attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical attention.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor or poison control centre immediately.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Product is a corrosive material. Use of gastric lavage or emesis is contra-indicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.
------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.
Hazardous combustion products	Carbon oxides.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
-----------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not breathe vapour or mist. Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges.
-----------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. Refer to protective measures listed in Sections 7 and 8.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure adequate ventilation. Use with local exhaust ventilation. Do not breathe vapour or mist. Use personal protection equipment. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store in accordance with the particular national regulations. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)
Cleaning agent.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supercedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Chemical name	European Union	Ireland	United Kingdom
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³
Isopropyl alcohol 67-63-0	-	TWA: 200 ppm STEL: 400 ppm Sk*	TWA: 400 ppm TWA: 999 mg/m ³ STEL: 500 ppm STEL: 1250 mg/m ³
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ Sk*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Isopropyl alcohol (67-63-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	500 mg/m ³	
worker Long term Systemic health effects	Dermal	888 mg/kg bw/d	

Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m ³	

Derived No Effect Level (DNEL)			
Isopropyl alcohol (67-63-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	89 mg/m ³	
Consumer Long term Systemic health effects	Dermal	319 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m ³	

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	
-------------------------------------------------------------	------	---------------	--

Predicted No Effect Concentration (PNEC) No information available.
(PNEC)

Predicted No Effect Concentration (PNEC)	
Isopropyl alcohol (67-63-0)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	140.9 mg/l
Marine water	140.9 mg/l
Sewage treatment plant	2251 mg/l
Freshwater sediment	552 mg/kg dry weight
Marine sediment	552 mg/kg dry weight
Soil	28 mg/kg dry weight

Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

8.2. Exposure controls

Engineering controls Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Hand protection

Face protection shield. Goggles. Eye protection must conform to standard EN 166
Wear suitable gloves. Recommended Use: Nitrile rubber. Glove thickness > 0.7mm.
Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. 30 minutes. Gloves must conform to standard EN 374

Skin and body protection

Respiratory protection

Wear suitable protective clothing.
In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Wear a respirator conforming to EN 140 with Type A filter or better.

Recommended filter type:

Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Viscous
Colour	Brown
Odour	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	-25 °C	None known
Initial boiling point and boiling range	36 °C	
Flammability	No data available	Flammable liquid
Flammability Limit in Air		None known
Upper flammability or explosive limits	6.5 Vol. %	

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Lower flammability or explosive limits	0.7 Vol.%	
Flash point	<= 60 °C	
Autoignition temperature	~310 °C	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm ² /s	@ 40°C
Dynamic viscosity	140000 mPa s	
Water solubility	Insoluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	< 1100	hPa @ 50 °C
Relative density	0.80 - 0.82	
Bulk density	No data available	
Liquid Density	0.81 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under recommended storage conditions.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

10.5. Incompatible materials

Incompatible materials Acids. Bases. Oxidising agent.

10.6. Hazardous decomposition products

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Causes serious eye damage.
Skin contact	Causes severe burns.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	9,865.80 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C11-C12, isoalkanes <2% aromatics	LD50 >5000mg/Kg (Rattus)	LC50 >5000 mg/Kg (Oryctolagus cuniculus) (OECD 402)	LC50 >5000 mg/m ³ (Rattus) (OECD 403)
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	=1219 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus cuniculus)	=72600 mg/m ³ (Rattus) 4 h
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Causes serious eye damage. Causes burns.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye	Rabbit	eye			Irritant

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
 Supersedes date 15-May-2024

Revision date 13-Aug-2024
 Revision Number 2.01

Irritation/Corrosion					
----------------------	--	--	--	--	--

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information
 Isopropyl alcohol (67-63-0)

Method	Species	Results
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes	Hamster, in vitro	Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	EC50: =36mg/L (72h, Desmodesmus)	LC50: =5.6mg/L (96h, Cyprinus carpio)	-	EC50: =5.2mg/L (48h, Daphnia magna)		

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

85536-14-7	subspicatus)					
Isopropyl alcohol 67-63-0	EC50 72 h > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1400000 ?g/L (Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)		
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchner iella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	2.2
Isopropyl alcohol	0.05
Methyl ethyl ketone	0.3

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C11-C12, isoalkanes <2% aromatics	The substance is not PBT / vPvB
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	The substance is not PBT / vPvB
Isopropyl alcohol	The substance is not PBT / vPvB
Methyl ethyl ketone	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable. Should not be released into the environment.

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Contaminated packaging	Handle contaminated packages in the same way as the product itself. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	UN2924
14.2 UN proper shipping name	Flammable liquid, corrosive, n.o.s (Hydrocarbons, C11-C12, isoalkanes <2% aromatics, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives)
14.3 Transport hazard class(es)	3
Labels	3 + 8
14.4 Packing group	III
Description	UN2924, Flammable liquid, corrosive, n.o.s (Hydrocarbons, C11-C12, isoalkanes <2% aromatics, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives), 3 (8), III, (D/E)
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	274
Classification code	FC
Tunnel restriction code	(D/E)
Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	38

IMDG

14.1 UN number or ID number	UN2924
14.2 UN proper shipping name	Flammable liquid, corrosive, n.o.s (Hydrocarbons, C11-C12, isoalkanes <2% aromatics, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives)
14.3 Transport hazard class(es)	3
Subsidiary hazard class	8
14.4 Packing group	III
Description	UN2924, Flammable liquid, corrosive, n.o.s (Hydrocarbons, C11-C12, isoalkanes <2% aromatics, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives), 3 (8), III, (60°C c.c.)
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	223, 274
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-C
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN2924
14.2 UN proper shipping name	Flammable liquid, corrosive, n.o.s (Hydrocarbons, C11-C12, isoalkanes <2% aromatics, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives)
14.3 Transport hazard class(es)	3
Subsidiary hazard class	8
14.4 Packing group	III
Description	UN2924, Flammable liquid, corrosive, n.o.s (Hydrocarbons, C11-C12, isoalkanes <2% aromatics, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives), 3 (8), III
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	A3, A803
Limited quantity (LQ)	1 L

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

ERG Code

3C

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulation (EC) No. 648/2004 (Detergents regulation)

Labelling for contents according to regulation (EC) No. 648/2004

aliphatic hydrocarbons	$\geq 30\%$
anionic surfactants	5 - < 15%

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

cationic surfactants	< 5%
Isopropyl alcohol	< 5%

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H400 - Very toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method

SAFETY DATA SHEET

EVO-STIK FAST ACT SILICONE REMOVER
Supersedes date 15-May-2024

Revision date 13-Aug-2024
Revision Number 2.01

Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs
Revision date 13-Aug-2024
Revision note SDS sections updated 3, 16
Training Advice When working with hazardous materials, regular training of operators is required by law
Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet