



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**EVO-STIK TECH SGS GROUT GREY**  
Supersedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** EVO-STIK TECH SGS GROUT GREY  
**Substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Cement Building and construction work  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**GB CLP (SI 2020/1567 as amended)**

<b>Skin irritation</b>	Category 2 - (H315)
<b>Serious eye damage</b>	Category 1 - (H318)
<b>Skin sensitisation</b>	Category 1 - (H317)
<b>Specific target organ toxicity (single exposure)</b>	Category 3 - (H335)
Category 3 Target organ effects: Respiratory irritation.	

### 2.2. Label elements

Contains Portland Cement



# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supercedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

## Signal word

Danger

## Hazard statements

H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H335 - May cause respiratory irritation.

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves, eye protection and face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER or doctor if you feel unwell  
P315 - Get immediate medical advice/attention  
P337 + P313 - If eye irritation persists: Get medical advice/attention  
P362 + P364 - Take off contaminated clothing and wash it before reuse  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight). If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the present reducing agent can diminish prematurely, and the cement/binder can become skin sensitizing (H317 or EUH203, respectively).

## 2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking. Material becomes extremely slippery when wet.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Quartz 14808-60-7	40 - <80	[5]	238-878-4	[B]	-	-	-	-
Portland Cement 65997-15-1	>25 - <40	[5]	266-043-4	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	-	-	-

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supercedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

Cement, alumina, chemicals 65997-16-2	1 - <2.5	No data available	266-045-5	Eye Irrit. 2 (H319)	-	-	-	-
--	----------	-------------------	-----------	---------------------	---	---	---	---

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(b) and Annex V of REACH Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

Full text of H- and EUH-phrases: see section 16

## Acute Toxicity Estimate

No information available

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Quartz	238-878-4	14808-60-7	-	-	-	-	-
Portland Cement	266-043-4	65997-15-1	-	-	-	-	-
Cement, alumina, chemicals	266-045-5	65997-16-2	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Take a copy of the Safety Data Sheet when going for medical treatment.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash it before reuse.
<b>Ingestion</b>	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Burning sensation. May cause blindness. May cause redness and tearing of the eyes. Itching. Rashes. Hives. Erythema (skin redness). Dust irritates eyes and air passages. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.
-----------------	--

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supercedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

**Effects of Exposure** No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** May cause sensitisation in susceptible persons. Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Product is or contains a sensitiser. May cause sensitisation by skin contact.

**Hazardous combustion products** Sulphur oxides.

#### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

#### 6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil.

#### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.

**Methods for cleaning up** Process mortar residues to let them harden, before returning the residues to recycling or disposing them according to applicable requirements. Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.

**Prevention of secondary hazards** Collect water from cleaning tools and reuse it or dispose it in local sewage systems. Do not spill water or dispose cleaning water into the environment.

#### 6.4. Reference to other sections

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supercedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Avoid generation of dust. Use personal protective equipment. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. For cements treated with a Cr (VI) reducing agent the effectiveness of the reducing agent diminishes with time and if not stored in an appropriate manner. After absorption of moisture or exceeding the shelf life the reducing agent for chromate will lose its efficiency and sensitisation by skin contact may occur.

### 7.3. Specific end use(s)

**Specific use(s)**  
Building and construction work. Cement.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m <sup>3</sup> ;	TWA: 0.1 mg/m <sup>3</sup> ; respirable fraction STEL: 0.3 mg/m <sup>3</sup> ; respirable
Portland Cement 65997-15-1	-	TWA: 10 mg/m <sup>3</sup> ; inhalable dust TWA: 4 mg/m <sup>3</sup> ; respirable dust STEL: 30 mg/m <sup>3</sup> ; inhalable dust STEL: 12 mg/m <sup>3</sup> ; respirable dust
Dust RR-12364-8	-	TWA: 10 mg/m <sup>3</sup> ; inhalable dust TWA: 4 mg/m <sup>3</sup> ; respirable dust STEL: 30 mg/m <sup>3</sup> ; inhalable dust STEL: 12 mg/m <sup>3</sup> ; respirable dust

**Derived No Effect Level (DNEL)** No information available

**Predicted No Effect Concentration (PNEC)**

### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supersedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

## Personal protective equipment

<b>Eye/face protection</b>	Tight sealing safety goggles. Face protection shield. Wear safety glasses with side shields (or goggles).
<b>Hand protection</b>	Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Gloves must conform to standard EN 374. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
<b>Skin and body protection</b>	Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.
<b>Respiratory protection</b>	Avoid generation of dust. In case of insufficient ventilation, wear suitable respiratory equipment. Possible nuisance dust. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	black. with filter for particulates. Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Powder
<b>Colour</b>	Grey
<b>Odour</b>	Cement.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	. °C	Not applicable
<b>Initial boiling point and boiling range</b>	No data available	Not applicable
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	No data available	Not applicable
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	11 - 14	
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	. mm <sup>2</sup> /s	Not applicable
<b>Dynamic viscosity</b>	.	Not applicable
<b>Water solubility</b>	No data available. Cement based products react and solidify in contact with water	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk density</b>	1.1 g/cm <sup>3</sup>	
<b>Density</b>	No data available	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supercedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

## 9.2. Other information

Solid content (%)	100	
Softening point	Not applicable	
VOC content		No data available

### **9.2.1. Information with regards to physical hazard classes**

Not applicable

### **9.2.2. Other safety characteristics**

No information available . Not applicable

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reactivity Product cures with moisture.

### 10.2. Chemical stability

Stability Keep away from Incompatible materials. Stable under recommended storage conditions.

### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Product cures with moisture.

### 10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage.
Skin contact	Specific test data for the substance or mixture is not available. May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supersedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

## Acute toxicity

### Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg  
ATEmix (dermal) >2000 mg/kg  
ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) >5 mg/L  
ATEmix (inhalation-vapour) >20 mg/L

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Portland Cement	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
Cement, alumina, chemicals	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rattus	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

**Respiratory or skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause respiratory irritation.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supersedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** Based on available data, the classification criteria are not met.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Cement, alumina, chemicals 65997-16-2	EC50 (72h)Algae (Pseudokirchneriella subcapitata) >5.6mg/L	LC50 (96h) (Onchorhyncus mykiss) >100 mg/L (OECD 203)	-	EC50 (48h) Daphnia magna =6.6mg/L (OECD 202)		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Cement, alumina, chemicals	Not PBT/vPvB

### 12.6. Endocrine disrupting properties

**Endocrine disruption for the environment** Based on available data, the classification criteria are not met.

### 12.7. Other adverse effects

**Other adverse effects** No information available.

**PMT or vPvM properties** Based on available data, the classification criteria are not met.

## SECTION 13: Disposal considerations

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supersedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

## 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
<b>Contaminated packaging</b>	Do not reuse empty containers.
<b>European Waste Catalogue</b>	17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03 10 13 06 particulates and dust (except 10 13 12 and 10 13 13) Cured product can be treated as construction waste. In the management of larger quantities consult with local authorities and local waste disposal company 10 13 14 waste concrete and concrete sludge
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supercedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## **Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)**

### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	47

**47** where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

### **Ozone-depleting substances (ODS) regulation (EC) 2024/590**

Not applicable

### **Persistent Organic Pollutants**

Not applicable

### **REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**

Not applicable

### **Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)**

This product does not contain any substance(s) on the Drug Precursors list.

### **National regulations**

#### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

# SAFETY DATA SHEET

EVO-STIK TECH SGS GROUT GREY  
Supersedes date 06-Jul-2023

Revision date 25-Jun-2026  
Revision Number 1.02

## Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation

### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

### Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 25-Jun-2026

### Indication of changes

**Revision Note** SDS sections updated, 3, 4, 5, 6, 7, 8, 10, 13.  
**Training Advice** No information available  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**