

Due due (identifier

SAFETY DATA SHEET

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Product Name	BOSTIK ALL WEATHER TROWEL BITUMINOUS	MASTIC
Pure substance/mixture	Mixture	
1.2. Relevant identified uses of the	substance or mixture and uses advised against	
Recommended use	Adhesives	
Uses advised against	None known	
1.3. Details of the supplier of the same	afety data sheet	
Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36		
E-mail address	SDS.box-EU@bostik.com	
1.4. Emergency telephone number	_	
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111	
SECTION 2: Hazards identifi	cation	
2.1. Classification of the substance	e or mixture	
GB CLP (SI 2020/1567 as amended)		
Specific target organ toxicity — re	peated exposure	Category 1 - (H372)
Chronic aquatic toxicity		Category 3 - (H412)
Flammable liquids		Category 3 - (H226)

2.2. Label elements

Contains Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)



Signal word Danger

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

Hazard statements

H372 - Causes damage to organs through prolonged or repeated exposure. H412 - Harmful to aquatic life with long lasting effects. H226 - Flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

- P102 Keep out of reach of children
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P260 Do not breathe dust/fume/gas/mist/vapours/spray
- P273 Avoid release to the environment
- P370 + P378 In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish
- P403 + P235 Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Harmful to aquatic life. In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	10 - <20	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)	-	01-2119458049- 33-XXXX
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	919-006-8	RR-108191-0	10 - <20	Asp. Tox. 1 (H304) Aquatic Chronic 4 (H413) (EUH066)	-	01-2119455996- 19-xxxx
Quaternary ammonium compounds,	269-924-1	68391-05-9	0.1- <1	Skin Corr. 1B (H314)	-	01-2119486994- 16-xxxx

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

di-C12-18-alkyldimethyl, chlorides				Eye Dam. 1 (H318) Acute Tox. 4 (H302) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)		
Isopropyl alcohol	(603-117-00- 0) 200-661-7	67-63-0	0.1- <1	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119457558- 25-XXXX

Full text of H- and EUH-phrases: see section 16

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.			
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.			
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.			
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.			
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.			
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.			
4.2. Most important symptoms an	d effects, both acute and delayed			
Symptoms	No information available.			
4.3. Indication of any immediate n	nedical attention and special treatment needed			
Note to doctors	No information available.			
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable Extinguishing Modia	Dry chamical Carbon diavide (CO2) Water array Alashal registrant form			

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

No information available.

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 14-Oct-2022

Unsuitable extinguishing media

Revision date 24-Aug-2023 Revision Number 2.03

5.2. Special hazards arising from t	he substance or mixture
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides.
5.3. Advice for firefighters	
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, protecti	ive equipment and emergency procedures
Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
6.3. Methods and material for cont	ainment and cleaning up
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC Supercedes Date: 14-Oct-2022

	this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
Recommended storage temperature	Keep at temperatures between 5 and 25 °C.
7.3. Specific end use(s)	
Specific use(s) Adhesives.	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics,	-	TWA: 350 mg/m ³
aromatics (2-25%)		
RR-91855-8		
Isopropyl alcohol	-	TWA: 400 ppm
67-63-0		TWA: 999 mg/m ³
		STEL: 500 ppm
		STEL: 1250 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
Isopropyl alcohol	-	40 mg/L (urine - Acetone end of	-
67-63-0		shift at end of workweek)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker	Inhalation	330 mg/m³		
Long term				
Systemic health effects				
worker	Dermal	44 mg/kg bw/d		

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 14-Oct-2022

Long term Systemic health effects		
--------------------------------------	--	--

Isopropyl alcohol (67-63-0)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	500 mg/m³		
worker Long term Systemic health effects	Dermal	888 mg/kg bw/d		

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-al	kanes, isoalkanes, cyclics, a	aromatics (2-25%) (RR-91855-8)	
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	71 mg/m³	
Consumer Long term Systemic health effects	Dermal	26 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

Isopropyl alcohol (67-63-0)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	89 mg/m³	
Consumer Long term Systemic health effects	Dermal	319 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)		
Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides (68391-05-9)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	13 µg/l	
Marine water	1.3 µg/l	
Sewage treatment plant	1.2 mg/l	
Freshwater sediment	5.5 mg/kg dry weight	
Marine sediment	0.55 mg/kg dry weight	
Soil	1.4 mg/kg dry weight	

Isopropyl alcohol (67-63-0)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	140.9 mg/l
Marine water	140.9 mg/l
Sewage treatment plant	2251 mg/l
Freshwater sediment	552 mg/kg dry weight

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

Marine sediment	552 mg/kg dry weight
Soil	28 mg/kg dry weight
8.2. Exposure controls	
Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment Eye/face protection Hand protection	Tight sealing safety goggles. Wear protective gloves. Gloves must conform to standard EN 374. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.
Skin and body protection	Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical propertiesPhysical stateLiquid

Appearance	Paste	
Colour	Black	
Odour	Slight.	
Dronorty	Values	Demorika - Mathad
Property Molting point (freezing point	<u>Values</u> No data available	<u>Remarks • Method</u> None known
Melting point / freezing point	>= 153 °C	NOTE KTOWIT
Initial boiling point and boiling	>= 153 C	
range Flammability	Not applicable for liquids	
Flammability Limit in Air	Not applicable for liquids	None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	> 39 °C	
Autoignition temperature	200°C	
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 1000 mm²/s	@ 40°C
Dynamic viscosity	No data available	
Water solubility	Insoluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	1	No data available

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 14-Oct-2022

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity		
10.1. Reactivity		
Reactivity	No information available.	
10.2. Chemical stability		
Stability	Stable under normal conditions.	
Explosion data		
Sensitivity to mechanical impact	None.	
Sensitivity to static discharge	Yes.	
10.3. Possibility of hazardous reac	tions	
Possibility of hazardous reactions	None under normal processing.	
10.4. Conditions to avoid		
Conditions to avoid	Heat, flames and sparks.	
10.5. Incompatible materials		
Incompatible materials	None known based on information supplied.	
10.6. Hazardous decomposition products		
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.	
SECTION 11: Toxicological i	nformation	
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008	
Information on likely routes of exp	osure	
Product Information		
Inhalation	Based on available data, the classification criteria are not met.	
Eye contact	Based on available data, the classification criteria are not met.	
Skin contact	Based on available data, the classification criteria are not met.	
Ingestion	Based on available data, the classification criteria are not met.	
Symptoms related to the physical, chemical and toxicological characteristics		
Symptoms	No information available.	
Acute toxicity		

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50 >15000 mg/Kg (Rattus) OECD 401	LD50 > 3400 mg/kg (Rattus) OECD 402	LC50 (4hrs) >13.1 mg/l (Rattus)
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	LD50 >4150 mg/kg bw (Rattus) (OECD 423 Guideline)Read across	LD50 > 2000 mg/kg Read Across)	-
Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides	= 750 mg/kg (Rattus) (OECD 401)	-	= 0.22 mg/L (Rat)4 h = 0.28 mg/L (Rat)4 h
Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus cuniculus)	=72600 mg/m ³ (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			Irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Isopropyl alcohol (67-63-0)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		No sensitisation responses
Sensitisation			were observed

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information Isopropyl alcohol (67-63-0)		
Method	Species	Results
OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Hamster, in vitro	Not mutagenic

Carcinogenicity

Based on available data, the classification criteria are not met.

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

Reproductive toxicity	Based on available data, the classification criteria are not met.	
STOT - single exposure	Based on available data, the classification criteria are not met.	
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard	Based on available data, the classification criteria are not met.	
11.2. Information on other hazards		
11.2.1. Endocrine disrupting properties		
Endocrine disrupting properties	No information available.	
11.2.2. Other information		
Other adverse effects	No information available.	

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	mg/l (Pseudokirchner ella subcapitata)	mg/l (Oncorhynchus	-	EL50 48hr 10-30mg/l (daphnia magna)		
RR-91855-8 Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %) RR-108191-0	OECD 401 -	LL50 (96hr) >1000 mg/kg (Oncorhynchus mykiss) Semi static (Read across)	-	ECo (48hr) >1000mg/L Daphnia magna (OECD 202 guideline) Read across		
Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides 68391-05-9	-	LC50: =0.66mg/L (96h, Danio rerio) LC50: =0.26mg/L (96h, Danio rerio)		-		
Isopropyl alcohol 67-63-0	EC50 72 h > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1400000 ?g/L (Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

	(al # a a a # la a # a a	CO C10		in a all ran a a	a valiaa		$(\cap \cap \Box \cap ())$	(RR-91855-8)	
- H\	/drocarbons	1.9-1.17	n-alkanes	ISOAIKADAS	CVCIICS	aromatics	12-25%	188-91855-81	
	, ai obai boi io,	00 012,	n unanoo,	ioountarioo,	0,0100,	aronnatioo	(2 20 /0)	(111 01000 0)	

Method Exposure time Value Results	
------------------------------------	--

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 14-Oct-2022

28 days	biodegradation	74.7 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Quaternary ammonium compounds, di-C12-18-alkyldimethyl,	4.8
chlorides	
Isopropyl alcohol	0.05

12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	The substance is not PBT / vPvB
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	The substance is not PBT / vPvB
Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides	The substance is not PBT / vPvB
Isopropyl alcohol	The substance is not PBT / vPvB PBT assessment does
	not apply

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	17 03 02 bituminous mixtures other than those mentioned in 17 03 01 15 01 10*: Packaging containing residues of or contaminated by dangerous substances 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC Supercedes Date: 14-Oct-2022 Revision date 24-Aug-2023 Revision Number 2.03

Note:	The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.
 Land transport (ADR/RID) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) Labels 14.4 Packing group Description 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions Classification code Tunnel restriction code Limited quantity (LQ) ADR Hazard Id (Kemmler Number) 	UN1133 Adhesives 3 3 III UN1133, Adhesives, 3, III, (D/E) Not applicable None F1 (D/E) 5 L 30
 IMDG 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group Description 14.5 Marine pollutant 14.6 Special precautions for user Special Provisions Limited Quantity (LQ) EmS-No. 14.7 Maritime transport in bulk according to IMO instruments Transport in bulk according to 	UN1133 Adhesives 3 III UN1133, Adhesives, 3, III, (39°C c.c.) NP 223, 955 5 L F-E, S-D Annex II of MARPOL and the IBC Code Not applicable
 <u>Air transport (ICAO-TI / IATA-DGR</u> 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group Description 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions Limited quantity (LQ) ERG Code 	UN1133 Adhesives 3 III UN1133, Adhesives, 3, III Not applicable

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

- H226 Flammable liquid and vapour
- H302 Harmful if swallowed
- H304 May be fatal if swallowed and enters airways
- H314 Causes severe skin burns and eye damage
- H318 Causes serious eye damage
- H336 May cause drowsiness or dizziness
- H372 Causes damage to organs through prolonged or repeated exposure
- H400 Very toxic to aquatic life
- H411 Toxic to aquatic life with long lasting effects
- H413 May cause long lasting harmful effects to aquatic life

Legend	TIMA (time unighted everyone)
TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC Supercedes Date: 14-Oct-2022

Revision date 24-Aug-2023 Revision Number 2.03

STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sour No information available Prepared By Revision date Indication of changes	ces for data Product Safety & Regulatory Affairs 24-Aug-2023
Revision note	SDS sections updated, 6, 8.
Training Advice	Provide adequate information, instruction, and training for operator
Further information	No information available

This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet