



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK QUICK DRYING FLEXACRYL GREY
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Primers, Sealers, and Undercoaters
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin sensitisation	Category 1 - (H317)
---------------------------	---------------------

2.2. Label elements

Contains 1,2-benzisothiazol-3(2H)-one [BIT]; 2-methyl-2H-isothiazol-3-one [MIT]; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]



Signal word
Warning

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Hazard statements

H317 - May cause an allergic skin reaction.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P261 - Avoid breathing vapours
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Titanium dioxide 13463-67-7	10 - <20	01-2119489379-17-XXXX	236-675-5 (022-006-00-2)	[C]	-	-	-	V,W,10
Diethylene glycol monobutyl ether acetate 124-17-4	1 - <2.5	01-2119475110-51-XXXX	204-685-9	Eye Irrit. 2 (H319)	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.01 < 0.036	01-2120761540-60-XXXX	220-120-9 (613-088-00-6)	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.036%	1	1	-
2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4	0.0025 - <0.01	01-2120764690-50-xxxx	220-239-6 (613-326-00-9)	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1	Skin Sens. 1A :: C>=0.0015%	10	1	-

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

				(H410) (EUH071)				
reaction mass of 5-chloro-2-methyl-2 H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	<0.0015	No data available	611-341-5	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1A :: C>=0.0015%	100	100	B

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
Diethylene glycol monobutyl ether acetate	204-685-9	124-17-4	-	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21 +	0.21 +
2-methyl-2H-isothiazol-3-one [MIT]	220-239-6 (613-326-00-9)	2682-20-4	285	243	0.11	-	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	66	141	0.17	-	-

This product does not contain candidate substances of very high concern at a concentration ≥0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
-----------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.
Hazardous combustion products	Carbon oxides. Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other information	Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

Recommended storage temperature Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Primers, Sealers, and Undercoaters.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Talc 14807-96-6	-	TWA: 1 mg/m ³ STEL: 3 mg/m ³
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Magnesite	-	TWA: 10 mg/m ³

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

13717-00-5		TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Carbon black 1333-86-4	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Diethylene glycol monobutyl ether acetate (124-17-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Dermal	100 mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m ³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Diethylene glycol monobutyl ether acetate (124-17-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Dermal	60 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	7.9 mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m ³	
Consumer	Dermal	0.345 mg/kg bw/d	

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supercedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Long term Systemic health effects			
--------------------------------------	--	--	--

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Diethylene glycol monobutyl ether acetate (124-17-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.108 mg/l
Marine water	0.0108 mg/l
Freshwater - intermittent	0.6 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	0.8 mg/kg dry weight
Marine sediment	0.08 mg/kg dry weight
Soil	0.29 mg/kg dry weight

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Avoid contact with eyes. Eye protection must conform to standard EN 166.

Hand protection

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection

Wear protective gloves and protective clothing. Avoid contact with skin, eyes or clothing.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Colour	Grey
Odour	Sweet.

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	
Initial boiling point and boiling range	100 °C	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 80 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known.
pH (as aqueous solution)	7 - 8.5	
Kinematic viscosity	No data available	None known
Dynamic viscosity	525000 mPa s	
Water solubility	Miscible in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.16	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None under normal processing.
------------------------------------	-------------------------------

10.4. Conditions to avoid

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supercedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Conditions to avoid Do not freeze.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂). Hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Diethylene glycol monobutyl ether acetate	=6500 mg/kg (Rattus)	5400 - 5700 mg/kg (Oryctolagus cuniculus)	=72500 mg/m ³ (Rattus) 4 h
1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
2-methyl-2H-isothiazol-3-one [MIT]	LD50 =285 mg/Kg (Rattus)	LD50 >242 mg/Kg (Rattus)	=0.11 mg/L (Rattus) 4 h
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	66 mg/kg (Rat)	LD50 = 8141 mg/kg (Rat) OECD 402	= 0.33 mg/L (Rat) 4h

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Titanium dioxide	Carc. 2

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Diethylene glycol monobutyl ether acetate 124-17-4	-	LC50: 50 - 70mg/L (96h, Brachydanio rerio) LC50: =77mg/L (96h, Pimephales promelas)	-	LC50: =665mg/L (48h, Daphnia magna)		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4	EC50 (72hr) 0.157 mg/l (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96hr) 5.71 mg/l (Oncorhynchus mykiss) OECD 203	-	EC50 (48hr) 1.68 mg/l (Daphnia) (OECD 202)	10	1
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Diethylene glycol monobutyl ether acetate (124-17-4)			
Method	Exposure time	Value	Results
OECD Test No. 301C: Ready Biodegradability: Modified MITI Test (I) (TG 301 C)	28 days	100%	Readily biodegradable

2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4)			
Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and Anaerobic Transformation in Aquatic Sediment Systems		Half-life	1.28-2.1 days
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		biodegradation Half-life	Readily biodegradable 4.1 days

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Diethylene glycol monobutyl ether acetate	1.7
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
2-methyl-2H-isothiazol-3-one [MIT]	-0.32
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB
Diethylene glycol monobutyl ether acetate	The substance is not PBT / vPvB
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one [MIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP

14.6 Special precautions for user
Special Provisions None

14.7 Maritime transport in bulk
according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user

Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

Ozone-depleting substances (ODS) Regulation (EU) 2024/590
Not applicable

Persistent Organic Pollutants
Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors
Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H301 - Toxic if swallowed
H302 - Harmful if swallowed
H310 - Fatal in contact with skin
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation

Notes relating to the classification and labelling of mixtures

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes date 18-Jul-2024

Revision date 15-Nov-2024
Revision Number 2.03

STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	15-Nov-2024
<u>Indication of changes</u>	

Revision Note	Not applicable.
Training Advice	No information available
Further information	No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet