



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK GRIPFILL ADHESIVE**  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name EVO-STIK GRIPFILL ADHESIVE

### Other means of identification

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik SA  
51 Esplanade du Général de Gaulle  
92800 Puteaux – La Défense  
FRANCE  
Tel: +33 (0)1 49 00 90 00

#### Supplier

Bostik Industries Limited  
IDA Business & Technology Park  
Ballynattin, Arklow,  
Co. Wicklow  
Ireland  
Tel: +353 (1) 8624900  
Fax: +353 (1) 8402186

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

Ireland

#### NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom

Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe

112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids	Category 2 - (H225)
Skin irritation	Category 2 - (H315)
Eye irritation	Category 2 - (H319)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

### 2.2. Label elements

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4



**Signal word**  
Danger

## Hazard statements

H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H412 - Harmful to aquatic life with long lasting effects.

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P273 - Avoid release to the environment  
P280 - Wear protective gloves and eye/face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P403 + P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Additional information

This product requires tactile warnings if supplied to the general public.

## 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

## PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Xylenes (o-, m-, p-isomers) 1330-20-7	5 - <10	01-2119488216-32-XXXX	215-535-7 (601-022-00-9)	Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT RE 2 (H373)	-	-	-	C

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes date** 09-Jun-2023

**Revision date** 11-Jun-2025  
**Revision Number** 4

				Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 3 (H226)				
Acetone 67-64-1	5 - <10	01-2119471330 -49-XXXX	200-662-2 (606-001-00-8)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	5 - <10	01-2119475515 -33-xxxx	927-510-4	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	-	-	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	1 - <5	01-2119484651 -34-XXXX	931-254-9	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)	-	-	-	P
Ethylbenzene 100-41-4	1 - <2.5	01-2119489370 -35-XXXX	202-849-4 (601-023-00-4)	Acute Tox. 4 (H332) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225)	-	-	-	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102)-P260-P262-P301 + P310-P331 shall apply.

**Full text of H- and EUH-phrases: see section 16**

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE<sub>mix</sub>) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Xylenes (o-, m-, p-isomers)	215-535-7 (601-022-00-9)	1330-20-7	2500	1990	4.8	-	-
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	-	-	-	-	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	64742-49-0	16750	3350	-	-	-

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Ethylbenzene	202-849-4 (601-023-00-4)	100-41-4	3500	15400	4.99	17.6	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation.
Effects of Exposure	No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	No information available.
-----------------	---------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated
--	--

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Silicon dioxide.

## 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

## 7.2. Conditions for safe storage, including any incompatibilities

### Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

### Recommended storage temperature

Keep at temperatures between 5 and 25 °C.

## 7.3. Specific end use(s)

### Specific use(s)

Adhesives.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

### Other information

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Kaolin 1332-58-7	-	TWA: 2 mg/m <sup>3</sup> ; respirable dust	TWA: 2 mg/m <sup>3</sup> ; respirable dust STEL: 6 mg/m <sup>3</sup> ; respirable dust
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm; TWA: 221 mg/m <sup>3</sup> ; STEL: 100 ppm; STEL: 442 mg/m <sup>3</sup> ; pSk	TWA: 50 ppm; TWA: 221 mg/m <sup>3</sup> ; STEL: 100 ppm; STEL: 442 mg/m <sup>3</sup> ; pSk	TWA: 50 ppm; TWA: 220 mg/m <sup>3</sup> ; STEL: 100 ppm; STEL: 441 mg/m <sup>3</sup> ; pSk
Acetone 67-64-1	TWA: 500 ppm; TWA: 1210 mg/m <sup>3</sup> ;	TWA: 500 ppm; TWA: 1210 mg/m <sup>3</sup> ; STEL: 1500 ppm (calculated); STEL: 3630 mg/m <sup>3</sup> (calculated);	TWA: 500 ppm; TWA: 1210 mg/m <sup>3</sup> ; STEL: 1500 ppm; STEL: 3620 mg/m <sup>3</sup> ;
Ethylbenzene 100-41-4	TWA: 100 ppm; TWA: 442 mg/m <sup>3</sup> ; STEL: 200 ppm; STEL: 884 mg/m <sup>3</sup> ; pSk	TWA: 100 ppm; TWA: 442 mg/m <sup>3</sup> ; STEL: 200 ppm; STEL: 884 mg/m <sup>3</sup> ; pSk	TWA: 100 ppm; TWA: 441 mg/m <sup>3</sup> ; STEL: 125 ppm; STEL: 552 mg/m <sup>3</sup> ; pSk

**Derived No Effect Level (DNEL)** No information available

#### Derived No Effect Level (DNEL)

##### Xylenes (o-, m-, p- isomers) (1330-20-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d	
Long term Systemic health effects	Inhalation	77 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes date** 09-Jun-2023

**Revision date** 11-Jun-2025  
**Revision Number** 4

worker			
Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m <sup>3</sup>	

<b>Acetone (67-64-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Inhalation	1210 mg/m <sup>3</sup>	

<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d	

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane (64742-49-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Dermal	13964 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Acetone (67-64-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	447 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes date** 09-Jun-2023

**Revision date** 11-Jun-2025  
**Revision Number** 4

Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

## 8.2. Exposure controls

<b>Engineering controls</b>	Ensure adequate ventilation, especially in confined areas.
<b>Personal protective equipment</b>	
<b>Eye/face protection</b>	Tight sealing safety goggles. Face protection shield.
<b>Hand protection</b>	Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
<b>Skin and body protection</b>	Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Paste
<b>Colour</b>	Beige
<b>Odour</b>	Solvent.

<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	= 60 °C	
<b>Flammability</b>	No data available	Flammable liquid
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	-10 °C	
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	None known



# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

Kinematic viscosity	500 mm <sup>2</sup> /s	@ 40°C
Dynamic viscosity	No data available	
Water solubility	Insoluble in water.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	<110 kPa	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.18	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

## 9.2. Other information

Solid content (%)	< 80	
VOC content		approx 350 g/L

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

### 10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

## Information on likely routes of exposure

### Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. May cause redness and tearing of the eyes.

## Acute toxicity

### Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	23,253.60 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	47.90 mg/l
ATEmix (inhalation-vapour)	128.50 mg/l

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers)	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	= 11 mg/L (ATE)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m <sup>3</sup> (vapour) (rat OECD 403)
Ethylbenzene	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.6 mg/L (Rattus) 4 h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Xylenes (o-, m-, p- isomers) (1330-20-7)			
Acetone (67-64-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Not a skin sensitiser

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in practice					Narcotic effects

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Oral	200-3400 mg/kg bw/d	91 days	No Observed Adverse Effect Level LOAEL 1700 mg/kg bw/d
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm No Observed Adverse Effect Level

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** Based on available data, the classification criteria are not met.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes date** 09-Jun-2023

**Revision date** 11-Jun-2025  
**Revision Number** 4

## 12.1. Toxicity

### Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h) = 31.9 mg/l (Daphnia magna)		
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)		

## 12.2. Persistence and degradability

### Persistence and degradability

No information available.

Xylenes (o-, m-, p- isomers) (1330-20-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	87.8 % Readily biodegradable

Acetone (67-64-1)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Xylenes (o-, m-, p- isomers)	3.15

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

Acetone	-0.24
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
Ethylbenzene	3.6

## 12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Xylenes (o-, m-, p- isomers)	Not PBT/vPvB
Acetone	Not PBT/vPvB
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not PBT/vPvB
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Not PBT/vPvB
Ethylbenzene	Not PBT/vPvB

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

## 12.7. Other adverse effects

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

### Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (D/E)

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes date 09-Jun-2023

Revision date 11-Jun-2025  
Revision Number 4

14.5 Environmental hazards No  
14.6 Special precautions for user  
Special Provisions 640D  
Classification code F1  
Tunnel restriction code (D/E)  
Limited quantity (LQ) 5 L  
ADR Hazard Id (Kemmler Number) 33

## IMDG

14.1 UN number or ID number UN1133  
14.2 UN proper shipping name Adhesives  
14.3 Transport hazard class(es) 3  
14.4 Packing group II  
Description UN1133, Adhesives, 3, II, (-10°C c.c.)  
14.5 Marine pollutant NP  
14.6 Special precautions for user  
Special Provisions None  
Limited Quantity (LQ) 5 L  
EmS-No. F-E, S-D  
14.7 Maritime transport in bulk according to IMO instruments  
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1133  
14.2 UN proper shipping name Adhesives  
14.3 Transport hazard class(es) 3  
14.4 Packing group II  
Description UN1133, Adhesives, 3, II  
14.5 Environmental hazards No  
14.6 Special precautions for user  
Special Provisions A3  
Limited quantity (LQ) 1 L  
ERG Code 3L

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes date** 09-Jun-2023

**Revision date** 11-Jun-2025  
**Revision Number** 4

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

## Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

## Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Hydrocarbons, C6, isoalkanes, <5% n-hexane - 64742-49-0		25000

## Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

## Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes date** 09-Jun-2023

**Revision date** 11-Jun-2025  
**Revision Number** 4

H336 - May cause drowsiness or dizziness  
H373 - May cause damage to organs through prolonged or repeated exposure  
H411 - Toxic to aquatic life with long lasting effects  
H412 - Harmful to aquatic life with long lasting effects

## Notes relating to the identification, classification and labelling of substances

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers  
Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply

SVHC: Substances of Very High Concern for Authorisation:  
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances  
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances  
STOT RE: Specific target organ toxicity - Repeated exposure  
STOT SE: Specific target organ toxicity - Single exposure  
EWC: European Waste Catalogue  
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
IATA: International Air Transport Association  
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG: International Maritime Dangerous Goods  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

## Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

## Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)  
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)  
European Chemicals Agency (ECHA) (ECHA\_API)  
Environmental Protection Agency  
Acute Exposure Guideline Level(s) (AEGl(s))  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
NIOSH (National Institute for Occupational Safety and Health)



# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes date** 09-Jun-2023

**Revision date** 11-Jun-2025  
**Revision Number** 4

---

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set

<b>Prepared By</b>	Product Safety & Regulatory Affairs
<b>Revision date</b>	11-Jun-2025
<b>Revision Note</b>	SDS sections updated: 2
<b>Training Advice</b>	Provide adequate information, instruction, and training for operator
<b>Further information</b>	No information available

**Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)**

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**