

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK BITUMINOUS BLACK PAINT

Supercedes Date: 25-Oct-2023

Revision date 22-Apr-2024 Revision Number 3.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK BITUMINOUS BLACK PAINT

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Paints and varnishes

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Specific target organ toxicity — repeated exposure	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

2.2. Label elements

Contains Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)



United Kingdom - BE Page 1 / 12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

Signal word

Danger

Hazard statements

H336 - May cause drowsiness or dizziness.

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

H226 - Flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe vapour

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P312 - Call a POISON CENTER or doctor if you feel unwell

P391 - Collect spillage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	40 - <80	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)	-	01-2119458049- 33-XXXX

United Kingdom - BE Page 2/12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

Full text of H- and EUH-phrases: see section 16

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eve contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious Ingestion

person. Call a doctor.

Remove all sources of ignition. Ensure that medical personnel are aware of the Self-protection of the first aider

> material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Causes damage to organs through prolonged or repeated exposure. **Effects of Exposure**

4.3. Indication of any immediate medical attention and special treatment needed

No information available. Note to doctors

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

No information available. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated

fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides.

United Kingdom - BE Page 3/12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions**

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing

vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient

ventilation, wear suitable respiratory equipment.

Do not eat, drink or smoke when using this product. Contaminated work clothing should General hygiene considerations

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

United Kingdom - BE Page 4/12

BOSTIK BITUMINOUS BLACK PAINT

Supercedes Date: 25-Oct-2023

Revision date 22-Apr-2024 Revision Number 3.01

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep from freezing.

Recommended storage

temperature

Do not freeze. Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)

Paints and varnishes.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics,	-	TWA: 350 mg/m ³
aromatics (2-25%)		-
RR-91855-8		

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	330 mg/m³			
worker Long term Systemic health effects	Dermal	44 mg/kg bw/d			

Derived No Effect Level (DNEL)					
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	71 mg/m³			
Consumer Long term Systemic health effects	Dermal	26 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d			

United Kingdom - BE Page 5/12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Eye protection must conform to standard EN 166. Hand protection

Wear protective gloves. The breakthrough time of the gloves depends on the material

and the thickness as well as the temperature.

Wear suitable protective clothing. Skin and body protection

In case of inadequate ventilation wear respiratory protection. In case of mist, spray or Respiratory protection

aerosol exposure wear suitable personal respiratory protection and protective suit.

Organic gases and vapours filter conforming to EN 14387. Recommended filter type:

Local authorities should be advised if significant spillages cannot be contained. Do not **Environmental exposure controls**

allow into any sewer, on the ground or into any body of water. Prevent product from

None known

entering drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid **Appearance** Liquid Colour Black

Odour Characteristic.

Remarks • Method Property Values

Melting point / freezing point No data available >= 153 °C Initial boiling point and boiling

range

Flammability No data available Flammable liquid Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

>= 40 °C Flash point **Autoignition temperature** >= 200 °C

Decomposition temperature

Not applicable. Insoluble in water. No data available pН

pH (as aqueous solution) No data available None known

 $>= 290 \text{ mm}^2/\text{s}$ @ 40°C None known Kinematic viscosity

No data available **Dynamic viscosity** Insoluble in water. Water solubility

Solubility(ies) No data available None known **Partition coefficient** No data available None known Vapour pressure No data available None known Relative density 0.89 - 0.92 None known

No data available **Bulk Density** No data available **Density**

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available **Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

VOC content $<= 440 \, g/L$

United Kingdom - BE Page 6/12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available. Reactivity

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Do not freeze.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

May cause drowsiness or dizziness. Inhalation

Based on available data, the classification criteria are not met. Eye contact

Skin contact Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Acute toxicity

United Kingdom - BE Page 7/12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >2000 mg/kg ATEmix (dermal) >2000 mg/kg >20000 ppm ATEmix (inhalation-gas) ATEmix (inhalation-dust/mist) >5 mg/l ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12,	LD50 >15000 mg/Kg (Rattus)	LD50 > 3400 mg/kg (Rattus)	LC50 (4hrs) >13.1 mg/l (Rattus)
n-alkanes, isoalkanes, cyclics,	OECD 401	OECD 402	
aromatics (2-25%)			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. Germ cell mutagenicity

Based on available data, the classification criteria are not met. Carcinogenicity

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Based on available data, the classification criteria are not met. **Aspiration hazard**

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

United Kingdom - BE Page 8/12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Hydrocarbons, C9-C12,	EL50 (72h) = 4.1	LL50 96hr 10-30	-	EL50 48hr		
n-alkanes, isoalkanes,	mg/l (mg/l		10-30mg/l		
cyclics, aromatics	Pseudokirchner	(Oncorhynchus		(daphnia magna)		
(2-25%)	ella subcapitata)	mykiss)				
RR-91855-8	OECD 401					

12.2. Persistence and degradability

Persistence and degradability No information available.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)

Method	Exposure time	Value	Results
	28 days	biodegradation	74.7 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics	The substance is not PBT / vPvB
(2-25%)	

12.6. Endocrine disrupting properties

No information available. **Endocrine disrupting properties**

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

European Waste Catalogue

17 03 02 bituminous mixtures other than those mentioned in 17 03 01 15 01 10*: Packaging containing residues of or contaminated by dangerous substances

United Kingdom - BE Page 9/12

BOSTIK BITUMINOUS BLACK PAINT

Supercedes Date: 25-Oct-2023

Revision date 22-Apr-2024 Revision Number 3.01

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number UN1999 **14.2 UN proper shipping name** UN1999 Tars, liquid

14.3 Transport hazard class(es) 3
Labels 3

14.4 Packing group

Description UN1999, Tars, liquid, 3, III, (D/E), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special precautions for user

Special Provisions None
Classification code F1
Tunnel restriction code (D/E)
Limited quantity (LQ) 5 L
ADR Hazard Id (Kemmler 30

Number)

IMDG

14.1 UN number or ID number14.2 UN proper shipping nameTars, liquid

14.3 Transport hazard class(es) 314.4 Packing group || | | |

Description UN1999, Tars, liquid, 3, III, (40°C c.c.), Marine pollutant

14.5 Marine pollutant NP14.6 Special precautions for user

Special Provisions955Limited Quantity (LQ)5 LEmS-No.F-E, S-E

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1999 **14.2 UN proper shipping name** UN1999 Tars, liquid

14.3 Transport hazard class(es) 314.4 Packing group | | | | |

Description UN1999, Tars, liquid, 3, III

14.5 Environmental hazards Yes14.6 Special precautions for user Special Provisions A3

Limited quantity (LQ) 10 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom - BE Page 10 / 12

BOSTIK BITUMINOUS BLACK PAINT

Supercedes Date: 25-Oct-2023

Revision date 22-Apr-2024 Revision Number 3.01

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H336 - May cause drowsiness or dizziness

H372 - Causes damage to organs through prolonged or repeated exposure

United Kingdom - BE Page 11 / 12

BOSTIK BITUMINOUS BLACK PAINT

Revision date 22-Apr-2024 Supercedes Date: 25-Oct-2023 **Revision Number** 3.01

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average) **STEL** STEL (Short Term Exposure Limit)

Ceiling Limit Value Ceiling Sk* Skin designation

SVHC Substance(s) of Very High Concern

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals PBT Very Persistent and very Bioaccumulative (vPvB) Chemicals vPvB

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG) IATA International Air Transport Association (IATA)

Regulations concerning the International Transport of Dangerous Goods by Rail RID

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 22-Apr-2024

Indication of changes

Revision note Not applicable.

Training Advice Provide adequate information, instruction, and training for operator

No information available **Further information**

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 12/12