



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR

Other means of identification

Substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Roof Coating

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Industries Limited
IDA Business & Technology Park
Ballynattin, Arklow,
Co. Wicklow
Ireland
Y14 A370
Tel : +353 (0)402 32370

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)
United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids	Category 3 - (H226)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Target organ effects: Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Hazardous to the aquatic environment - chronic	Category 2 - (H411)

2.2. Label elements

Contains Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); Naphtha, petroleum, hydrotreated heavy, <2% aromatics

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01



Signal word
Danger

Hazard statements

H226 - Flammable liquid and vapour.
H336 - May cause drowsiness or dizziness.
H372 - Causes damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe vapour
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P391 - Collect spillage
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics,	>25 - <40	01-2119458049-33-XXXX	919-446-0	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304)	-	-	-	-

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

aromatics (2-25%) RR-91855-8				Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)				
Aluminum 7429-90-5	10 - <20	01-2119529243 -45-xxxx	231-072-3 (013-002-00-1)	Flam. Sol. 1 (H228) Water-react. 2 (H261)	-	-	-	T
Naphtha, petroleum, hydrotreated heavy, <2% aromatics 64742-48-9	5 - <10	01-2119463258 -33-XXXX	919-857-5	STOT SE 3 (H336) Asp. Tox. 1 (H304) (EUH066) Flam. Liq. 3 (H226)	-	-	-	P

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Note T - This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	-	3400	-	-	-
Aluminum	231-072-3 (013-002-00-1)	7429-90-5	-	-	0.8889	-	-
Naphtha, petroleum, hydrotreated heavy, <2% aromatics	919-857-5	64742-48-9	6006	5005	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice and attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

	Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	No information available.
------------------------	---------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Vapours may form explosive mixture with air. Most vapours are heavier than air. Vapours may spread along ground and collect in low or confined areas (sewers, basements, tanks).
Hazardous combustion products	Carbon oxides. Hydrocarbons. Aldehydes.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so. Residues which cannot be recycled are disposed of as chemical waste. Equipment cleaned with organic solvent, washings are collected and disposed of as solvent waste.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Recommended storage temperature Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)
Roof Coating.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union (Directives 98/24/EC and 2004/37/EC)	Ireland (CoP 2024)	United Kingdom
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	-	-	TWA: 350 mg/m ³
Mica 12001-26-2	-	TWA: 3 mg/m ³ ; respirable fraction STEL: 9 mg/m ³ (calculated); respira ble fraction	TWA: 10 mg/m ³ ; total inhalable TWA: 0.8 mg/m ³ ; respirable STEL: 30 mg/m ³ ; total inhalable STEL: 2.4 mg/m ³ ; respirable
Aluminum 7429-90-5	-	TWA: 1 mg/m ³ ; respirable fraction STEL: 3 mg/m ³ (calculated); respira ble dust	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	330 mg/m ³	
worker Long term Systemic health effects	Dermal	44 mg/kg bw/d	

Naphtha, petroleum, hydrotreated heavy, <2% aromatics (64742-48-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	208 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	871 mg/m ³	

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	71 mg/m ³	
Consumer Long term Systemic health effects	Dermal	26 mg/kg bw/d	
Consumer	Oral	26 mg/kg bw/d	

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

Long term Systemic health effects			
--------------------------------------	--	--	--

Naphtha, petroleum, hydrotreated heavy, <2% aromatics (64742-48-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	125 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	185 mg/m ³	
Consumer Long term Systemic health effects	Oral	125 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.
Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Viscous Liquid
Colour Silver, bronze
Odour Solvent.

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	> 155 °C	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 40 °C	None known
Autoignition temperature	200 °C	None known
Decomposition temperature		None known
pH	No data available	Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 36.7 mm ² /s	@ 40°C
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water.	None known

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	1.03 1.12	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) No information available
VOC content <= 450 g/L

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

Inhalation May cause drowsiness or dizziness.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/L
ATEmix (inhalation-vapour) >20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50 >15000 mg/Kg (Rattus) OECD 401	LD50 > 3400 mg/kg (Rattus) OECD 402	LC50 (4hrs) >13.1 mg/l (Rattus)
Aluminum	-	-	> 0.888888 mg/L (Rat) 4 h
Naphtha, petroleum, hydrotreated heavy, <2% aromatics	LD50 >2000 mg/kg (Rattus)	>3000 mg/Kg (Rattus)	Ld50 (4h)>5.6mg/L (Rattus)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Naphtha, petroleum, hydrotreated heavy, <2% aromatics (64742-48-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Mild skin irritant Read-across

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Naphtha, petroleum, hydrotreated heavy, <2% aromatics	Muta. 1B

Carcinogenicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Naphtha, petroleum, hydrotreated heavy, <2% aromatics	Carc. 1B

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	EL50 (72h) = 4.1 mg/l (Pseudokirchnerella subcapitata) OECD 401	LL50 96hr 10-30 mg/l (Oncorhynchus mykiss)	-	EL50 48hr 10-30mg/l (daphnia magna)		
Naphtha, petroleum, hydrotreated heavy, <2% aromatics 64742-48-9	-	LC50 (96h) >1000 mg/L Oncorhynchus mykiss	-	LL50 (48h) >1000 mg/L Daphnia magna		

12.2. Persistence and degradability

Persistence and degradability No information available.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Method	Exposure time	Value	Results
	28 days	biodegradation	74.7 % Readily biodegradable

Naphtha, petroleum, hydrotreated heavy, <2% aromatics (64742-48-9)

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	>60 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This product does not contain any substances that are assessed to be a PBT or a vPvB.

Chemical name	PBT and vPvB assessment
Aluminum	Not PBT/vPvB
Naphtha, petroleum, hydrotreated heavy, <2% aromatics	Not PBT/vPvB

12.6. Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects No information available.
PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number UN1966
14.2 UN proper shipping name Hydrogen, refrigerated liquid
14.3 Transport hazard class(es) 2
Labels 2.1
14.4 Packing group Not regulated

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

Description UN1966, Hydrogen, refrigerated liquid, 2, (B/D), Environmentally Hazardous
14.5 Environmental hazards Yes
14.6 Special precautions for user
Special Provisions None
Classification code 3F
Tunnel restriction code (B/D)
Limited quantity (LQ) 0
ADR Hazard Id (Kemmler Number) 223

IMDG

14.1 UN number or ID number UN1966
14.2 UN proper shipping name Hydrogen, refrigerated liquid
14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description UN1966, Hydrogen, refrigerated liquid, 2.1, Marine pollutant
14.5 Marine pollutant P
14.6 Special precautions for user
Special Provisions None
Limited Quantity (LQ) 0
EmS-No. F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1966
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description Forbidden
14.5 Environmental hazards Yes
14.6 Special precautions for user
Special Provisions None
Limited quantity (LQ) Forbidden
ERG Code 10L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Naphtha, petroleum, hydrotreated heavy, <2% aromatics	64742-48-9	

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

Export and import of hazardous chemicals (Regulation (EC) No 649/2012)

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Naphtha, petroleum, hydrotreated heavy, <2% aromatics - 64742-48-9		25000

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants Regulation (EU) 2019/1021

Not applicable

Regulation (EU) 2019/1148 of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Aluminum - 7429-90-5	Regulated		

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

This chemical is a VOC according to 2004/42/EC

Subcategory

One-pack performance coatings

solvent based

500 g/L

Maximum content of VOC in g/l of the product in a ready to use condition 450 g/L

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

H226 - Flammable liquid and vapour
H228 - Flammable solid
H261 - In contact with water releases flammable gases
H304 - May be fatal if swallowed and enters airways
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply

Note T - This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

SAFETY DATA SHEET

BOSTIK SILVACOTE ALUMINIUM SOLAR PROTECTOR
Supersedes date 06-Jul-2023

Revision date 14-Sep-2026
Revision Number 1.01

European Chemicals Agency (ECHA) (ECHA_API)
U.S. Environmental Protection Agency
U.S. EPA Acute Exposure Guideline Level(s) (AEGL(s))
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
U.S. National Institute for Occupational Safety and Health (NIOSH)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 14-Sep-2026

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet