



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK CARPET ADHESIVE

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Aerosol Adhesives and/or sealants

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA
51 Esplanade du Général de Gaulle
92800 Puteaux – La Défense
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosols	Category 1 - (H222, H229)
Skin irritation	Category 2 - (H315)
Eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Target organ effects: Narcotic effects.	
Aspiration hazard	Category 1 - (H304)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

Contains Acetone; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Hydrocarbons, C6, isoalkanes, <5% n-hexane

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03



Signal word
Danger

Hazard statements

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, eye protection and face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P331 - Do NOT induce vomiting
P405 - Store locked up
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product is exempt from the requirement for a child resistant fastening and tactile warning of danger, as it is an aspiration hazard, placed on the market in the form of an aerosol or in a container with a sealed spray attachment. Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of an explosive/highly flammable mixture is possible.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
---------------	----------	---------------------------	--------------------	---	------------------------------------	----------	----------------------	-------

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene 68476-85-7	>25 - <40	01-2119485911 -31-xxxx	270-704-2 (649-202-00-6)	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	K,S,U
Acetone 67-64-1	20 - <25	01-2119471330 -49-XXXX	200-662-2 (606-001-00-8)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	10 - <20	01-2119475515 -33-xxxx	927-510-4	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	-	-	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	5 - <10	01-2119484651 -34-XXXX	931-254-9	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066) [E]	-	-	-	P
n-Hexane contained in UVCB 110-54-3	0.1 - <0.5	-	203-777-6 (601-037-00-0)	Skin Irrit. 2 (H315) Repr. 2 (H361 f) STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	-	-	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Note K - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (Einecs No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3 of Annex VI to Regulation (EC) No 1272/2008.

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Note S - This substance may not require a label according to Article 17 of Regulation (EC) No 1272/2008 (see section 1.3 of Annex I to that Regulation).

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of H- and EUH-phrases: see section 16

Substance of unknown or variable composition, complex reaction products or biological material (UVCB)

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	270-704-2 (649-202-00-6)	68476-85-7	-	-	-	-	-
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	-	-	-	-	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	64742-49-0	16750	3350	-	-	-
n-Hexane contained in UVCB	203-777-6 (601-037-00-0)	110-54-3	-	-	-	-	-

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No.	SVHC candidates
n-Hexane contained in UVCB	110-54-3	X

This product does not contain any synthetic polymer microparticles as defined by entry 78 of Annex XVII to Regulation (EC) No. 1907/2006.

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Erythema (skin redness). May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers,

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Use clean non-sparking tools to collect absorbed material.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so. Residues which cannot be recycled are disposed of as chemical waste. Equipment cleaned with organic solvent, washings are collected and disposed of as solvent waste. Collect water from cleaning tools and reuse it or dispose it in local sewage systems. Do not spill water or dispose cleaning water into the environment.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from food, drink and animal feedingstuffs. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Store away from other materials. Keep/store only in original container. Store in a dry place. Store in a closed container.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Adhesives and/or sealants. Aerosol.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene 68476-85-7	-	-	TWA: 1000 ppm; TWA: 1750 mg/m ³ ; STEL: 1250 ppm; STEL: 2180 mg/m ³ ;
Acetone 67-64-1	TWA: 500 ppm; TWA: 1210 mg/m ³ ;	TWA: 500 ppm; TWA: 1210 mg/m ³ ; STEL: 1500 ppm (calculated); STEL: 3630 mg/m ³ (calculated);	TWA: 500 ppm; TWA: 1210 mg/m ³ ; STEL: 1500 ppm; STEL: 3620 mg/m ³ ;
n-Hexane contained in UVCB 110-54-3	TWA: 20 ppm; TWA: 72 mg/m ³ ;	TWA: 20 ppm; TWA: 72 mg/m ³ ; STEL: 60 ppm (calculated); STEL: 216 mg/m ³ (calculated); pSk	TWA: 20 ppm; TWA: 72 mg/m ³ ; STEL: 60 ppm; STEL: 216 mg/m ³ ;

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Acetone (67-64-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m ³	
Long term Systemic health effects worker	Inhalation	1210 mg/m ³	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	2085 mg/m ³	
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d	

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Dermal	13964 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	2085 mg/m ³	

Derived No Effect Level (DNEL)

Acetone (67-64-1)

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
 Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
 Revision Number 3.03

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	447 mg/m ³	
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
Hand protection	Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	Wear appropriate personal protective clothing to prevent skin contact.
Respiratory protection	Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better.
Environmental exposure controls	Do not allow uncontrolled discharge of product into the environment.

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol
Colour	Amber
Odour	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	Not applicable, Aerosol
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	Not applicable, Aerosol
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable.
pH (as aqueous solution)	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	

Water solubility	Insoluble in water.
Solubility(ies)	No data available
Partition coefficient	No data available
Vapour pressure	No data available
Relative density	No data available
Bulk density	No data available
Liquid Density	No data available
Relative vapour density	No data available
Particle characteristics	
Particle Size	No information available
Particle Size	No information available
Distribution	

9.2. Other information

Solid content (%)	No information available
VOC content	approx 82 g/L

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

ATEmix (inhalation-dust/mist) >5 mg/L
ATEmix (inhalation-vapour) >20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	-	-	LD50 (4h) >20 mg/l (rattus)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m ³ (vapour) (rat OECD 403)
n-Hexane contained in UVCB	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h

Substance of unknown or variable composition, complex reaction products or biological material (UVCB)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Acetone (67-64-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Not a skin sensitiser

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
n-Hexane contained in UVCB	Repr. 2

STOT - single exposure May cause drowsiness or dizziness.

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in practice					Narcotic effects

STOT - repeated exposure Based on available data, the classification criteria are not met.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Oral	200-3400 mg/kg bw/d	91 days	No Observed Adverse Effect Level LOAEL 1700 mg/kg bw/d
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm No Observed Adverse Effect Level

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h)= 31.9 mg/l (Daphnia magna)		
n-Hexane contained in UVCB 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	-		

Substance of unknown or variable composition, complex reaction products or biological material (UVCB)

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

12.2. Persistence and degradability

Persistence and degradability No information available.

Acetone (67-64-1)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	2.8
Acetone	-0.24
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
n-Hexane contained in UVCB	4

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	Not PBT/vPvB
Acetone	Not PBT/vPvB
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not PBT/vPvB
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Not PBT/vPvB
n-Hexane contained in UVCB	Not PBT/vPvB

12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable. Should not be released into the environment.

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Handle contaminated packages in the same way as the product itself. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 16 05 04* gases in pressure containers (including halons) containing dangerous substances 15 01 04 metallic packaging
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (D)
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)
Limited quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No.	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	A145, A167, A802
Limited quantity (LQ)	30 kg G
ERG Code	10L

SECTION 15: Regulatory information

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59) $\geq 0.1\%$

Chemical name	CAS No.
n-Hexane contained in UVCB	110-54-3

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene - 68476-85-7	50	200
Hydrocarbons, C6, isoalkanes, <5% n-hexane - 64742-49-0		25000

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) which are regulated pursuant to the EU regulations on drug precursors [(EC) No. 111/2005 and (EC) No. 273/2004] above levels that can be easily used or extracted by readily applicable or economically viable means.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking
H220 - Extremely flammable gas
H225 - Highly flammable liquid and vapour
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361f - Suspected of damaging fertility
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note K - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (Einecs No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3 of Annex VI to Regulation (EC) No 1272/2008

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply

Note S - This substance may not require a label according to Article 17 of Regulation (EC) No 1272/2008 (see section 1.3 of Annex I to that Regulation)

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	SK*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

Prepared By	Product Safety & Regulatory Affairs
Revision date	27-Mar-2026
Revision Note	SDS sections updated 1
Training Advice	When working with hazardous materials, regular training of operators is required by law
Further information	No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

SAFETY DATA SHEET

EVO-STIK CARPET ADHESIVE
Supersedes date 20-Mar-2026

Revision date 27-Mar-2026
Revision Number 3.03

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet