

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022

Revision date 03-Jan-2025 Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1.	Product	identifier	

Product Name BOSTIK LIQUID COLOUR FOR CEMENT BLACK

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Colouring agent
-----------------	-----------------

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom

Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction EUH210 - Safety data sheet available on request

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

BOSTIK LIQUID COLOUR FOR CEMENT BLACK

Supercedes date 03-Oct-2022

P102 - Keep out of reach of children

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	concentration		M-Factor (long-ter m)	Notes
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.01 < 0.036	01-2120761540 -60-XXXX		Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	1A :: C>=0.036%	1	1	-

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
1,2-benzisothiazol-3(2 H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21+	0.21 +

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

If medical advice is needed, have product container or label at hand. Show this safety

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022

	data sheet to the doctor in attendance.	
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.	
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.	
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.	
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Neve give anything by mouth to an unconscious person.	
4.2. Most important symptoms and	d effects, both acute and delayed	
Symptoms	No information available.	
Effects of Exposure	No information available.	
4.3. Indication of any immediate m	edical attention and special treatment needed	
Note to doctors	No information available.	
SECTION 5: Firefighting me	asures	
5.1. Extinguishing media		
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Unsuitable extinguishing media	No information available.	
5.2. Special hazards arising from t	he substance or mixture	
Specific hazards arising from the chemical	No information available.	
Hazardous combustion products	Carbon monoxide. Carbon dioxide (CO2).	
5.3. Advice for firefighters		
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	
SECTION 6: Accidental relea	ase measures	
6.1. Personal precautions, protect	ive equipment and emergency procedures	
Personal precautions	Ensure adequate ventilation.	
For emergency responders	Use personal protection recommended in Section 8.	
6.2. Environmental precautions		
Environmental precautions	See Section 12 for additional Ecological Information.	
6.3. Methods and material for cont	ainment and cleaning up	
Methods for containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.	

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.
7.2. Conditions for safe storage, in	ncluding any incompatibilities
Storage Conditions	Keep container tightly closed in a dry and well-ventilated place.
7.3. Specific end use(s)	
Specific use(s) Colouring agent.	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Carbon black	-	TWA: 3.5 mg/m ³
1333-86-4		STEL: 7 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
1,2-benzisothiazol-3(2H)-one	e [BIT] (2634-33-5)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	6.81 mg/m³		
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d		

Derived No Effect Level (DNEL)				
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer	Inhalation	1.2 mg/m ³		
Long term Systemic health effects				

BOSTIK LIQUID COLOUR FOR CEMENT BLACK

Consumer	Dermal	0.345 mg/kg bw/d	
Long term			
Systemic health effects			

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)			
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	4.03 μg/l		
Marine water	0.403 µg/l		
Sewage treatment plant	1.03 mg/l		
Freshwater sediment	49.9 µg/l		
Marine sediment	4.99 μg/l		
Soil	3 mg/kg dry weight		

8.2. Exposure controls

Fugue	oorina	controls
LIIUIII	CCIIIIU	CONTROLS

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protectionTight sealing safety goggles.Hand protectionWear suitable gloves. Gloves must conform to standard EN 374.Skin and body protectionSuitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical		
Physical state	Liquid	
Appearance	Liquid	
Colour	Black	
Odour	Odourless.	
Odour threshold	Not applicable	
Property	Values	Remarks • Method
Melting point / freezing point	> 1000 °C	
Initial boiling point and boiling	No data available	None known
range		
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	4 - 8	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	No data available	
-		

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022

Revision date 03-Jan-2025 Revision Number 2.01

Relative vapour density	No data available	None known		
Particle characteristics Particle Size	No information available			
Particle Size Distribution	No information available			
9.2. Other information Solid content (%) VOC content	No information available	No data available		
9.2.1. Information with regards to physical hazard classes Not applicable				

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity

10.1. Reactivity	
Reactivity	No information available.
10.2. Chemical stability	
Stability	Stable under normal conditions.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
10.3. Possibility of hazardous reac	tions
Possibility of hazardous reactions	None under normal processing.
10.4. Conditions to avoid	
Conditions to avoid	None known based on information supplied.
10.5. Incompatible materials	
Incompatible materials	None known based on information supplied.
10.6. Hazardous decomposition pro	oducts_
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.
SECTION 11: Toxicological i	nformation
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008_

Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
1,2-benzisothiazol-3(2H)-one	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
[BIT]			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Based on available data, the classification criteria are not met.		
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.		
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.		
Germ cell mutagenicity	Based on available data, the classification criteria are not met.		
Carcinogenicity	Based on available data, the classification criteria are not met.		
Reproductive toxicity	Based on available data, the classification criteria are not met.		
STOT - single exposure	Based on available data, the classification criteria are not met.		
STOT - repeated exposure	Based on available data, the classification criteria are not met.		
Aspiration hazard	Based on available data, the classification criteria are not met.		
11.2. Information on other hazards			
11.2.1. Endocrine disrupting properties			

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
1,2-benzisothiazol-3(2	EC50 3Hr	LC50 (96hr) 2.15	-	EC50(48hr) 2.94	1	1
H)-one [BIT]	13mg/l (activated	mg/I Cyprinodon		mg/l (Daphnia		
2634-33-5	sludge) (OECD	variegatus EPA		Magna) OECD		
	209)	540/9-85-006		202		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
1,2-benzisothiazol-3(2H)-one [BIT]	0.7

12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022 Revision date 03-Jan-2025 Revision Number 2.01

Other information

Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user	Not regulated Not regulated Not regulated Not regulated Not applicable	
Special Provisions	None	
IMDG 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Marine pollutant 14.6 Special precautions for user Special Provisions 14.7 Maritime transport in bulk	Not regulated Not regulated Not regulated Not regulated NP None	
according to IMO instruments	Annex II of MARPOL and the IBC Code	Not applicable
Air transport (ICAO-TI / IATA-DGR) 14.1 UN number or ID number 14.2 UN proper shipping name		

	•••••••••••••••••••••••••••••••••••••••	
14.2	UN proper shipping name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	
Special Provisions		None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European

BOSTIK LIQUID COLOUR FOR CEMENT BLACK

Supercedes date 03-Oct-2022

parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) Regulation (EU) 2024/590 Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H302 - Harmful	if swallowed
H315 - Causes	skin irritation

- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H330 Fatal if inhaled
- H400 Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend			
TWA	TWA (time-weighted average)		
STEL	STEL (Short Term Exposure Limit)		
Ceiling	Ceiling Limit Value		
Sk*	Skin designation		
SVHC	Substance(s) of Very High Concern		
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals		
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals		
STOT RE	Specific target organ toxicity - Repeated exposure		
STOT SE	Specific target organ toxicity - Single exposure		
EWC	European Waste Catalogue		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by		
	Road		
IMDG	International Maritime Dangerous Goods (IMDG)		
ΙΑΤΑ	International Air Transport Association (IATA)		
RID	Regulations concerning the International Transport of Dangerous Goods by Rail		

Key literature references and sources for data				
No information available				
Prepared By	Product Safety & Regulatory Affairs			
Revision date	03-Jan-2025			
Indication of changes				

BOSTIK LIQUID COLOUR FOR CEMENT BLACK Supercedes date 03-Oct-2022 Revision date 03-Jan-2025 Revision Number 2.01

Revision Note Training Advice Further information SDS sections updated, 2, 3, 15. No information available No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet