

Revision date 15-Nov-2024

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER COATING

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin sensitisation Category 1 - (H317)

2.2. Label elements

Contains 1,2-benzisothiazol-3(2H)-one [BIT]; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]



Signal word Warning

United Kingdom - BE Page 1 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Revision date 15-Nov-2024

Hazard statements

H317 - May cause an allergic skin reaction.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing vapours

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-	REACH	EC No (EU	Classification	Specific	M-Factor	M-Factor	Notes
	%	registration	Index No)		concentration		(long-ter	
		number		Regulation (EC) No.	limit (SCL)		m)	
				1272/2008 [CLP]				
Diethylene glycol	1 - <2.5	01-2119475110	204-685-9	Eye Irrit. 2 (H319)	-	-	-	-
monobutyl ether		-51-XXXX						
acetate								
124-17-4								
Cellulose	1 - <2.5	[5]	232-674-9	No data available	_	-	-	-
9004-34-6								
1,2-benzisothiazol-3(0.01 <	01-2120761540	220-120-9	Acute Tox. 4 (H302)	Skin Sens.	1	1	
2H)-one [BIT]	0.036	-60-XXXX	(613-088-00-6)	Acute Tox. 2 (H330)	1A ::			
2634-33-5				Skin Irrit. 2 (H315)	C>=0.036%			
				Eye Dam. 1 (H318)				
				Skin Sens. 1A				
				(H317)				
				Aquatic Acute 1				
				(H400)				
				Aquatic Chronic 1				
				(H410)				
reaction mass of	0.0015 -	No data	611-341-5	Acute Tox. 3 (H301)	Eye Dam. 1 ::	100	100	В
5-chloro-2-methyl-2	< 0.0025	available		Acute Tox. 2 (H310)				
H-isothiazol-3-one				Acute Tox. 2 (H330)	Eye Irrit. 2 ::			
and				Skin Corr. 1C	0.06%<=C<0			
2-methyl-2H-isothiaz				(H314)	.6%			
ol-3-one (3:1)				Eye Dam. 1 (H318)				
[C(M)IT/MIT]				Skin Sens. 1A	:: C>=0.6%			
55965-84-9				(H317)	Skin Irrit. 2 ::			
				<u> </u>	0.06%<=C<0			
				(H400)	.6%			
				Aquatic Chronic 1	Skin Sens.			

United Kingdom - BE Page 2 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

Supercedes date 24-Jul-2023

COATING Revision Number 1.1

Revision date 15-Nov-2024

		(H410)	1A ::		
		(EUH071)	C>=0.0015%		

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour -	
					dust/mist - mg/L	vapour - mg/L	gas - ppm
Diethylene glycol monobutyl ether acetate	204-685-9	124-17-4	-	-	-	-	-
Cellulose	232-674-9	9004-34-6	-	-	-	-	-
1,2-benzisothiazol-3(2 H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21+	0.21+
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT]		55965-84-9	66	141	0.17	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

Show this safety data sheet to the doctor in attendance. General advice

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a doctor.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin

irritation or allergic reactions see a doctor.

Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never Ingestion

give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Itching. Rashes. Hives. **Symptoms**

United Kingdom - BE Page 3 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsMay cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

Revision date 15-Nov-2024

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

United Kingdom - BE Page 4 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Take off contaminated clothing and wash it before reuse.

Revision date 15-Nov-2024

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Kaolin	-	TWA: 2 mg/m ³
1332-58-7		STEL: 6 mg/m ³
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Aluminum hydroxide (Al(OH)3)	-	TWA: 10 mg/m ³
21645-51-2		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Cellulose	-	TWA: 10 mg/m ³
9004-34-6		TWA: 4 mg/m ³
		STEL: 20 mg/m ³
		STEL: 12 mg/m ³
Carbon black	-	TWA: 3.5 mg/m ³
1333-86-4		STEL: 7 mg/m ³
Silica, amorphous	-	TWA: 6 mg/m ³
7631-86-9		TWA: 2.4 mg/m ³
		STEL: 18 mg/m ³
		STEL: 7.2 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Diethylene glycol monobutyl ether acetate (124-17-4)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Dermal	100 mg/kg bw/d			

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)					
Type	Exposure route	Derived No Effect Level	Safety factor		
	·	(DNEL)	-		
worker	Inhalation	6.81 mg/m ³			
Long term		-			
Systemic health effects					

United Kingdom - BE Page 5 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Revision date 15-Nov-2024

worker	Dermal	0.966 mg/kg bw/d	
Long term			
Systemic health effects			

Derived No Effect Level (DNEL)						
Diethylene glycol monobutyl	Diethylene glycol monobutyl ether acetate (124-17-4)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Systemic health effects Long term	Dermal	60 mg/kg bw/d				
Consumer Systemic health effects Long term	Oral	7.9 mg/kg bw/d				

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)					
Туре	Exposure route		Safety factor		
		(DNEL)			
Consumer	Inhalation	1.2 mg/m ³			
Long term					
Systemic health effects					
Consumer	Dermal	0.345 mg/kg bw/d			
Long term					
Systemic health effects					

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)					
Diethylene glycol monobutyl ether acetate (124-17-4)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	0.108 mg/l				
Marine water	0.0108 mg/l				
Freshwater - intermittent	0.6 mg/l				
Sewage treatment plant	100 mg/l				
Freshwater sediment	0.8 mg/kg dry weight				
Marine sediment	0.08 mg/kg dry weight				
Soil	0.29 mg/kg dry weight				

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	4.03 μg/l				
Marine water	0.403 μg/l				
Sewage treatment plant	1.03 mg/l				
Freshwater sediment	49.9 μg/l				
Marine sediment	4.99 μg/l				
Soil	3 mg/kg dry weight				

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Hand protection

Tight sealing safety goggles.

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

United Kingdom - BE Page 6 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 **Revision Number** 1.1

None known

Revision date 15-Nov-2024

Skin and body protection Suitable protective clothing.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid

Appearance Thixotropic Paste

Colour Black

No information available. Odour

Remarks • Method **Property** Values

Melting point / freezing point No data available None known Initial boiling point and boiling No data available None known

range

Flammability No data available

Flammability Limit in Air None known

Upper flammability or explosive No data available

Lower flammability or explosive No data available

limits

Flash point No data available None known **Autoignition temperature** No data available None known **Decomposition temperature** None known None known.

No data available pН

pH (as aqueous solution) No data available

No data available Kinematic viscosity

Dvnamic viscosity No data available

Water solubility No data available. None known Solubility(ies) No data available None known Partition coefficient No data available None known Vapour pressure No data available None known

Relative density 1.36

No data available **Bulk density** Density No data available

No data available Relative vapour density None known

Particle characteristics

No information available **Particle Size Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available. Reactivity

10.2. Chemical stability

United Kingdom - BE Page 7 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

impact

None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Revision date 15-Nov-2024

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components).

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >2000 mg/kg

 ATEmix (dermal)
 149,031.30 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

Component Information

United Kingdom - BE Page 8 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Revision date 15-Nov-2024

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diethylene glycol monobutyl	=6500 mg/kg (Rattus)	5400 - 5700 mg/kg	=72500 mg/m ³ (Rattus) 4 h
ether acetate		(Oryctolagus cuniculus)	-
Cellulose	>5 g/kg (Rattus)	> 2 g/kg (Oryctolagus	>5800 mg/m³ (Rattus) 4 h
		cuniculus) > 2000 mg/kg	-
		(Oryctolagus cuniculus)	
1,2-benzisothiazol-3(2H)-one	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
[BIT]			
reaction mass of	66 mg/kg (Rat)	LD50 = 8141 mg/kg (Rat)	= 0.33 mg/L (Rat) 4h
5-chloro-2-methyl-2H-isothiazo		OECD 402	
I-3-one and			
2-methyl-2H-isothiazol-3-one			
(3:1) [C(M)IT/MIT]			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

United Kingdom - BE Page 9 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 **Revision Number** 1.1

Revision date 15-Nov-2024

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Diethylene glycol	=	LC50: 50 -	=	LC50: =665mg/L		
monobutyl ether acetate		70mg/L (96h,		(48h, Daphnia		
124-17-4		Brachydanio		magna)		
		rerio) LC50:				
		=77mg/L (96h,				
		Pimephales				
		promelas)				
1,2-benzisothiazol-3(2	EC50 3Hr	LC50 (96hr) 2.15	-	EC50(48hr) 2.94	1	1
H)-one [BIT]	13mg/l (activated	mg/l Cyprinodon		mg/l (Daphnia		
2634-33-5	sludge) (OECD	variegatus EPA		Magna) OECD		
	209)	540/9-85-006		202		
reaction mass of	EC50 (72h)	EC50 (96h) =	-	EC50 (48h) =0.1	100	100
5-chloro-2-methyl-2H-is	=0.048 mg/L	0.22 mg/L		mg/L (Daphnia		
othiazol-3-one and	(Pseudokirchner	(Oncorhynchus		magna) (OECD		
2-methyl-2H-isothiazol-	iella subcapitata)	mykiss) (OECD		202)		
3-one (3:1)	(OECD 201)	211)				
[C(M)IT/MIT]	,	•				
55965-84-9						

12.2. Persistence and degradability

Persistence and degradability No information available.

Diethylene glycol monobutyl ether acetate (124-17-4)			
Method	Exposure time	Value	Results
OECD Test No. 301C: Ready	28 days	100%	Readily biodegradable
Biodegradability: Modified MITI Test	-		
(I) (TG 301 C)			

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Test			
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Diethylene glycol monobutyl ether acetate	1.7
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the PBT and vPvB assessment

threshold of declaration.

	Chemical name	PBT and vPvB assessment
--	---------------	-------------------------

United Kingdom - BE Page 10 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Diethylene glycol monobutyl ether acetate	The substance is not PBT / vPvB
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

Revision date 15-Nov-2024

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group

Not regulated
Not regulated
Not regulated
Not regulated

14.5 Marine pollutant NP14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

United Kingdom - BE Page 11 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Revision date 15-Nov-2024

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide: Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

United Kingdom - BE Page 12 / 13

IDENDEN 30-150 BLACK BRUSHABLE VAPOUR BARRIER

COATING

Supercedes date 24-Jul-2023 Revision Number 1.1

Revision date 15-Nov-2024

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H301 - Toxic if swallowed H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H319 - Causes serious eye irritation

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 15-Nov-2024

Indication of changes

Revision Note SDS sections updated, 3.
Training Advice No information available
Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13