



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Preparation of safety data sheets for hazardous chemicals Code of Practice June 2023

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name ULTRA MASTIK NSW

Product Code(s)

30840346

30615421; 30840346; 30840252

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Building and construction work Adhesive

Uses advised against No information available.

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

Label elements

Exclamation mark
Corrosion

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024



Signal word
DANGER

Hazard statements

H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wear protective gloves/clothing and eye/face protection
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor
IF ON SKIN: Wash with plenty of water and soap
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read carefully and follow all instructions.
Contact with product at elevated temperatures can result in thermal burns.
Product dust may be irritating to eyes, skin and respiratory system.
Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin.
Repeated exposure may cause skin dryness or cracking.
Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.
When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No.	Weight-%
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	10 - 30
Calcium diformate	544-17-2	1 - 5

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

Non-hazardous ingredients	Proprietary	Balance
---------------------------	-------------	---------

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Take a copy of the Safety Data Sheet when going for medical treatment.

Inhalation **Solid:** . Inhalation of dust/particles. Blow nose. Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact **Solid:** . Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash before reuse.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Dust irritates eyes and air passages.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical The melted product can cause severe burns.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2).

Special protective actions for fire-fighters

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containment Prevent product from entering drains. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Prevent dust cloud. Cover powder spill with plastic sheet or tarp to minimize spreading. Do not touch or walk through spilled material.

Methods for cleaning up **Solid:** . Take up dust-free and set down dust-free. Do not breathe dust. Take precautionary measures against static charges. Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust. Avoid generation of dust. Pick up and transfer to properly labeled containers. Use personal protective equipment as required.

Precautions to prevent secondary hazards

Prevention of secondary hazards Eliminate all ignition sources if safe to do so. Powdered material may form explosive dust-air mixtures. Use non-sparking tools. Extremely slippery when spilled.

Reference to other sections See section 8 for more information.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use adequate ventilation and/or engineering controls in high temperature processing to prevent exposure to vapors. Ensure adequate ventilation. Avoid generation of dust. Use personal protection equipment. Take off contaminated clothing and wash before reuse. Avoid contact with skin and eyes. Do not breathe dust.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. For cements treated with a Cr (VI) reducing agent the effectiveness of the reducing agent diminishes with time and if not stored in an appropriate manner. After absorption of moisture or exceeding the shelf life the reducing agent for chromate will lose its efficiency and sensitization by skin contact may occur.

Recommended storage temperature Keep at temperatures between 41 and 86 °F / 5 and 30 °C.

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	TWA: 10 mg/m ³

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Hand protection For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Nitrile rubber.

Respiratory protection High efficiency particulate air filter. Recommended filter type: P3. Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Solid
Appearance	Powder
Color	White
Odor	No information available
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable
pH (as aqueous solution)	No data available	Insoluble in water
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	No data available	
Evaporation rate	No data available	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Relative vapor density	No data available	
Relative density	1.49 kg/L	
Water solubility	Insoluble in water	Cement based

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

	products react and solidify in contact with water
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No information available
Oxidizing properties	No information available
Other information	
Solid content (%)	No information available
Density	No information available
VOC content	No information available

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under recommended storage conditions. Keep away from Incompatible materials.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions Fine dust dispersed in air, in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Conditions to avoid

Conditions to avoid Under dusty conditions avoid all sources of ignition, including sparks and static electricity. Product cures with moisture.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂).

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000
ATEmix (dermal)	>5000
ATEmix (inhalation-gas)	>20000
ATEmix (inhalation-vapor)	>20
ATEmix (inhalation-dust/mist)	>5

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m ³ (Rattus)
Calcium diformate	=2650 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
Respiratory or skin sensitization	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Dust irritating to respiratory tract. Thermal decomposition can lead to release of irritating gases and vapors. May cause respiratory irritation.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Calcium diformate 544-17-2	RC50 (72h) > 1000 mg/l (Pseudokirchnerella subcapitata)	LC50: >=1000mg/L (96h, Brachydanio rerio)	-	EC50 (48h) > 1000 mg/l (Daphnia magna) EPA-660/3-75-009

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Illicit Drug Precursors/Reagents

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

International Inventories

AIIC	Complies
NZIoC	Not Listed
ENCS	Not Listed
IECSC	Complies
KECL	Complies
PICCS	Not Listed

Legend:

- AIIC - Australian Inventory of Industrial Chemicals
- NZIoC - New Zealand Inventory of Chemicals
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing Chemicals Inventory
- PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Directive 2011/65/EU (EU RoHS 2), as amended by the Delegated Directive (EU) 2015/863 (EU RoHS 3)

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Revision date 16-Jan-2025

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

ULTRA MASTIK NSW
Revision Number 2

Revision date 16-Jan-2025
Supersedes date 03-Apr-2024

TWA TWA (time-weighted average)
Ceiling Maximum limit value
C Carcinogen

STEL
Sk*

STEL (Short Term Exposure Limit)
Skin designation

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet