

DAMPFIX IMMERSED POWDER

Revision Number 2.01

Revision date27-Apr-2023Supersedes Date:13-Dec-2021

Section 1: Identification: Product	identifier and chemical identity
Product identifier	
Product Name	DAMPFIX IMMERSED POWDER
Product Code(s) 30840501 30840501	
Other means of identification	
Pure substance/mixture	Mixture
Recommended use of the chemica	al and restrictions on use
Recommended use	Waterproofing Sealers
Uses advised against	No information available
Details of manufacturer or imported	<u>er</u>
Supplier Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia Tel: 613 9279-9333 Fax: 613 9279-9342	
ABN: 79 003 893 838	
E-mail address	au-bostik-sds@bostik.com
Emergency telephone number	
Emergency telephone number	24-hr Emergency: 1800 033 111
Section 2: Hazard(s) identification	

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)

Label elements

Corrosion



DAMPFIX IMMERSED POWDER

Revision Number 2.01

Signal word DANGER

Hazard statements

H315 - Causes skin irritation H318 - Causes serious eye damage Repeated exposure may cause skin dryness or cracking

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/clothing and eye/face protection IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a doctor IF ON SKIN: Wash with plenty of water and soap If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash it before reuse

Other hazards which do not result in classification

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system.

Repeated exposure may cause skin dryness or cracking.

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	10 - <30
Sulfuric acid, aluminum salt (3:2)	10043-01-3	< 1%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures		
Emergency telephone number	Poisons Information Center, Australia: 13 11 26 Poisons Information Center, New Zealand: 0800 764 766	
Description of first aid measures		
General advice	If medical advice is needed, have product container or label at hand.	
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.	
Eye contact	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.	
Skin contact	Brush off loose particles from skin. Remove material from skin immediately. Take off	
Australia - EN	Page 2/9	

	contaminated clothing and wash before reuse.	
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.	
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).	
Most important symptoms and effects, both acute and delayed		
Symptoms	Burning sensation. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	

Section 5: Firefighting measures		
Suitable Extinguishing Media		
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Unsuitable extinguishing media	No information available.	
Specific hazards arising from the c	<u>chemical</u>	
Specific hazards arising from the chemical	No information available.	
Hazardous combustion products	Carbon oxides. Sulfur oxides.	
Special protective actions for fire-fighters		
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	
Section 6: Accidental release meas	sures	
Personal precautions, protective e	quipment and emergency procedures	
Personal precautions	Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.	
Other information	Refer to protective measures listed in Sections 7 and 8.	
For emergency responders	Use personal protection recommended in Section 8.	
Environmental precautions		
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil.	
Methods and material for containm	nent and cleaning up	
Methods for containment	Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Prevent dust cloud.	

DAMPFIX IMMERS	ED POWDER
Revision Number	2.01

Methods for cleaning up	Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.		
Precautions to prevent secondary	hazards		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
Section 7: Handling and storage, i	ncluding how the chemical may be safely used		
Precautions for safe handling			
Advice on safe handling	Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take off contaminated clothing and wash before reuse.		
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.		
Conditions for safe storage, including any incompatibilities			
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.		
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.		

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	TWA: 10 mg/m ³
Sulfuric acid, aluminum salt (3:2) 10043-01-3	TWA: 2 mg/m ³

Appropriate engineering controls

Engineering controlsShowers, eyewash stations, and ventilation systems.Individual protection measures, such as personal protective equipmentEye/face protectionTight sealing safety goggles.Skin and body protectionWear suitable protective clothing. Long sleeved clothing.Hand protectionWear suitable gloves. Impervious gloves.Respiratory protectionRecommended filter type:. Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.Environmental exposure controlsNo information available.Section 9: Physical and chemical properties

DAMPFIX IMMERSED POWDER

Revision Number 2.01

Information on basic physical and chemical properties

Physical state Appearance Color Odor Odor threshold	Solid Powder Gray Odorless No information available	
Property	Values	Remarks • Method
рН	No data available	
pH (as aqueous solution)	No data available	
Melting point / freezing point	Not applicable . °C	
Initial boiling point and boiling	Not applicable . °C	
range		
Flash point	Not applicable . °C	
Evaporation rate	Not applicable .	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits		
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Relative vapor density	No data available	
Relative density	1.25	
Water solubility	Insoluble in water Cement based	
	products react and solidify in contact	
	with water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	Not applicable .	
Dynamic viscosity	Not applicable . No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other information		
Softening Point	Not relevant	
Solid content (%)	No information available	
Liquid Density	No information available	
VOC content	1 g/L	SCAQMD Method 304-91
	5	
Section 10: Stability and reactivity		
Reactivity		
Reactivity	Product cures with moisture.	
Chemical stability		

Stability

Keep away from Incompatible materials. Stable under recommended storage conditions.

Explosion data Sensitivity to mechanical None. impact Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid	
Conditions to avoid	Product cures with moisture.
Incompatible materials	
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.
Hazardous decomposition product	<u>s</u>
Hazardous decomposition products	Carbon oxides. Nitrogen oxides (NOx).
Section 11: Toxicological informati	on
Acute toxicity	
Information on likely routes of expo	osure
Product Information	
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)
Sulfuric acid, aluminum salt (3:2)	>2000 mg/kg (Rattus)	> 5000 mg/kg (Rabbit)	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
Respiratory or skin sensitization	No information available.

Germ cell mutagenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Sulfuric acid, aluminum salt (3:2)	-	LC50 96 h = 100 mg/L (Carassius auratus)	-	EC50: =136mg/L (15min, Daphnia magna)
10043-01-3				Daprina magna)

Persistence and degradability

Persistence and degradability	No information available.	
Bioaccumulative potential Bioaccumulation	No information available.	
<u>Mobility</u>		
Mobility in soil	No information available.	
Mobility	No information available.	
Other adverse effects		
Other adverse effects	No information available.	
Section 13: Disposal consideration	ns	
Disposal methods		
Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.	
Contaminated packaging	Do not reuse empty containers.	
Section 14: Transport information		
ADG	Not regulated	
ΙΑΤΑ	Not regulated	

IMDG

Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)No poisons schedule number allocatedPoison Schedule NumberNot applicable

International Inventories	
AIIC	Listed
NZIoC	Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

Legend:

AIIC - Australian Inventory of Industrial Chemicals

NZIOC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

DAMPFIX IMMERSED POWDER Revision Number 2.01

Section 16: Any other relevant information

Prepared By

Product Safety & Regulatory Affairs

Revision date

27-Apr-2023

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

 TWA
 TWA (time-weighted average)

 Ceiling
 Maximum limit value

 C
 Carcinogen

 Section 11: TOXICOLOGICAL INFORMATION

 LD50 (lethal dose)

 Section 12: Ecological information

 EC50 (effective concentration)

STEL (Short Term Exposure Limit) Skin designation

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

STEL

End of Safety Data Sheet