



SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

1. Identification

1.1. Product Identifier

Product Name WEBCRETE(R) 95

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cement.
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1 (800) 843-0844 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)
Fax: +1 (414) 774-8075

E-mail msds@bostik.com

1.4. Emergency telephone number

Telephone: 1-800-227-0332
(Outside U.S.) 1-703-527-3887

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

2.2. Label Elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018



Appearance No information available **Physical State** Solid **Odor** No information available

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown acute toxicity

9 % of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Product dust may be irritating to eyes, skin and respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical name	CAS No.	Weight-%
---------------	---------	----------

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

Limestone	1317-65-3	30 - 60
Cement, alumina, chemicals	65997-16-2	10 - 30
Cement, portland, chemicals	65997-15-1	10 - 30
Calcium sulfate dihydrate	10101-41-4	1 - 5
Gypsum (Ca(SO ₄).2H ₂ O)	13397-24-5	1 - 5
Quartz	14808-60-7	1 - 5

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	Brush off loose particles from skin. Wash off immediately with plenty of water for at least 15 minutes. May cause sensitization by skin contact. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Ingestion	Do NOT induce vomiting. If swallowed, seek medical advice immediately and show this container or label. Rinse mouth.
Self-protection of the first aider	Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Irritating to skin. Causes serious eye damage. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization in susceptible persons. Product dust may be irritating to eyes, skin and respiratory system.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization of susceptible persons. May cause sensitization by skin contact. Treat symptomatically.
---------------------------	---

4.4. Reference to Other Sections

Reference to other sections	Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION Section 11: TOXICOLOGY INFORMATION
------------------------------------	--

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media
Use extinguishing agent suitable for type of surrounding fire.

Unsuitable extinguishing media
None known.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical
Thermal decomposition can lead to release of irritating and toxic gases and vapors.

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

Hazardous combustion products Carbon oxides.

Explosion Data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

5.3. Advice for firefighters

Special protective actions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Avoid creating dust. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing and eye/face protection.

For emergency responders Sweep up to prevent slipping hazard.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent dust cloud. Take up mechanically, placing in appropriate containers for disposal. Protect from moisture.

Methods for cleaning up Use personal protective equipment as required. Sweep up and shovel into suitable containers for disposal. Avoid creating dust. Clean contaminated surface thoroughly.

6.4. Reference to other sections

Reference to other sections Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Avoid generation of dust. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin and eyes. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep out of the reach of children. Keep containers tightly closed in a cool, well-ventilated place. Protect from direct contact with water or excessive moisture. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Incompatible materials None known based on information supplied.

7.3. Specific end use(s)

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

Specific Use(s)
Cement.

Other information No information available.

7.4. References to Other Sections

Reference to other sections Section 13: DISPOSAL CONSIDERATIONS
Section 10: STABILITY AND REACTIVITY

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Limestone 1317-65-3	No data available	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	-
Cement, alumina, chemicals 65997-16-2	10 mg/m ³ (total; 5 mg/m ³ (resp)	-	-	-
Cement, portland, chemicals 65997-15-1	TWA: 1 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	IDLH: 5000 mg/m ³ TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica	TWA: 1 mg/m ³
Calcium sulfate dihydrate 10101-41-4	TWA: 10 mg/m ³ inhalable particulate matter	-	-	TWA: 10 mg/m ³
Gypsum (Ca(SO4).2H2O) 13397-24-5	TWA: 10 mg/m ³ inhalable particulate matter	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	TWA: 0.025 mg/m ³

Chemical name	Argentina	Brazil	Chile	Venezuela
Limestone 1317-65-3	TWA: 10 mg/m ³	-	TWA: 7 mg/m ³	-
Cement, portland, chemicals 65997-15-1	TWA: 10 mg/m ³	TWA: 1 mg/m ³	TWA: 8.8 mg/m ³	TWA: 10 mg/m ³
Calcium sulfate dihydrate 10101-41-4	-	TWA: 10 mg/m ³	-	-
Gypsum (Ca(SO4).2H2O) 13397-24-5	-	TWA: 10 mg/m ³	TWA: 8.8 mg/m ³	-
Quartz 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.08 mg/m ³	TWA: 0.025 mg/m ³

8.2. Exposure controls

Engineering controls Showers

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

Eyewash stations
Ventilation systems.

Personal protective equipment [PPE]

Eye/face protection Wear safety glasses with side shields (or goggles).
Skin and body protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General hygiene considerations Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Regular cleaning of equipment, work area and clothing is recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Solid
Color Gray
Odor No information available
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No data available	
Flash point	> 93.3 °C / > 200 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability or explosive limits	No information available	
Lower flammability or explosive limits	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	Cement based products react and solidify in contact with water	
Solubility in Other Solvents		
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

9.2. Other information

Softening Point No information available
Molecular weight No information available
Solvent content (%) No information available
Solid content (%) 100
Density 2.600 g/cm³

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

VOC Content (%) < .1 g/L

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Protect from moisture.

10.5. Incompatible materials

None known based on information supplied.

10.6. Hazardous decomposition products

None known based on information supplied.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product Information

Inhalation

No data available

Eye contact

May cause irritation of respiratory tract.

Skin contact

Avoid contact with eyes. Corrosive to eyes.

Ingestion

Irritating to skin. May cause sensitization by skin contact.

No data available.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Cement, alumina, chemicals 65997-16-2	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rat	-
Cement, portland, chemicals 65997-15-1	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
Quartz 14808-60-7	>20000 mg/kg	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Symptoms

No information available.

Skin corrosion/irritation

Irritating to skin.

Serious eye damage/eye irritation

Causes severe eye damage.

Irritation

No information available.

Corrosivity

No information available.

Sensitization

May cause sensitization by skin contact.

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

Germ cell mutagenicity	No information available.
Reproductive toxicity	No information available.
Developmental toxicity	No information available.
Teratogenicity	No information available.
STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Chronic Toxicity	Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure.
Target organ effects	Eyes, Skin, Lungs, Respiratory system.
Aspiration hazard	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
 IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
 NTP (National Toxicology Program)
Known - Known Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h) >10000mg/L (Oncorhynchus mykiss)		CE50 (48h) >1000 mg/L Daphnia Magna
Cement, alumina, chemicals 65997-16-2	EC50 (72h) Algae (Pseudokirchneriella subcapitata) >5.6mg/L	LC50 (96h) (Oncorhynchus mykiss) >100 mg/L (OECD 203)		EC50 (48h) Daphnia magna =6.6mg/L (OECD 202)

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

13.1. Waste treatment methods

Disposal of Wastes It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

Contaminated packaging Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG Not regulated

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Classification is shown in section 2 of this SDS

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

Key Literature References and Sources for Data

SAFETY DATA SHEET

WEBCRETE(R) 95
Revision Number 3

Revision date 02-Jan-2020
Supersedes Date: 03-Jan-2018

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	02-Jan-2020
Revision note	SDS sections updated, 1, 2, 3, 8, 11, 12, 15.
Training Advice	No information available
Further information	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet