

In accordance with OSHA 29 CFR 1910.1200

MVP4(R) Revision Number 4 Revision date 25-Sep-2024 Supersedes date 03-Jan-2019

1. Identification

1.1. Product identifier

Product Name MVP4(R)

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.

11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA

Phone: +1(800) 726-7845 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)

Chemtrec: 1-800-424-9300 (US), 1-703-527-3887 (Outside U.S.)

Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Respiratory sensitization	Category 1
Flammable liquids	Category 4

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled Combustible liquid

US - EN Page 1 / 11

MVP4(R)Revision date25-Sep-2024Revision Number4Supersedes date03-Jan-2019



Appearance Paste Physical state Liquid Odor No information available

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray In case of inadequate ventilation wear respiratory protection Keep away from flames and hot surfaces. - No smoking Wear protective gloves/eye protection/face protection

Precautionary Statements - Response

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing If experiencing respiratory symptoms: Call a POISON CENTER or doctor In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Information

No information available.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Limestone	1317-65-3	30 - 60
Naphtha (petroleum), hydrotreated heavy, <0.1%	64742-48-9	1 - <5
Benzene		
Propylene carbonate	108-32-7	1 - <5
Quartz	14808-60-7	0.1 - <1
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - <1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. First-aid measures

4.1. Description of first aid measures

US - EN Page 2 / 11

MVP4(R)

Revision Number 4

General advice Show this safety data sheet to the doctor in attendance.

Inhalation May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration.

Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use

barrier to give mouth-to-mouth resuscitation. Get immediate medical attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic

reactions see a physician.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give

anything by mouth to an unconscious person. Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section

8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or

wheezing. Itching. Rashes. Hives.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. Fire-Fighting Measures

5.1. Extinguishing media

Suitable Extinguishing Media

Large Fire

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media CAUTION: All these products have a very low flash point: Use of water spray when fighting

fire may be inefficient.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Product is or contains a sensitizer. May cause sensitization

by inhalation.

Hazardous combustion products Carbon oxides. Carbon dioxide (CO2). Sulfur oxides.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

US - EN Page 3 / 11

MVP4(R)

Revision Number 4

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

or walk through spilled material. Evacuate personnel to safe areas. Stop leak if you can do it without risk. Take precautionary measures against static discharges. Avoid contact with

skin, eyes or clothing. Keep people away from and upwind of spill/leak.

Other information Water spray may reduce vapor; but may not prevent ignition in closed spaces. Refer to

protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for

additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containmentStop leak if you can do it without risk. Contain and collect spillage with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up

Use personal protective equipment as required. Dam up. Soak up with inert absorbent

material. Take up mechanically, placing in appropriate containers for disposal. Take precautionary measures against static discharges. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Handle in accordance with good industrial hygiene and

safety practice. Do not eat, drink or smoke when using this product. Use with local exhaust ventilation. Do not breathe vapor or mist. Wash thoroughly after handling. Take off

contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and

well-ventilated place. Store locked up. Keep out of the reach of children. Protect from

moisture.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

7.3 References to other sections

US - EN Page 4 / 11

MVP4(R)Revision date25-Sep-2024Revision Number4Supersedes date03-Jan-2019

Reference to other sections Section 10: STABILITY AND REACTIVITY

Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product contains substances which in their raw state are powder form, however in this

product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to

occur from exposure to this product.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Limestone	-	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³ total dust
1317-65-3		TWA: 5 mg/m ³ respirable	TWA: 5 mg/m ³ respirable dust
		fraction	_
		(vacated) TWA: 15 mg/m³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
Quartz	TWA: 0.025 mg/m³ respirable	TWA: 50 μg/m³	IDLH: 50 mg/m ³ respirable dust
14808-60-7	particulate matter	(vacated) TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³ respirable
		respirable dust	dust
		: (250)/(%SiO2 + 5) mppcf	
		TWA respirable fraction	
		: (10)/(%SiO2 + 2) mg/m ³	
		TWA respirable fraction	

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Limestone	TWA: 10 mg/m ³	-	LPP: 7 mg/m ³	-
1317-65-3	-		LPP: 5 mg/m ³	
Quartz 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	LPP: 0.08 mg/m ³	TWA: 0.025mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Quartz	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m ³ TWA	TWA: 0.025 mg/m ³
14808-60-7			(respirable particulate	
			matter)	

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only

depend on the material, but also on further marks of quality and various manufacturers.

US - EN Page 5 / 11

MVP4(R)

Revision Number 4

Revision Number 4

Revision Number 4

Revision Number 4

Supersedes date 03-Jan-2019

Skin and body protectionWear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial

hygiene and safety practice. Do not eat, drink or smoke when using this product. Regular

cleaning of equipment, work area and clothing is recommended.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Appearance Paste Color Gray

Odor No information available
Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pHNo data availableNone knownpH (as aqueous solution)No data availableNone knownMelting point / freezing pointNo data availableNone known

Initial boiling point and boiling range 172 °C / 341.6 °F

Flash point > 86 °C / 186.8 °F ASTM 3278
Evaporation rate No data available None known
Flammability No data available None known
Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

No data available None known Vapor pressure Relative vapor density No data available None known Relative density No data available None known Water solubility No data available None known Solubility(ies) No data available None known No data available Partition coefficient None known No data available None known **Autoignition temperature Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known

9.2. Other information

Explosive properties

Oxidizing properties

No information available

No information available

No information available

Solid content (%) 91.7

Softening point No information available
Molecular weight No information available

VOC content

Liquid Density 1.462 g/cm³

Bulk density No information available

No information available

10. Stability and reactivity

US - EN Page 6 / 11

MVP4(R)

Revision Number 4

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Hazardous polymerization may occur.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Protect from moisture.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation May cause sensitization in susceptible persons.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion May cause additional affects as listed under "Inhalation".

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling

of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing.

Coughing and/ or wheezing.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >5000 mg/kg

 ATEmix (dermal)
 24,760.10 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapor)
 >20 mg/l

US - EN Page 7 / 11

MVP4(R)Revision date25-Sep-2024Revision Number4Supersedes date03-Jan-2019

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	•	-
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	>6000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	>8500 mg/m³ (Rattus) 4 h
Propylene carbonate 108-32-7	LD50 > 5000 mg/kg (Rattus) OECD 401	> 3000 mg/kg (Oryctolagus cuniculus)	-
Quartz 14808-60-7	>2000 mg/kg (Rattus)	-	-
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	=2234 mg/kg (Rattus)	LD 50 (Rattus) > 2000 mg/kg OECD 402	>640 ppm (Rattus) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity This product contains substances which in their raw state are powder form, however in this

product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to

occur from exposure to this product.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz	A2	Group 1	Known	X
14808-60-7				

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposureBased on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Target organ effects Respiratory system, Eyes, Skin.

Aspiration hazard Based on available data, the classification criteria are not met.

Other adverse effects

No information available.

Interactive effects

No information available.

US - EN Page 8 / 11

MVP4(R)

Revision Number 4

Revision Number 4

Revision Number 4

Revision Number 4

Supersedes date 03-Jan-2019

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmondesmus subspicatus)	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	-	LC50: =2200mg/L (96h, Pimephales promelas)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
Propylene carbonate 108-32-7	ErC50 (72h): > 900mg/L (Desmodesmus subspicatus, OECD-201)	LC50 (96) h > 1000 mg/L (Cyprinus carpio, 67/548/EWG, Annex V, C.1.)	EC50 > 10000 mg/L 17 h	EC50 (48h): > 1000mg/L (Daphnia magna, OECD 202)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Limestone	0.9
1317-65-3	
Propylene carbonate	-0.41
108-32-7	
Benzenesulfonyl isocyanate, 4-methyl-	0.6
4083-64-1	

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

US - EN Page 9 / 11

MVP4(R)

Revision Number 4

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: This corrosive material, as per 49 CFR §173.154 and when the product meets the

packaging requirements of 49 CFR §173.154 (b)(2) [inner packagings not over 5.0 kg (11lbs) net capacity each for, and packed in strong outer packagings] is excepted from labeling and placarding requirements so long as the material is not offered for transport by

aircraft.

DOT

UN number or ID number NA1993

UN proper shipping name Combustible liquid, n.o.s. Transport hazard class(es) Combustible liquid

Packing group ||

Special Provisions IB3, T1,TP1, 148

DOT Marine Pollutant NP

Description NA1993, Combustible liquid, n.o.s.(Naphtha, petroleum, heavy alkylate), III

Emergency Response Guide 128

Number

IATA Not regulated

IMDG Not regulated

15. Regulatory information

International Inventories

TSCA	Complies
DSL	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Complies - The components of this product are either listed or exempt from listing on inventory. Active

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

US - EN Page 10 / 11

MVP4(R)Revision date25-Sep-2024Revision Number4Supersedes date03-Jan-2019

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

Prepared By Product Stewardship and Regulatory Affairs.

Revision date 25-Sep-2024

Revision Note SDS sections updated. 3.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at

https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-mana gement/medical-device-policy/ which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet

US - EN Page 11 / 11