



Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

1. Identification

1.1. Product Identifier

Product Name ULTRAFINISH(TM) PRO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cement.
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1 (800) 843-0844 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)
Fax: +1 (414) 774-8075

Manufacturer

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1 (800) 843-0844 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)
Fax: +1 (414) 774-8075

E-mail msds@bostik.com

1.4. Emergency telephone number

Telephone: 1-800-227-0332
(Outside U.S.) 1-703-527-3887

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

2.2. Label Elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes serious eye damage
May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure
May cause respiratory irritation

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016



Appearance Powder

Physical State Solid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see first aid measures on this label)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

Not applicable

Unknown acute toxicity

31 % of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Product dust may be irritating to eyes, skin and respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	CAS No.	Weight-%
---------------	---------	----------

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Cement, alumina, chemicals	65997-16-2	30 - 60
Ashes, residues	68131-74-8	5 - 10
Quartz	14808-60-7	5 - 10
Limestone	1317-65-3	3 - 7
Calcium Sulfoaluminate Cement	960375-09-1	1 - 5
Calcium sulfate	7778-18-9	1 - 5
Slags, ferrous metal, blast furnace	65996-69-2	1 - 5
Calcium oxide	1305-78-8	1 - 5
Bentonite	1302-78-9	1 - 5
Cellulose	9004-34-6	1 - 5
Cement, portland, chemicals	65997-15-1	0.1 - 1

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	Immediate medical attention is required. If symptoms persist, call a physician.
Eye contact	If symptoms persist, call a physician. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin contact	If skin irritation persists, call a physician. Brush off loose particles from skin. Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Ingestion	Do NOT induce vomiting. If swallowed, seek medical advice immediately and show this container or label. Rinse mouth.
Self-protection of the first aider	Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization of susceptible persons. Treat symptomatically.

4.4. Reference to Other Sections

Reference to other sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
Section 11: TOXICOLOGY INFORMATION

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media
Use extinguishing agent suitable for type of surrounding fire.

Unsuitable extinguishing media
None known.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical
Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

5.3. Advice for firefighters

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid creating dust. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing and eye/face protection.

For emergency responders Sweep up to prevent slipping hazard.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent dust cloud. Take up mechanically, placing in appropriate containers for disposal.

Methods for cleaning up Sweep up and shovel into suitable containers for disposal. Avoid creating dust.

6.4. Reference to other sections

Reference to other sections Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling Wash contaminated clothing before reuse. Handle in accordance with good industrial hygiene and safety practice. Avoid generation of dust. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep out of the reach of children. Protect from direct contact with water or excessive moisture. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed and dry. Product cures with moisture. Keep from freezing.

Incompatible materials Acids. Aluminum. Alkali.

7.3. Specific end use(s)

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Specific Use(s)
Cement.

Other information No information available.

7.4. References to Other Sections

Reference to other sections Section 13: DISPOSAL CONSIDERATIONS
Section 10: STABILITY AND REACTIVITY

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Cement, alumina, chemicals 65997-16-2	10 mg/m ³ (total; 5 mg/m ³ (resp)	-	-	-
Ashes, residues 68131-74-8	TWA: 1 mg/m ³ Cu dust and mist	IDLH: 100 mg/m ³ Cu dust and mist IDLH: 10 mg/m ³ Ni Ceiling: 0.05 mg/m ³ V dust and fume 15 min TWA: 1 mg/m ³ Cu dust and mist TWA: 0.015 mg/m ³ except Nickel carbonyl Ni	-	-
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	TWA: 0.1 mg/m ³
Limestone 1317-65-3	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ STEL: 20 mg/m ³
Calcium sulfate 7778-18-9	TWA: 10 mg/m ³ inhalable particulate matter	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³
Calcium oxide 1305-78-8	TWA: 2 mg/m ³	IDLH: 25 mg/m ³ TWA: 2 mg/m ³	TWA: 5 mg/m ³	TWA: 2 mg/m ³
Bentonite 1302-78-9	TWA: 1 mg/m ³ respirable particulate matter	-	-	-
Cellulose 9004-34-6	TWA: 10 mg/m ³	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 1 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ STEL: 20 mg/m ³
Cement, portland, chemicals 65997-15-1	TWA: 1 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	IDLH: 5000 mg/m ³ TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica	TWA: 10 mg/m ³ STEL: 20 mg/m ³

Chemical Name	Argentina	Brazil	Chile	Venezuela
Quartz 14808-60-7	TWA: 0.05 mg/m ³	-	TWA: 0.08 mg/m ³	TWA: 0.025 mg/m ³
Limestone 1317-65-3	TWA: 10 mg/m ³	-	TWA: 7 mg/m ³	-
Calcium sulfate 7778-18-9	TWA: 10 mg/m ³	-	-	TWA: 10 mg/m ³

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Calcium oxide 1305-78-8	TWA: 2 mg/m ³	-	TWA: 1.75 mg/m ³	TWA: 2 mg/m ³
Cellulose 9004-34-6	TWA: 10 mg/m ³	-	TWA: 8.8 mg/m ³	TWA: 10 mg/m ³
Cement, portland, chemicals 65997-15-1	TWA: 10 mg/m ³	-	TWA: 8.8 mg/m ³	TWA: 10 mg/m ³

8.2. Exposure controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Personal protective equipment [PPE]

Eye/face protection Tight sealing safety goggles. Face protection shield. Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General hygiene considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Keep away from food, drink and animal feeding stuffs.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Solid
Appearance Powder
Color Gray
Odor No information available
Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash Point	No data available °C / °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability or explosive limits	No information available	
Lower flammability or explosive limits	No information available	
Vapor Pressure	No information available	
Vapor Density	No information available	
Relative Density	No information available	None known
Water Solubility	Partially soluble	
Solubility in Other Solvents		
Partition coefficient	No information available	
Autoignition Temperature	No information available	
Decomposition Temperature	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	No information available	

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Explosive properties No information available
Oxidizing properties No information available

9.2. Other information

Softening Point No information available
Molecular Weight No information available
Solvent content (%) No information available
Solid content (%) 100
Density No information available
VOC (volatile organic compound) No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Incompatible materials. Protect from moisture. Product cures with moisture. Keep away from heat, sparks and flames.

10.5. Incompatible materials

Acids. Aluminum. Alkali.

10.6. Hazardous decomposition products

Carbon oxides. Hydrogen sulfide.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product information No data available
Inhalation May cause irritation of respiratory tract.
Eye contact Corrosive to eyes.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Cement, alumina, chemicals 65997-16-2	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rat	-
Ashes, residues 68131-74-8	> 2000 mg/kg (Rat)	-	-
Quartz 14808-60-7	>20000 mg/kg	-	-
Limestone 1317-65-3	>5000 mg/kg (rat)	-	-

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Calcium Sulfoaluminate Cement 960375-09-1	>2000 mg/Kg	-	-
Calcium sulfate 7778-18-9	> 3000 mg/kg (Rat)	-	CL50 >2.61 mg/L (4h) Rat
Slags, ferrous metal, blast furnace 65996-69-2	LD50 >2000 mg/Kg	-	-
Calcium oxide 1305-78-8	>2000 mg/kg (Rat)	LD50 > 2500 mg/kg (rabbit)	-
Bentonite 1302-78-9	> 5000 mg/kg (Rat)	-	-
Cellulose 9004-34-6	> 5 g/kg (Rat)	> 2 g/kg (Rabbit) > 2000 mg/kg (Rabbit)	> 5800 mg/m ³ (Rat) 4 h
Cement, portland, chemicals 65997-15-1	LD50 >2000 mg/Kg (Rat)	LD50 >2000 mg/Kg	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Symptoms	No information available.
Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	Causes severe eye damage.
Irritation	No information available.
Corrosivity	No information available.
Sensitization	No information available. May produce an allergic reaction.
Germ Cell Mutagenicity	No information available.
Reproductive Toxicity	No information available.
Developmental Toxicity	No information available.
Teratogenicity	No information available.
STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Chronic Toxicity	Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. May cause adverse liver effects.
Target Organ Effects	Eyes, Respiratory system, Skin, Kidney, Liver, Lungs, Nasal Cavities.
Aspiration hazard	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ashes, residues 68131-74-8	-	Group 1	Known	X
Quartz 14808-60-7	A2	Group 1	Known	X
Cellulose 9004-34-6	-	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
---------------	----------------------	------	-------------	-----------

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

			Microorganisms	
Cement, alumina, chemicals 65997-16-2	EC50 (72h)Algae (Pseudokirchneriella subcapitata) >5.6mg/L	LC50 (96h) Fish (Oncorhynchus mykiss) >100 mg/L (OECD 203)		EC50 (48h) Daphnia magna =6.6mg/L (OECD 202)
Ashes, residues 68131-74-8				EC50: 140 - 2000mg/L (24h, Daphnia magna)
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/L Fish (Oncorhynchus mykiss)		CE50 (48h) >1000 mg/L Daphnia Magna
Calcium sulfate 7778-18-9	CL50 (72h) >100 mg/L Algae	LC50: >1970mg/L (96h, Pimephales promelas) LC50: =2980mg/L (96h, Lepomis macrochirus)		CE50 (48h) >100 mg/L Waterflea (Daphnia magna)
Calcium oxide 1305-78-8	EC50 (Pseudokirchneriella subcapitata (green algae)): 106,02 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes	LC50 96 h = 50.6 mg/L (Oncorhynchus mykiss)	EC50 (Bacteria): 229,2 mg/l Exposure time: 3 h Test Type: static test Method: OECD Test Guideline 209 GLP: yes	EC50 (48h) = 49.1 mg/l(Daphnia magna) OECD 202
Bentonite 1302-78-9	EC50 (72h)> 100 mg/L (Desmodesmus subspicatus)	LC50: =19000mg/L (96h, Oncorhynchus mykiss) LC50: 8.0 - 19.0g/L (96h, Salmo gairdneri)		EC50 (48h) > 100 mg/L (Daphnia magna) OECD 202

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal of Wastes

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

Contaminated packaging

Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG Not regulated

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.
Ashes, residues	68131-74-8

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 07-Nov-2018

Revision note Not applicable.

Training Advice No information available

Safety Data Sheet

ULTRAFINISH(TM) PRO
Revision Number 2

Revision Date 07-Nov-2018
Supersedes Date: 21-Apr-2016

Further information

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet