

In accordance with OSHA 29 CFR 1910.1200

WOODGRIP(TM) PLUS

Revision Number 3

Revision date 14-Nov-2022 Supersedes Date: 15-Feb-2019

1. Identification			
1.1. Product identifier			
Product Name	WOODGRIP(TM) PLUS		
<u>Other means of identification</u> Other information	Not applicable		
1.2. Relevant identified uses o	f the substance or mixture and us	es advised against	
Recommended use Restrictions on use	Adhesives and/or sealants No information available		
1.3. Details of the supplier of t	<u>ne safety data sheet</u>		
Bostik Inc. 11320 W. Watertown Plank Roa Wauwatosa, Wisconsin 53226 U Phone: +1 (800) 843-0844 (Dor Phone: +1 (414) 774-2250 (Inte Fax: +1 (414) 774-8075	SA nestic Toll Free) rnational)		
E-mail	msds@bostik.com		
1.4. Emergency telephone nun	iber		
Emergency Telephone	Rocky Mountain Poison Ce	US), 1-703-527-3887 (Outside U.S.) enter: 1-866-767-5089 sportation Emergency Center)	
2. Hazard(s) identificat	ion		
2.1. Classification of the subst	ance or mixture		
Skin sensitization		Category 1	
Reproductive toxicity		Category 1B	
Hazards not otherwise classifi	ed (HNOC)		

Not applicable

2.2. Label elements


EMERGENCY OVERVIEW

Danger

Hazard statements

May cause an allergic skin reaction May damage fertility or the unborn child

WOODGRIP(TM) PLUS Revision Number 3



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

2 % of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No	Weight-%
Limestone	1317-65-3	40 - 70
Carbonic acid, calcium salt (1:1)	471-34-1	3 - <7
Trimethoxyvinylsilane	2768-02-7	1 - <5
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0.1 - <1
Quartz	14808-60-7	0.1 - <1
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	22673-19-4	0.1 - <1

*The exact percentage (concentration) of composition has been withheld as a trade secret

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	Immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. May cause sensitization by skin contact. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Call a physician immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergic skin reaction. Erythema (skin redness). Hives. Itching.	
4.3. Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.	

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Large Fire	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Full water jet.
5.2. Special hazards arising from th	e substance or mixture
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Silicon dioxide.
Explosion data Sensitivity to mechanical impac	t None.
Sensitivity to static discharge	None.
5.3. Advice for firefighters	
Special protective equipment for fire-fighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

WOODGRIP(TM) P	LUS
Revision Number	3

6.1. Personal precautions, protective equipment and emergency procedures		
Personal precautions	Use personal protective equipment as required. Do not touch or walk through spilled material. Ensure adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.	
Other information	Refer to protective measures listed in Sections 7 and 8.	
6.2. Environmental precautions		
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.	
6.3. Methods and material for containment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).	
Methods for cleaning up	Use personal protective equipment as required. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.	
Reference to other sections	See section 8 for more information. See section 13 for more information.	

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep/store only in original container. Keep away from food, drink and animal feeding stuffs. Protect from moisture.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

7.3 References to other sections

Reference to other sections	Section 13: DISPOSAL CONSIDERATIONS
	Section 10: STABILITY AND REACTIVITY

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is

unlikely to occur from exposure to this product.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
		(vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	
Carbonic acid, calcium salt (1:1) 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 μg/m ³ TWA: 50 μg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	STEL: 0.2 mg/m³ Sn TWA: 0.1 mg/m³ Sn S*	TWA: 0.1 mg/m³ Sn (vacated) TWA: 0.1 mg/m³ Sn (vacated) S*	IDLH: 25 mg/m³ Sn TWA: 0.1 mg/m³ except Cyhexatin Sn

Chemical name	Argentina	Brazil	Chile	Colombia
Limestone	TWA: 10 mg/m ³	-	LPP: 7 mg/m ³	-
1317-65-3			LPP: 5 mg/m ³	
Quartz 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	LPP: 0.08 mg/m ³	TWA: 0.025mg/m ³
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	TWA: 0.1 mg/m ³ Skin STEL: 0.2 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³	LPP: 0.09 mg/m ³ S*	STEL: 0.2mg/m ³ TWA: 0.1mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Carbonic acid, calcium salt (1:1) 471-34-1	-	TWA: 10mg/m ³	-	TWA: 10 mg/m ³
Quartz 14808-60-7	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	TWA: 0.025 mg/m ³
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	TWA: 0.1mg/m ³ STEL: 0.2mg/m ³	STEL: 0.2mg/m ³ TWA: 0.1mg/m ³	0.2 mg/m³ STEL (as Sn) 0.1 mg/m³ TWA (as Sn)	Skin STEL: 0.2 mg/m³ TWA: 0.1 mg/m³

8.2. Exposure controls

OTHER INFORMATION

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³

Chemical name	Argentina	Brazil	Chile	Colombia
Methyl alcohol 67-56-1	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 156 ppm TWA: 200 mg/m ³ STEL: 250 ppm	LPP: 175 ppm LPP: 229 mg/m³ S*	STEL: 250ppm TWA: 200ppm
		Skin	LPT: 250 ppm LPT: 328 mg/m ³	

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Methyl alcohol 67-56-1	TWA: 200ppm STEL: 250ppm	STEL: 250ppm STEL: 328mg/m ³ TWA: 200ppm TWA: 262mg/m ³	250 ppm STEL 200 ppm TWA	Skin STEL: 250 ppm TWA: 200 ppm

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
	Ventilation eyetemet

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General hygiene considerations	Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash it before reuse. Regular cleaning of equipment, work area and clothing is recommended.

9. Physical and chemical properties

WOODGRIP(TM) PLUS Revision Number 3

Physical state	Liquid			
Appearance	Paste			
Color	Beige			
Odor	Fruity			
Odor threshold	No information available			
_				
Property	<u>Values</u>	Remarks • Method		
рН	No data available	None known		
pH (as aqueous solution)	No data available	None known		
Melting point / freezing point	No data available	None known		
Initial boiling point and boiling rang		None known		
Flash point	> 110 °C / 230 °F	ASTM D3278		
Evaporation rate	No data available	None known		
Flammability	Not applicable for liquids .	None known		
Flammability Limit in Air		None known		
Upper flammability or explosive limits	No data available			
Lower flammability or explosive limits	No data available			
Vapor pressure	No data available	None known		
Relative vapor density	No data available	None known		
Relative density	No data available	None known		
Water solubility	No data available	None known		
Solubility(ies)	No data available	None known		
Partition coefficient	No data available	None known		
Autoignition temperature	No data available	None known		
Decomposition temperature	No data available	None known		
Kinematic viscosity	No data available	None known		
Dynamic viscosity	No data available	None known		
9.2. Other information				
Explosive properties	No information available			
Oxidizing properties	No information available			
Solvent content (%)	No information available			
Solid content (%)	96.8			
Softening Point	No information available			
Molecular weight	No information available			
VOC content	0 g/L	No information available		
Liquid Density	1.710 g/cm ³			
Bulk density	No information available			
10. Stability and reactivity				
10.1. Reactivity				
Reactivity	Product cures with moisture.			
10.2. Chemical stability				
Chemical stability	Stable under normal conditions.			
10.3. Possibility of hazardous react	ions			
Possibility of hazardous reactions	None under normal processing.			
10.4. Conditions to avoid				
Conditions to avoid	Protect from moisture. Exposure to a	ir or moisture over prolonged periods. Do not freeze.		
	rioleor nom moisiure. Exposure to a			
US - EN		Page 7 / 13		
		=		

WOODGRIP(TM) PLUS
Revision Number 3

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Water.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon oxides Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

<u>Acute toxicity</u> Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal)	63,457.50 mg/kg
ATEmix (inhalation-vapor)	875.10 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Carbonic acid, calcium salt (1:1) 471-34-1	LD50 > 2000 mg/kg (Rattus) OECD 420	LD50 >2000 mg/kg (Rattus) OECD 402	LC50 (4h) >3mg/ml (Rattus)
Trimethoxyvinylsilane 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
N-(3-(trimethoxysilyl)propyl)ethy lenediamine 1760-24-3	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air
Quartz 14808-60-7	>20000 mg/kg	-	-
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	LD50 = 1864 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (Rattus) OECD 402	LC50 4hr: 16.8 mg/l (Rattus) (OECD TG 403)

WOODGRIP(TM) PLUS

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute	Rabbit	eye		24 hours	Non-irritant
Eye Irritation/Corrosion					

Respiratory or skin sensitization

May cause sensitization by skin contact.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitizing
Sensitization, Buehler test			-

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation	in vitro	Not mutagenic
Test		-

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)

Method	Species	Results
OECD Test No. 476: In vitro Mammalian Cell	in vitro	Mutagenic
Gene Mutation Test		

Carcinogenicity

Based on available data, the classification criteria are not met. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	Х

Legend

ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans NTP (National Toxicology Program) Known - Known Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

Quartz (14808-60-7)

Method	Species	Results

WOODGRIP(TM) PLUS

IARC (International Agency for Research on	Human evidence	Carcinogenic
Cancer)		

Reproductive toxicity

Contains a known or suspected reproductive toxin. May cause harm to breast-fed children.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Subchronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapor		90 days	0.058 NOAEL

Target organ effects	Eyes, Respiratory system, Skin.
Aspiration hazard	Based on available data, the classification criteria are not met.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmondesmus subspicatus)	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Carbonic acid, calcium salt (1:1) 471-34-1	IC50 72H Algae >1000 mg/l	CL50 96H >1000 mg/l	-	EC50 48H Daphnia >1000 mg/l
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)
N-(3-(trimethoxysilyl)prop yl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static
Tin, dibutylbis(2,4-pentanedio nato-O,O')-, (OC-6-11)-	>2.0 mg/l	>2.0 mg/l	-	EC50 0.0036 mg/l 48Hr (Daphnia magna)

WOODGRIP(TM) PLUS

22673-19-4

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9
Trimethoxyvinylsilane 2768-02-7	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3

12.4. Mobility in soil

Mobility	No information available.
Other adverse effects	
Other adverse effects	No information available.

13. Disposal considerations

13.1. Waste treatment methods	
Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.

14. Transport information

Note:	The information shown here, may not always agree with the bill of lading shipping description for the material The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition) 49 CFR 171.4(c) "Exceptions. Except when all or part of the transportation is by vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft."
DOT UN number or ID number Proper Shipping Name Transport hazard class(es) Packing Group Special Provisions Marine Pollutant	UN3082 Environmentally hazardous substance, liquid, n.o.s. 9 III 8, 146, 173, 335, IB3, T4, TP1, TP29 Np

WOODGRIP(TM) PLUS	Revision date	
Revision Number 3	Supersedes Date:	
Description	UN3082, Environmentally hazardous substance, liquid, n.o.s.(Tin,	
Emergency Response Guide	dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-), 9, III, Marine Pollutant	
Number	171	
IATA	UN3082	
UN number or ID number	Environmentally hazardous substance, liquid, n.o.s.	
UN proper shipping name	9	
Transport hazard class(es)	III	
Packing group	A97, A158, A197	
Special Provisions	UN3082, Environmentally hazardous substance, liquid, n.o.s.(Tin,	
Description	dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-), 9, III	
IMDG	UN3082	
UN number or ID number	Environmentally hazardous substance, liquid, n.o.s.	
UN proper shipping name	9	
Transport hazard class(es)	III	
Packing group	F-A, S-F	
EmS-No	274, 335, 969	
Special Provisions	P	
Marine pollutant	UN3082, Environmentally hazardous substance, liquid, n.o.s.(Tin,	
Description	dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-), 9, III, Marine Pollutant	

15. Regulatory information

International Inventories

DSL Listed	

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

14-Nov-2022 15-Feb-2019

WOODGRIP(TM) PLUS

STEL (Short Term Exposure Limit)

Skin designation

SVHC: Substances of Very High Concern for Authorization:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No	SVHC candidates
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	22673-19-4	Х

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA Ceiling	TWA (time-weighted average) Maximum limit value	STEL *
Prepared By	Product Safety & Regulatory Affairs.	
Revision date	14-Nov-2022	
Revision Note	Not applicable.	

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at

https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-mana gement/medical-device-policy/ which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet