

In accordance with OSHA 29 CFR 1910.1200

BOSTIK(R) LOCK A485MP Revision Number 1

Revision date 12-Mar-2021 Supersedes Date: Not applicable

1. Identification

1.1. Product identifier

Product Name BOSTIK(R) LOCK A485MP

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive

Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.

11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA

Phone: +1 (800) 843-0844 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International)

Fax: +1 (414) 774-8075

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone Chemtrec (Transport/Environmental): 1-800-424-9300

1-703-527-3887 (Outside U.S.)

Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200.

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200.

Appearance No information available Physical state Liquid Odor No information available

US - EN Page 1/9

BOSTIK(R) LOCK A485MP

Revision Number 1 Supersedes Date: 12-Mar-2021

Revision date 12-Mar-2021

2.3. Other Information

No information available.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No	Weight-%
Kaolin	1332-58-7	30 - 60

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. First-aid measures

4.1. Description of first aid measures

Inhalation IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do

not rub affected area. If eye irritation persists: Get medical advice/attention.

Skin contact Wash off immediately with plenty of water for at least 15 minutes. In the case of skin

irritation or allergic reactions see a physician.

Ingestion Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious

person. If swallowed, call a poison control center or physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Carbo

CALITION: Use of water spray when fighting fire may be ineffi

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

US - EN Page 2/9

BOSTIK(R) LOCK A485MP

Revision Number 1 Supersedes Date: 12-Mar-2021

Hazardous combustion products Carbon dioxide (CO2). Silicon dioxide.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

Revision date 12-Mar-2021

(approved or equivalent) and full protective gear.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Avoid contact

with skin and eyes.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. See Section 12 for additional Ecological

Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other noncombustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

hygiene and safety practice. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. Avoid contact with skin and eyes. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

7.3 References to other sections

Reference to other sections Section 10: STABILITY AND REACTIVITY

Section 13: DISPOSAL CONSIDERATIONS

US - EN Page 3/9

BOSTIK(R) LOCK A485MP Revision Number 1 Supersedes Date: 12-Mar-2021

Revision date 12-Mar-2021

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Kaolin	TWA: 2 mg/m³ particulate	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³ total dust
1332-58-7	matter containing no asbestos	TWA: 5 mg/m ³ respirable	TWA: 5 mg/m ³ respirable dust
	and <1% crystalline silica,	fraction	-
	respirable particulate matter	(vacated) TWA: 10 mg/m³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	

Chemical name	Argentina	Brazil	Chile	Colombia
Kaolin	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 13 mg/m ³	TWA: 2mg/m ³
1332-58-7			TWA: 4.5 mg/m ³	

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Kaolin 1332-58-7	TWA: 2mg/m³	TWA: 2mg/m³	2 mg/m³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	TWA: 2 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear suitable gloves. The selection of suitable gloves does not only depend on the Hand protection

material, but also on further marks of quality and various manufacturers.

Wear suitable protective clothing. Skin and body protection

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Wear suitable gloves and eye/face protection. Handle in accordance with good industrial General hygiene considerations

hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Regular cleaning of

equipment, work area and clothing is recommended.

US - EN Page 4/9

BOSTIK(R) LOCK A485MP

Revision Number 1 Supersedes Date: 12-Mar-2021

Revision date 12-Mar-2021

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid

AppearanceNo information availableColorNo information availableOdorNo information availableOdor thresholdNo information available

Property Plane Pla

pH 9.0 - 10.0
pH (as aqueous solution) No data available None known
Melting point / freezing point No data available None known

Initial boiling point and boiling

No data available

None known range

Flash point No data available None known Evaporation rate No data available None known

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressure No data available None known Relative vapor density No data available None known No data available None known Relative density Water solubility No data available None known No data available Solubility(ies) None known No data available Partition coefficient None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known

Dynamic viscosity 55000 - 65000 mPa s Spindle TD @ 10 rpm @ 25 °C

9.2. Other information

Explosive properties

Oxidizing properties

Solvent content (%)

No information available
No information available
No information available

Solid content (%) 60-62

Softening Point No information available Molecular weight No information available

VOC Content (%) 0 % 0 g/L

Density 1.10 g/cm³

Bulk density No information available

10. Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

US - EN Page 5/9

Revision date 12-Mar-2021

BOSTIK(R) LOCK A485MP

Revision Number 1 Supersedes Date: 12-Mar-2021

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Keep from freezing.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin	LD50 (Rattus) > 2000 mg/kg	> 5000 mg/kg (Rattus)	1.5 mg/l 4hr
1332-58-7			-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

US - EN Page 6/9

BOSTIK(R) LOCK A485MP

Revision Number 1 Supersedes Date: 12-Mar-2021

STOT - single exposureBased on available data, the classification criteria are not met.

STOT - repeated exposure

Aspiration hazard

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Revision date 12-Mar-2021

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity . No information available.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Kaolin	IC 50 (72h) > 1000 mg/l	LC 50 (96h) > 1000 mg/l	-	EC 50 (48h) > 1000 mg/l
1332-58-7		-		(Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and

disposal methods in compliance with applicable regulations.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: Keep from freezing

US - EN Page 7/9

BOSTIK(R) LOCK A485MP Revision date 12-Mar-2021
Revision Number 1 Supersedes Date: 12-Mar-2021

·

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

International Inventories

TSCA	Listed
DSL	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Prepared By Product Safety & Regulatory Affairs.

Revision date 12-Mar-2021

US - EN Page 8/9

BOSTIK(R) LOCK A485MP Revision Number 1

sion Number 1 Supersedes Date: 12-Mar-2021

Revision date 12-Mar-2021

Revision note

No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

US - EN Page 9/9