



DECLARATION OF PERFORMANCE

ZWALUW POLYFLEX 422 WHITE

Number 606-24-0001 & 17001051-3001

Revision Number

1

1. Unique identification code of the product-type:

EN 15651-1:F-EXT-INT-CC (CLASSE 25HM)

2. Intended use/es:

Sealants for façade elements. for interior and exterior application. (intended for use in cold climates).

3. Manufacturer:

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00
www.bostik.com

4. Authorised representative:

Not applicable

5. System(s) of assessment and verification of constancy of performance (AVCP):

System 3

6. :

6a. Harmonized standard:

EN 15651-1

Notified body/ies:

NB 1213: SKZ - Testing GmbH, Germany

6b. European Assessment Document:

European Technical Assessment:

Not applicable

Technical Assessment Body:

Not applicable

Notified body/ies:

Not applicable

7. Declared performance(s):

Conditioning:

Procedure A

Substrate:

Anodised aluminium without primer Mortar M2 without primer

EN 15651-1: 2012

Essential characteristics	Performance
Reaction-to-fire (EN 13501-1)	Class E
Release of dangerous substances	NPD: No Performance Determined
Resistance to flow (EN ISO 7390)	≤ 3 mm
Loss of volume (EN ISO 10563)	≤ 10 %
Adhesion/elongation under pretension and after immersion in water (EN ISO	NF: No Failure

606-24-0001 &
17001051-3001