

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SIROFLEX PU-FOAM CLEANER

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Surface cleaning

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company NameManufacturerBostik LimitedBostik GmbH

Common Rd Niederlassung Albertshausen

ST16 3EH Giebelstadter Weg 16

Stafford UK D-97234 Reichenberg-Albertshausen

Tel: +44 (1785) 27 26 25 Germany

Fax: +44 (1785) 25 72 36 Tel: +49 9366 90710

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Aerosols	Category 1 - (H222, H229)
Eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Target organ effects: Narcotic effects.	

2.2. Label elements

Contains Acetone



United Kingdom - BE Page 1 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

Signal word

Danger

Hazard statements

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P261 - Avoid breathing mist/vapours/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, eye protection and face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of an explosive/highly flammable mixture is possible. Repeated exposure may cause skin dryness or cracking. During transportation by car the cans should stand upright in the cargo space. In case of insufficient ventilation and/or through use, the formation of an explosive/highly flammable mixture is possible. The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam. When foaming the propellants are highly flammable.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No. (Index No.)		concentration	M-Factor	M-Factor (long-ter m)	Notes
Acetone	80 - 100	01-2119471330	200-662-2	Eye Irrit. 2 (H319)	-	-	-	-
67-64-1		-49-XXXX	(606-001-00-8)	STOT SE 3 (H336)				
				Flam. Liq. 2 (H225)				
				(EUH066)				
Carbon dioxide	1 - <5	[4]	204-696-9	Press. Gas (H281)	-	-	-	-
124-38-9								
Butane	1 - <3	01-2119474691	203-448-7	Flam. Gas 1 (H220)	-	-	-	C,U
106-97-8		-32-XXXX	(601-004-00-0)	Press. Gas (H280)				
Isobutane	1 - <2.5	01-2119485395	200-857-2	Flam. Gas 1 (H220)	-	-	-	C,U
75-28-5		-27-XXXX	(601-004-00-0)	Press. Gas (H280)				

United Kingdom - BE Page 2 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

NOTE [4] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex IV of REACH Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour -	
					dust/mist - mg/L	vapour - mg/L	gas - ppm
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	•	-	•
Carbon dioxide	204-696-9	124-38-9	1	-	1	-	1
Butane	203-448-7 (601-004-00-0)	106-97-8	•	-	•	-	•
Isobutane	200-857-2 (601-004-00-0)	75-28-5	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety

data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a doctor.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin,

eyes or clothing.

United Kingdom - BE Page 3 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024

Revision date 07-Jul-2025 Revision Number 1.01

4.2. Most important symptoms and effects, both acute and delayed

May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour **Symptoms**

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

No information available. **Effects of Exposure**

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Dry chemical. Carbon dioxide (CO2). Water spray. Suitable Extinguishing Media

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

Hazardous combustion products Carbon oxides.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See Personal precautions

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take

precautionary measures against static discharges. Avoid breathing

dust/fume/gas/mist/vapours/spray.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions**

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce

vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

United Kingdom - BE 4 / 14 Page

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient

ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face

protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition

(i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep/store only in original container.

Store in a dry place. Store in a closed container.

7.3. Specific end use(s)

Specific use(s)

Surface cleaning.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Acetone	TWA: 500 ppm;	TWA: 500 ppm;
67-64-1	TWA: 1210 mg/m ³ ;	TWA: 1210 mg/m ³ ;
	_	STEL: 1500 ppm;
		STEL: 3620 mg/m ³ ;
Carbon dioxide	TWA: 5000 ppm;	TWA: 5000 ppm;

United Kingdom - BE Page 5 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024

Revision date 07-Jul-2025 Revision Number 1.01

124-38-9	TWA: 9000 mg/m³;	TWA: 9150 mg/m³; STEL: 15000 ppm; STEL: 27400 mg/m³;
Butane 106-97-8	-	TWA: 600 ppm; TWA: 1450 mg/m³; STEL: 750 ppm;
		STEL: 1810 mg/m ³ ;

Chemical name	European Union	Ireland	United Kingdom
Acetone	-	50 mg/L (urine - Acetone end of	-
67-64-1		shift)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DN	Derived No Effect Level (DNEL)					
Acetone (67-64-1)	•					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d				
Short term Local health effects worker	Inhalation	2420 mg/m³				
Long term Systemic health effects worker	Inhalation	1210 mg/m³				

Derived No Effect Level (DN	Derived No Effect Level (DNEL)						
Acetone (67-64-1)	Acetone (67-64-1)						
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
Consumer Long term Systemic health effects	Inhalation	200 mg/m³					
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d					
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d					

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)				
Acetone (67-64-1)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	10.6 mg/l			
Freshwater - intermittent	21 mg/l			
Marine water	1.06 mg/l			
Microorganisms in sewage treatment	100 mg/l			
Freshwater sediment	30.4 mg/kg dry weight			
Marine water	3.04 mg/kg dry weight			
Soil	29.5 mg/kg dry weight			

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

United Kingdom - BE Page 6 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The

breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform

to standard EN 374

Skin and body protectionWear appropriate personal protective clothing to prevent skin contact.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A filter or better.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Aerosol
Colour Colourless

Odour Characteristic. Solvent.

Property Values Remarks • Method

Melting point / freezing point Not applicable No data available °C

Initial boiling point and boiling No data available Not applicable, Aerosol

range

Flammability No data available

Flammability Limit in Air None known

Upper flammability or explosive No data available

imits

Lower flammability or explosive No data available

limits

Flash point No data available Not applicable, Aerosol

Autoignition temperature >200 °C

Decomposition temperatureNone known

pH No data available Not applicable. Insoluble in water.

pH (as aqueous solution)
No data available
None known
No data available
None known

Dynamic viscosity

Water solubility

No data available
Insoluble in water.

Solubility(ies)
No data available
None known
Partition coefficient
No data available
None known
Vapour pressure
No data available
None known
Relative density
No data available
No data available
None known

Bulk density

Density

No data available

0.7813 g/cm³

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%)

VOC content approx 751.3 g/L

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available Not applicable

United Kingdom - BE Page 7 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. May cause irritation

of respiratory tract. May cause drowsiness or dizziness.

Eye contact Causes serious eye irritation. (based on components). May cause redness, itching, and

pain.

Skin contact May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations

may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

United Kingdom - BE Page 8 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

 ATEmix (oral)
 >2000 mg/kg

 ATEmix (dermal)
 >2000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Butane	-	-	=658 g/m³ (Rattus) 4 h
Isobutane	-	-	=658 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)							
Method	Species	Exposure route	Effective dose	Exposure time	Results		
OECD Test No. 405:	Rabbit	eye			irritant		
Acute Eye							
Irritation/Corrosion							

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Acetone (67-64-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Not a skin sensitiser

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in					Narcotic effects
practice					

United Kingdom - BE Page 9 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Oral	200-3400 mg/kg bw/d	91 days	No Observed Adverse Effect Level LOAEL 1700 mg/kg bw/d
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm No Observed Adverse Effect Level

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Acetone	-	LC50 96 h 4.74	EC50 = 14500	EC50 48 h		
67-64-1		- 6.33 mL/L	mg/L 15 min	10294 - 17704		
		(Oncorhynchus		mg/L (Daphnia		
		mykiss)		magna Static)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Acetone (67-64-1)					
Method	Exposure time	Value	Results		
OECD Test No. 301B: Ready	28 days	biodegradation	91 % Readily biodegradable		
Biodegradability: CO2 Evolution Test					
(TG 301 B)					

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
Acetone	-0.24	

United Kingdom - BE Page 10 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

Butane	2.31
Isobutane	2.8

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentBased on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment	
Acetone	Not PBT/vPvB	
Butane	Not PBT/vPvB	
Isobutane	Not PBT/vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

European Waste Catalogue 16 05 04* gases in pressure containers (including halons) containing dangerous

substances

15 01 04 metallic packaging

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
Labels
UN1950
Aerosols
2
2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, 2, (D)

14.5 Environmental hazards No.

14.6 Special precautions for user

Special Provisions 190, 327, 344, 625

Classification code 5F Tunnel restriction code (D) Limited quantity (LQ) 1 L

United Kingdom - BE Page 11 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

<u>IMDG</u>

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)

UN1950
Aerosols
2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, 2.1

14.5 Marine pollutant NP

14.6 Special precautions for user

Special Provisions 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ)See SP277 **EmS-No.**F-D, S-U

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950

14.2 UN proper shipping name Aerosols, flammable

14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, flammable, 2.1

14.5 Environmental hazards No

14.6 Special precautions for user

Special Provisions A145, A167, A802

Limited quantity (LQ) 30 kg G ERG Code 10L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

United Kingdom - BE Page 12 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product contains one or more substance(s) on the Drug Precursors list. Suspicious transactions and significant disappearances and thefts are to be reported. Verify that registration requirements are met. Verify that requirements to provide information to the Competent Authorities are met. The table below indicates ingredients above the cut-off threshold considered as relevant which are listed.

Chemical name	EU - Drug precursors (111/2005 and	EU - Drug precursors - Threshold
	273/2004)	Quantities (111/2005)
Acetone 67-64-1	Category 3	50kg

Regulation (EC) No. 648/2004 (Detergents regulation)

Labelling for contents according to regulation (EC) No. 648/2004

aliphatic hydrocarbons	5 - < 15%

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking

H220 - Extremely flammable gas

H225 - Highly flammable liquid and vapour

H280 - Contains gas under pressure; may explode if heated

United Kingdom - BE Page 13 / 14

SIROFLEX PU-FOAM CLEANER Supercedes date 09-Apr-2024 Revision date 07-Jul-2025 Revision Number 1.01

H281 - Contains refrigerated gas; may cause cryogenic burns or injury

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Notes relating to the identification, classification and labelling of substances

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas,

liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 07-Jul-2025

Indication of changes

Revision NoteSDS sections updated, 2.Training AdviceNo information availableFurther informationNo information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 14 / 14