



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant
Uses advised against Consumer use
Reason why uses advised against Restricted substance per REACH Annex XVII

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 1B - (H350)
Specific target organ toxicity (single exposure)	Category 2 - (H371)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

Contains 2-Butanone, oxime; 3-aminopropyltriethoxysilane; 2-octyl-2H-isothiazol-3-one [OIT]

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01



Signal word
Danger

Hazard statements

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H350 - May cause cancer.
H371 - May cause damage to organs.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use
P260 - Do not breathe dust, fume, gas, mist, vapors and spray
P280 - Wear protective gloves, protective clothing, eye protection and face protection
P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor
P362 + P364 - Take off contaminated clothing and wash it before reuse
P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

Restricted to professional users.

Additional information

Restricted to professional users.

2.3. Other hazards

Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Causes mild skin irritation. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	>25 - <40	01-2119827000-58-XXXX	934-956-3	Asp. Tox. 1 (H304)	-	-	-	-
2-Butanone, oxime 96-29-7	1 - <2.5	01-2119539477-28-XXXX	202-496-6 (616-014-00-0)	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315)	-	-	-	-

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

				Skin Sens. 1 (H317) Eye Dam. 1 (H318) STOT SE 3 (H336) STOT SE 1 (H370) Carc. 1B (H350) STOT RE 2 (H373)				
3-aminopropyltriethoxysilane 919-30-2	0.1- <1	01-2119480479 -24-XXXX	213-048-4 (612-108-00-0)	Acute Tox. 4 (H302) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	-	-	-
Octamethylcyclotetrasiloxane [D4] 556-67-2	0.05 - <0.1	01-2119529238 -36-XXXX	209-136-7 (014-018-00-1)	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	-
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	0.0025 - <0.01	No data available	247-761-7 (613-112-00-5)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Sens. 1A :: C>=0.0015%	100	100	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes
[G] - PBT / vPvB substance

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	-	-	-	-	-
2-Butanone, oxime	202-496-6 (616-014-00-0)	96-29-7	100+	1100+	-	-	-
3-aminopropyltriethoxysilane	213-048-4 (612-108-00-0)	919-30-2	1490	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125+	311+	0.27+	0.27+	0.27+

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supercedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. Wash off immediately with plenty of water for at least 15 minutes. If symptoms persist, call a doctor.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
Effects of Exposure	May cause cancer. May cause damage to organs.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon dioxide (CO ₂). Nitrogen oxides (NO _x). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
---	---

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
---------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.
-----------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.
General hygiene considerations	Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits	Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis
-----------------	--

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

and released upon curing

Chemical name	European Union	United Kingdom
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	TWA/8h 5mg/m ³ STEL/15 mins 10mg/m ³	-
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ ; inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ ; inhalable dust STEL: 7.2 mg/m ³ ; respirable dust
Ethanol 64-17-5	-	TWA: 1000 ppm; TWA: 1920 mg/m ³ ; STEL: 3000 ppm; STEL: 5760 mg/m ³ ;

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
2-Butanone, oxime (96-29-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
DNEL/DMEL Long term Systemic health effects	Inhalation	0.028 mg/m ³	
Long term Local health effects	Inhalation	0.9 mg/m ³	
DNEL/DMEL Long term Systemic health effects	Dermal	0.004 mg/kg bw/d	

3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m ³	
worker Short term Systemic health effects	Inhalation	59 mg/m ³	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m ³	

Derived No Effect Level (DNEL)			
2-Butanone, oxime (96-29-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	0.00482 mg/m ³	

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Long term Local health effects	Dermal	0.43 mg/m ³	
-----------------------------------	--------	------------------------	--

3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m ³	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m ³	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection None under normal use conditions.

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid	
Appearance	Paste	
Colour	See section 1 for more information	
Odour	Characteristic.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 100 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
Water solubility	Insoluble in water. Product cures with moisture	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	0.96	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Prolonged contact may cause redness and irritation. Causes mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

The following ATE values have been calculated for the mixture

ATEmix (oral)	8,333.30 mg/kg
ATEmix (dermal)	91,666.70 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 Inhalation(4h) >5266 mg/m ³ (Rattus)
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rattus, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rattus, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rattus (Vapour)
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m ³ (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal			Eye Damage

Respiratory or skin sensitisation May cause an allergic skin reaction.

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information		
2-Butanone, oxime (96-29-7)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Chemical name	European Union
2-Butanone, oxime	Carc. 1B

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

STOT - single exposure May cause damage to organs.

H371 - May cause damage to the following organs: upper respiratory tract.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonea costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h) > 3193 mg/l (Acartia tonsa)		
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h,	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)		

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

		Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)				
3-aminopropyltriethoxy silane 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)			
Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
2-Butanone, oxime	0.65
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Not PBT/vPvB
2-Butanone, oxime	Not PBT/vPvB
3-aminopropyltriethoxysilane	Not PBT/vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	Not PBT/vPvB

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

12.7. Other adverse effects

Other adverse effects No information available.
PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None
14.7 Maritime transport in bulk according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
2-Butanone, oxime	96-29-7	75 28

28 . Reserved for industrial and professional use.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains a biocide : Contains OIT. May produce an allergic reaction

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors
Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)
This product does not contain any substance(s) on the Drug Precursors list.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H226 - Flammable liquid and vapour
H301 - Toxic if swallowed
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H311 - Toxic in contact with skin
H312 - Harmful in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H330 - Fatal if inhaled
H336 - May cause drowsiness or dizziness
H350 - May cause cancer
H361f - Suspected of damaging fertility
H370 - Causes damage to organs
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS LMN SILICONE OAK
Supersedes date 27-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Prepared By	Product Safety & Regulatory Affairs
Revision date	07-Jul-2025
<u>Indication of changes</u>	

Revision Note	Not applicable.
Training Advice	No information available
Further information	No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet