



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against Consumer use

Reason why uses advised against Restricted substance per REACH Annex XVII

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 1B - (H350)
Specific target organ toxicity (single exposure)	Category 2 - (H371)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

Contains 2-Butanone, oxime

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01



Signal word
Danger

Hazard statements

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H350 - May cause cancer.
H371 - May cause damage to organs.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use
P260 - Do not breathe dust, fume, gas, mist, vapors and spray
P280 - Wear protective gloves, protective clothing, eye protection and face protection
P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor
P362 + P364 - Take off contaminated clothing and wash it before reuse
P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

Restricted to professional users.

Additional information

Restricted to professional users.

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Causes mild skin irritation.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Limestone 1317-65-3	>25 - <40	[5]	215-279-6	[C]	-	-	-	-
Siloxanes and silicones, dimethyl, hydroxy-terminated 70131-67-8	>25 - <40	No data available	-	No data available	-	-	-	-
Hydrocarbons,	20 - <25	01-2119827000	934-956-3	Asp. Tox. 1 (H304)	-	-	-	-

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4		-58-XXXX							
Silica, amorphous 7631-86-9	5 - <10	01-2119379499 -16-XXXX	231-545-4	[C]	-	-	-	-	-
MOS/VOS UNKNOWN	1 - <5	No data available	-	No data available	-	-	-	-	-
Carbon black - nanoform 1333-86-4	1 - <2.5	01-2119384822 -32-XXXX	215-609-9	[C] [K]	-	-	-	-	-
2-Butanone, oxime 96-29-7	1 - <2.5	01-2119539477 -28-XXXX	202-496-6 (616-014-00-0)	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Eye Dam. 1 (H318) STOT SE 3 (H336) STOT SE 1 (H370) Carc. 1B (H350) STOT RE 2 (H373)	-	-	-	-	-
Magnesium carbonate 546-93-0	0.1- <1	No data available	208-915-9	No data available	-	-	-	-	-
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	0.1- <1	01-2119510159 -45-XXXX	237-511-5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	-	-	-	-	-
Poly(dimethylsiloxane) 63148-62-9	0.1 - <0.3	No data available	-	No data available	-	-	-	-	-
Dibutyltin diacetate 1067-33-0	0.05 - <0.1	01-2119634587 -29-XXXX	213-928-8 (050-033-00-X)	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1B (H317) Muta. 2 (H341) Repr. 1B (H360FD) STOT SE 1 (H370) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	1	1	-	-
Octamethylcyclotetrasiloxane [D4] 556-67-2	0.01 < 0.036	01-2119529238 -36-XXXX	209-136-7 (014-018-00-1)	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	-	-
Dodecamethylcyclotetrasiloxane [D6] 540-97-6	0.01 < 0.036	01-2119517435 -42-XXXX	208-762-8	PBT vPvB	-	-	-	-	-
Decamethylcyclotetrasiloxane [D5] 541-02-6	0.01 < 0.036	01-2119511367 -43-XXXX	208-764-9	PBT vPvB	-	-	-	-	-
2-(Carbomethoxy)ethyltrimethoxysilane 76301-00-3	0.01 < 0.036	No data available	-	No data available	-	-	-	-	-
Bis(trimethoxysilylpropyl)amine 82985-35-1	0.0025 - <0.01	01-2119969956 -12-XXXX	280-084-5	Eye Dam. 1 (H318)	-	-	-	-	-
Methyl alcohol	0.0025 -	01-2119433307	200-659-6	Acute Tox. 3 (H301) STOT SE 1 ::	-	-	-	-	-

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

67-56-1	<0.01	-44-XXXX	(603-001-00-X)	Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	C>=10% STOT SE 2 :: 3%<=C<10%			
Toluene 108-88-3	<0.0015	# 01-2119471310 -51-XXXX	203-625-9 (601-021-00-3)	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225)	-	-	-	-
Nanoparticle - identity unknown UNKNOWN	<0.0015	No data available	-	[K]	-	-	-	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes
[G] - PBT / vPvB substance

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Limestone	215-279-6	1317-65-3	-	-	-	-	-
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	-	-	-	-	-
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-
Carbon black - nanoform	215-609-9	1333-86-4	-	-	-	-	-
2-Butanone, oxime	202-496-6 (616-014-00-0)	96-29-7	100+	1100+	-	-	-
Magnesium carbonate	208-915-9	546-93-0	-	-	-	-	-
1-Propanamine, 3-(trimethoxysilyl)-	237-511-5	13822-56-5	-	-	-	-	-
Dibutyltin diacetate	213-928-8 (050-033-00-X)	1067-33-0	-	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
Dodecamethylcyclohexasiloxane [D6]	208-762-8	540-97-6	-	-	-	-	-
Decamethylcyclopentasiloxane [D5]	208-764-9	541-02-6	-	-	-	-	-
Bis(trimethoxysilylpropyl)amine	280-084-5	82985-35-1	-	-	-	-	-
Methyl alcohol	200-659-6 (603-001-00-X)	67-56-1	100	300	-	3	-
Toluene	203-625-9 (601-021-00-3)	108-88-3	-	-	-	-	-

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supercedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. Wash off immediately with plenty of water for at least 15 minutes. If symptoms persist, call a doctor.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
Effects of Exposure	May cause cancer. May cause damage to organs.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.
------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Nitrogen oxides (NO _x). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
---	---

SECTION 6: Accidental release measures

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supercedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
 Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
 Revision Number 1.01

titanium dioxide is unlikely to occur from exposure to this product This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	TWA/8h 5mg/m ³ STEL/15 mins 10mg/m ³	-
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ ; inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ ; inhalable dust STEL: 7.2 mg/m ³ ; respirable dust
Methyl alcohol 67-56-1	TWA: 200 ppm; TWA: 260 mg/m ³ ; pSk	TWA: 200 ppm; TWA: 266 mg/m ³ ; STEL: 250 ppm; STEL: 333 mg/m ³ ; pSk
Carbon black 1333-86-4	-	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³ ;

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL) 2-Butanone, oxime (96-29-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
DNEL/DMEL Long term Systemic health effects	Inhalation	0.028 mg/m ³	
Long term Local health effects	Inhalation	0.9 mg/m ³	
DNEL/DMEL Long term Systemic health effects	Dermal	0.004 mg/kg bw/d	

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	58 mg/m ³	
worker Long term	Dermal	8.3 mg/kg bw/d	
Short term worker	Inhalation	58 mg/m ³	
Short term worker	Dermal	8.3 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m ³	

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Dodecamethylcyclohexasiloxane [D6] (540-97-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	11 mg/m ³	
worker Long term Local health effects	Inhalation	1.22 mg/m ³	
worker Short term Local health effects	Inhalation	6.1 mg/m ³	

Decamethylcyclopentasiloxane [D5] (541-02-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Inhalation	9.7 mg/m ³	
worker Short term Local health effects	Inhalation	24.2 mg/m ³	
worker Long term Systemic health effects	Inhalation	97.3 mg/m ³	
worker Long term Local health effects	Inhalation	24.2 mg/m ³	

Methyl alcohol (67-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d	
Short term Systemic health effects worker	Inhalation	260 mg/m ³	
Short term Local health effects worker	Inhalation	260 mg/m ³	
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	260 mg/m ³	
Long term Local health effects worker	Inhalation	260 mg/m ³	

Toluene (108-88-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	384 mg/kg bw/d	
Long term Systemic health effects	Inhalation	192 mg/m ³	

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Local health effects worker			
Short term Systemic health effects worker	Inhalation	384 mg/m ³	
Long term Local health effects worker	Inhalation	192 mg/m ³	
Short term Local health effects worker	Inhalation	384 mg/m ³	

Derived No Effect Level (DNEL)			
2-Butanone, oxime (96-29-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	0.00482 mg/m ³	
Long term Local health effects	Dermal	0.43 mg/m ³	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m ³	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

Dodecamethylcyclohexasiloxane [D6] (540-97-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	2.7 mg/m ³	
Consumer Long term Local health effects	Inhalation	0.3 mg/m ³	
Consumer Short term Local health effects	Inhalation	1.5 mg/m ³	
Consumer Long term Systemic health effects	Oral	1.7 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	1.7 mg/kg bw/d	

Decamethylcyclopentasiloxane [D5] (541-02-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Inhalation	17.3 mg/m ³	
Consumer Short term Systemic health effects	Oral	5 mg/kg bw/d	

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Consumer Short term Local health effects	Inhalation	4.3 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	17.3 mg/m ³	
Consumer Long term Systemic health effects	Oral	5 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	4.3 mg/m ³	

Methyl alcohol (67-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	50 mg/m ³	
Consumer Long term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	50 mg/m ³	
Consumer Long term Systemic health effects	Dermal	50 mg/kg bw/d	

Toluene (108-88-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	56.5 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	226 mg/m ³	
Consumer Long term Local health effects	Inhalation	56 mg/m ³	
Consumer Local health effects Short term	Inhalation	226 mg/m ³	
Consumer Long term Systemic health effects	Dermal	226 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	8.13 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
 Supercedes date 29-Mar-2023

Revision date 07-Jul-2025
 Revision Number 1.01

Predicted No Effect Concentration (PNEC)	
1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Microorganisms in sewage treatment	13 mg/l
Soil	0.04 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

Dodecamethylcyclohexasiloxane [D6] (540-97-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Sewage treatment plant	>1 mg/l
Freshwater sediment	13 mg/kg dry weight
Marine sediment	1.3 mg/kg dry weight
Soil	3.77 mg/kg dry weight
Sewage treatment plant	>10 mg/l

Decamethylcyclopentasiloxane [D5] (541-02-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	>0.0012 mg/l
Marine water	>0.00012 mg/l
Freshwater sediment	2.4 mg/kg
Freshwater sediment	2.4 mg/kg
Soil	1.1 mg/kg
Sewage treatment plant	>10 mg/l

Toluene (108-88-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.68 mg/l
Marine water	0.68 mg/l
Sewage treatment plant	13.61 mg/l
Freshwater sediment	16.39 mg/kg dry weight
Marine sediment	16.39 mg/kg dry weight
Soil	2.89 mg/kg dry weight

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.
Environmental exposure controls	Do not allow uncontrolled discharge of product into the environment.

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	See section 1 for more information
Odour	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
Water solubility	Insoluble in water. Product cures with moisture	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.27	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Product cures with moisture.
------------	------------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supercedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Prolonged contact may cause redness and irritation. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	8,333.30 mg/kg
ATEmix (dermal)	91,666.70 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	>5000 mg/kg (Rattus)	-	-
Siloxanes and silicones, dimethyl, hydroxy-terminated	>15400 mg/kg (Rattus)	> 16 mL/kg (Oryctolagus cuniculus)	>8750 mg/m ³ (Rattus) 7 h
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 Inhalation(4h) >5266 mg/m ³ (Rattus)
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
Carbon black - nanoform	> 8000 mg/kg (Rat) OECD 401	LD50 > 2000 mg/kg	LC0 > 4.6 mg/m ³ (Rat) 4 h
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
Magnesium carbonate	>2000 mg/Kg Rat	-	-
1-Propanamine, 3-(trimethoxysilyl)-	LD50 (Rattus) > 2000 mg/ kg (2,97 ml/kg) (OECD 401)	LD50 (Oryctolagus cuniculus) > 2000 mg/kg 11,3 ml/kg) OECD 402	-
Poly(dimethylsiloxane)	>17 g/kg (Rattus)	> 2 g/kg (Oryctolagus cuniculus)	-
Dibutyltin diacetate	>2000 mg/Kg Rat	= 2318 mg/kg (Oryctolagus cuniculus)	-
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m ³ (Rattus) 4 h
Dodecamethylcyclohexasiloxane [D6]	>50 g/kg (Rattus)	> 2000 mg/kg (Rat)	-
Decamethylcyclopentasiloxane [D5]	>24134 mg/kg (Rattus)	> 16 mL/kg (Oryctolagus cuniculus)	= 8.67 mg/L (Rat) 4 h
Bis(trimethoxysilylpropyl)amine	=3600 µL/kg (Rattus)	= 11300 µL/kg (Oryctolagus cuniculus)	-
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		72 hours	irritant

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
Dibutyltin diacetate	Muta. 2

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information		
2-Butanone, oxime (96-29-7)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Chemical name	European Union
2-Butanone, oxime	Carc. 1B

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Dibutyltin diacetate	Repr. 1B
Octamethylcyclotetrasiloxane [D4]	Repr. 2
Toluene	Repr. 2

Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure May cause damage to organs.

H371 - May cause damage to the following organs: upper respiratory tract.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
---------------	---------------	------	-------------	-----------	----------	----------

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

	plants		microorganisms			(long-term)
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/ L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna		
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h)> 3193 mg/l (Acartia tonsa)		
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneri ella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
Carbon black - nanoform 1333-86-4	EC50 (72h) > 10.000 mg/l (scenedesmus subspicatus) OECD 201	LC0 (96h): 1.000 mg/l (Brachydanio rerio) OECD 203	-	EC50 (24h) > 5.600 mg/l (Daphnia magna) OECD 202		
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)		
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	EC50 (72h) > 1000 mg/l (Desmodesmus subspicatus) EU Method C.3 (Algal Inhibition test)	LC50 (96h) > >934 mg/L (Danio rerio) OECD 203	-	EC50 (48h) = 331 mg/L (Daphnia magna) OECD 202		
Poly(dimethylsiloxane) 63148-62-9	EC50 14d > 2,000 mg/	-	-	EC50(48hr) > 100 mg/l (Daphnia magna)		
Dibutyltin diacetate 1067-33-0	-	-	-	-	1	1
Octamethylcyclotetrasil oxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
Dodecamethylcyclohex asiloxane [D6] 540-97-6	-	90 d NOEC ≥14 µg/L, Oncorhynchus mykiss	-	NOEC ≥4.6 µg/L (21d) OECD 211 Daphnia Magna		
Bis(trimethoxysilylpropy l)amine 82985-35-1	-	LC50 (96h) =130 mg/L (Oncorhynchus mykiss) Semi-static	-	-		
Methyl alcohol	-	LC50 96 h > 100	EC50 = 39000	-		

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

67-56-1		mg/L (Pimephales promelas static)	mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min			
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchner iella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Silica, amorphous (7631-86-9)			
Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Method	Exposure time	Value	Results
OECD Test No. 301A: Ready Biodegradability: DOC Die-Away Test (TG 301 A)	28 days		67 % Not readily biodegradable

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Dodecamethylcyclohexasiloxane [D6] (540-97-6)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	4.5%	Not readily biodegradable

Decamethylcyclopentasiloxane [D5] (541-02-6)			
Method	Exposure time	Value	Results
OECD 310	28 days	0.14%	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Limestone	0.9
2-Butanone, oxime	0.65
Dibutyltin diacetate	3.39
Octamethylcyclotetrasiloxane [D4]	6.49
Dodecamethylcyclohexasiloxane [D6]	8.87
Decamethylcyclopentasiloxane [D5]	8.02
Methyl alcohol	-0.77
Toluene	2.73

12.4. Mobility in soil

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Not PBT/vPvB
Silica, amorphous	Not PBT/vPvB
Carbon black - nanoform	Not PBT/vPvB
2-Butanone, oxime	Not PBT/vPvB
Magnesium carbonate	Not PBT/vPvB
1-Propanamine, 3-(trimethoxysilyl)-	Not PBT/vPvB
Dibutyltin diacetate	Not PBT/vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
Dodecamethylcyclohexasiloxane [D6]	PBT / vPvB substance
Decamethylcyclopentasiloxane [D5]	PBT / vPvB substance
Bis(trimethoxysilylpropyl)amine	Not PBT/vPvB
Methyl alcohol	Not PBT/vPvB
Toluene	Not PBT/vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

12.7. Other adverse effects

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
2-Butanone, oxime	96-29-7	75 28

28 . Reserved for industrial and professional use.

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) which are regulated pursuant to the EU regulations on drug precursors [(EC) No. 111/2005 and (EC) No. 273/2004] above levels that can be easily used or extracted by readily applicable or economically viable means.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H226 - Flammable liquid and vapour

H301 - Toxic if swallowed

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H361f - Suspected of damaging fertility

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Ceiling Limit Value

SAFETY DATA SHEET

SIROFLEX CONTACTRACTORS PVCu SILICONE BLACK
Supersedes date 29-Mar-2023

Revision date 07-Jul-2025
Revision Number 1.01

Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 07-Jul-2025

Indication of changes

Revision Note Not applicable.
Training Advice No information available
Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet