

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SIROFLEX SUPERGLUE HIGH VISCOSITY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Consumer use This product is a cyanoacrylate-based adhesive

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Respiratory irritation	

2.2. Label elements

Contains ethyl-2-cyanoacrylate



United Kingdom - BE Page 1 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

Signal word

Warning

Hazard statements

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

EU Specific Hazard Statements

EUH202 - Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

P261 - Avoid breathing mist/vapours/spray

P264 - Wash hands thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye protection

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P337 + P313 - If eye irritation persists: Get medical advice/attention

P362 + P364 - Take off contaminated clothing and wash it before reuse

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Polymerises with evolution of heat. Bonds skin and eyes in seconds. Harmful to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No	Classification according to	concentration limit	M-Factor	(long-ter	registration
			Regulation (EC) No. 1272/2008 [CLP]	(SCL)		m)	number
ethyl-2-cyanoacrylate 80 - 100 %	230-391-5 (607-236-00- 9)	7085-85-0	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)	STOT SE 3 :: C>=10%	-	-	01-2119527766- 29-XXXX
Hydroquinone 0.05 - <0.1 %	204-617-8 (604-005-00- 4)	123-31-9	Acute Tox. 4 (H302) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 2 (H351) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	10	1	01-2119524016- 51-XXXX

Full text of H- and EUH-phrases: see section 16

United Kingdom - BE Page 2 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	
ethyl-2-cyanoacrylate	230-391-5 (607-236-00-9)	7085-85-0	-	-	-	-	-
Hydroquinone	204-617-8 (604-005-00-4)	123-31-9	390	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If irritation persists or eye and/or

skin remains bonded: Get medical advice/attention.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical

attention immediately if symptoms occur.

Eye contact If eyelids are bonded closed or if skin to skin or skin to clothing bonding has occurred,

release bonding by covering affected area with a pad wetted with warm water. Do not force eyes or any bonded skin apart. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists or eye and/or skin remains bonded: Get medical advice/attention. Do not rub

affected area. Get medical attention if irritation develops and persists.

Skin contact Polymerises with evolution of heat. If eyelids are bonded closed or if skin to skin or skin

to clothing bonding has occurred, release bonding by covering affected area with a pad

wetted with warm water. Do not force eyes or any bonded skin apart. Wash off

immediately with soap and plenty of water for at least 15 minutes. Allow acetone or warm water to penetrate the bond and gently attempt to move bonded areas without pulling the

skin away from bonded area. Do not remove clothing if adhering to skin.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

United Kingdom - BE Page 3 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Bonds skin and eyes in seconds.

Hazardous combustion products Nitrogen oxides (NOx).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Evacuate

personnel to safe areas. Avoid contact with skin, eyes or clothing. See section 8 for more

information.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not use cloths for mopping up. Flood with water to complete polymerization and

scrape off floor.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Use personal protection equipment. Do not eat, drink or smoke when using this product. See section 8 for more information. Take off contaminated clothing and wash it before reuse. Ensure adequate ventilation. Avoid

United Kingdom - BE Page 4 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

breathing vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Recommended storage

temperature

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8° C.

Do not freeze.

7.3. Specific end use(s)

Specific use(s)

Consumer use. This product is a cyanoacrylate-based adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
ethyl-2-cyanoacrylate	-	STEL: 0.3 ppm
7085-85-0		STEL: 1.5 mg/m ³
Hydroquinone	-	TWA: 0.5 mg/m ³
123-31-9		STEL: 1.5 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Hydroquinone (123-31-9)					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Dermal	3.33 mg/kg bw/d			
worker Long term Systemic health effects	Inhalation	2.1 mg/m³			

Derived No Effect Level (DN	EL)				
Hydroquinone (123-31-9)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Dermal	1.66 mg/kg bw/d			
Consumer Long term Systemic health effects	Inhalation	1.05 mg/m³			
Consumer Long term	Oral	0.6 mg/kg bw/d			

United Kingdom - BE Page 5 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

Systemic health effects

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)			
Hydroquinone (123-31-9)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.57 μg/l		
Freshwater - intermittent	1.34 µg/l		
Marine water	0.057 μg/l		
Freshwater sediment	0.0049 mg/kg dry weight		
Marine sediment	0.00049 mg/kg dry weight		
Soil	0.00064 mg/kg dry weight		
Sewage treatment plant	0.71 mg/l		

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be

replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection Wear suitable protective clothing.

Respiratory protection None under normal use conditions.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid

ColourClear, colourlessOdourCharacteristic.

Property Values Remarks • Method

Melting point / freezing pointNo data availableNone knownInitial boiling point and boiling> 149 °CNone known

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point 80 - 93.4 °C CC (closed cup)
Autoignition temperature No data available None known
Decomposition temperature None known

pH No data available Not applicable.
pH (as aqueous solution) No data available None known
Kinematic viscosity No data available None known

Kinematic viscosity

Dynamic viscosity

No data available
No data available

Water solubility Reacts with water. Polymerisation can occur

Solubility(ies) No data available None known

United Kingdom - BE Page 6 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

Partition coefficientNo data availableNone knownVapour pressure0.7@ 50 °C bar

Relative density

No data available

None known

Bulk density No data available Liquid Density 1.05

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture.

10.5. Incompatible materials

Incompatible materials Alcohols. Alkali. Amines. Water.

10.6. Hazardous decomposition products

Hazardous decompositionNone under normal use conditions. Stable under recommended storage conditions.

products

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

United Kingdom - BE Page 7 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Bonds skin and eyes in

seconds. Causes serious eye irritation. (based on components). May cause redness,

itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Bonds skin and eyes in

seconds. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ethyl-2-cyanoacrylate	>5000 mg/kg (Rattus) OECD 401	>2000 mg/Kg (Oryctolagus cuniculus) OECD 402	<21.1 mg/L (Rattus) 1 h
Hydroquinone	390 mg/kg (Rattus)	= 74800 mg/kg (Oryctolagus cuniculus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information Hydroquinone (123-31-9)

Method	Species	Results
OECD Test No. 476: In Vitro Mammalian Cell	Mouse	Mutagenic
Gene Mutation Tests using the Hprt and xprt		
genes		

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Hydroquinone	Muta. 2

United Kingdom - BE Page 8 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

Carcinogenicity

Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information

Hydroquinone (123-31-9)

Method	Species	Results
OECD Test No. 453: Combined Chronic	Rat	Limited evidence of a carcinogenic
Toxicity/Carcinogenicity Studies		effect

Chemical name	European Union
Hydroguinone	Carc. 2

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties N

No information available.

11.2.2. Other information

Other adverse effects

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
ethyl-2-cyanoacrylate 7085-85-0	polymerizes	polymerizes	-	-		
Hydroquinone 123-31-9	EC50: =0.335mg/L (72h, Pseudokirchneri ella subcapitata)	,		EC50: =0.29mg/L (48h, Daphnia magna)		1

12.2. Persistence and degradability

Persistence and degradability

No information available.

United Kingdom - BE Page 9 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Hydroquinone	0.59

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment		
ethyl-2-cyanoacrylate	The substance is not PBT / vPvB		
Hydroquinone	The substance is not PBT / vPvB		

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note: Applies only during air transport.

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated

14.2 UN proper shipping name

14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated
Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1 UN number or ID number Not regulated

United Kingdom - BE Page 10 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
Not regulated
Not regulated
Not regulated

14.5 Marine pollutant NP14.6 Special precautions for user Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

<u>Air transport (ICAO-TI / IATA-DGR)</u>

14.1 UN number or ID number UN3334

14.2 UN proper shipping name Aviation regulated liquid, n.o.s. (ethyl-2-cyanoacrylate)

14.3 Transport hazard class(es)914.4 Packing group

Description UN3334, Aviation regulated liquid, n.o.s. (ethyl-2-cyanoacrylate), 9, III

14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions A27 Limited quantity (LQ) 30 kg G ERG Code 9A

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the

United Kingdom - BE Page 11 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY

Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H341 - Suspected of causing genetic defects

H351 - Suspected of causing cancer H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 15-Jul-2024

Indication of changes

Revision note Not applicable.

Training Advice No information available Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process,

United Kingdom - BE Page 12 / 13

SIROFLEX SUPERGLUE HIGH VISCOSITY Supercedes date 19-Mar-2024

Revision date 15-Jul-2024 Revision Number 1.02

unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13