



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**SIROFLEX INSTANT PAINTABLE CAULK WHITE**  
**Supersedes date** 29-Aug-2024

**Revision date** 10-Nov-2025  
**Revision Number** 2.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** SIROFLEX INSTANT PAINTABLE CAULK WHITE  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**GB CLP (SI 2020/1567 as amended)**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **Signal word**

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **EU Specific Hazard Statements**

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

## 2.3. Other hazards

### PBT & vPvB

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Quartz 14808-60-7	0.1 - <0.3	[5]	238-878-4	[B]	-	-	-	-
Sodium hydroxide 1310-73-2	0.1 - <0.3	01-2119457892-27-XXXX	215-185-5 (011-002-00-6)	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Met. Corr. 1 (H290)	Eye Irrit. 2 :: 0.5%≤C<2% Eye Dam. 1 :: C≥2% Skin Corr. 1A :: C≥5% Skin Corr. 1B :: 2%≤C<5% Skin Irrit. 2 :: 0.5%≤C<2%	-	-	-
Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts 119345-04-9	0.1 - <0.3	01-2119492361-39-XXXX	601-601-6	Eye Dam. 1 (H318) Repr. 2 (H361fd) Aquatic Chronic 2 (H411)	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.01 < 0.036	01-2120761540-60-XXXX	220-120-9 (613-088-00-6)	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C≥0.036%	1	1	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	<0.0015	No data available	611-341-5	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Eye Dam. 1 :: C≥0.6% Eye Irrit. 2 :: 0.06%≤C<0.6% Skin Corr. 1C :: C≥0.6% Skin Irrit. 2 :: 0.06%≤C<0.6% Skin Sens. 1A ::	100	100	B

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

				(EUH071)	C>=0.0015%			
--	--	--	--	----------	------------	--	--	--

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(b) and Annex V of REACH Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

**Full text of H- and EUH-phrases: see section 16**

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Quartz	238-878-4	14808-60-7	-	-	-	-	-
Sodium hydroxide	215-185-5 (011-002-00-6)	1310-73-2	-	-	-	-	-
Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts	601-601-6	119345-04-9	-	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21 +	0.21 +
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	66	141	0.17	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical No information available.

Hazardous combustion products Silicon dioxide.

### 5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supercedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep from freezing.

**Recommended storage temperature** Do not freeze. Keep at temperatures between 5 and 35 °C.

## 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **Exposure Limits**

Chemical name	European Union	United Kingdom
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m <sup>3</sup> ; inhalable dust TWA: 2.4 mg/m <sup>3</sup> ; respirable dust STEL: 18 mg/m <sup>3</sup> ; inhalable dust STEL: 7.2 mg/m <sup>3</sup> ; respirable dust
Quartz 14808-60-7	TWA: 0.1 mg/m <sup>3</sup> ;	TWA: 0.1 mg/m <sup>3</sup> ; respirable fraction STEL: 0.3 mg/m <sup>3</sup> ; respirable
Sodium hydroxide 1310-73-2	-	STEL: 2 mg/m <sup>3</sup> ;

**Derived No Effect Level (DNEL)** No information available

#### **Derived No Effect Level (DNEL)**

##### **Quartz (14808-60-7)**

##### **Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts (119345-04-9)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	4.4 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	1.2 mg/kg	

##### **1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

#### **Derived No Effect Level (DNEL)**

##### **Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts (119345-04-9)**

# SAFETY DATA SHEET

**SIROFLEX INSTANT PAINTABLE CAULK WHITE**  
**Supersedes date** 29-Aug-2024

**Revision date** 10-Nov-2025  
**Revision Number** 2.02

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.1 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.6 mg/kg	
Consumer Long term Systemic health effects	Oral	0.6 mg/kg	

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts (119345-04-9)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.031 mg/l
Marine water	0.003 mg/l
Sewage treatment plant	1 mg/l
Freshwater sediment	3.24 mg/kg
Marine sediment	0.324 mg/kg
Soil	0.63 mg/kg

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

#### Eye/face protection Hand protection

Tight sealing safety goggles. Eye protection must conform to standard EN 166.  
Recommended Use: Nitrile rubber. Glove thickness > 0.4 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374

#### Skin and body protection Respiratory protection

Suitable protective clothing.  
None under normal use conditions.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	See section 1 for more information
Odour	Characteristic.

Property	Values	Remarks • Method
Melting point / freezing point	= 0 °C	
Initial boiling point and boiling range	= 100 °C	
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	approx No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	7 - 9	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm <sup>2</sup> /s	
Dynamic viscosity	No data available	
Water solubility	Soluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	0.71	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

### 9.2. Other information

Solid content (%)	No information available
VOC content	0 g/L

#### 9.2.1. Information with regards to physical hazard classes

Not applicable

#### 9.2.2. Other safety characteristics

No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

### 10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

#### Explosion data

Sensitivity to mechanical	None.
---------------------------	-------

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

impact  
Sensitivity to static discharge None.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

## 10.4. Conditions to avoid

Conditions to avoid Do not freeze.

## 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

Inhalation Based on available data, the classification criteria are not met.  
Eye contact Based on available data, the classification criteria are not met.  
Skin contact Based on available data, the classification criteria are not met.  
Ingestion Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Acute toxicity

##### Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg  
ATEmix (dermal) >2000 mg/kg  
ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) >5 mg/L  
ATEmix (inhalation-vapour) >20 mg/L

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Sodium hydroxide	= 325 mg/kg ( Rat )	= 1350 mg/kg ( Rabbit )	-
Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts	> 2000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-

# SAFETY DATA SHEET

**SIROFLEX INSTANT PAINTABLE CAULK WHITE**  
**Supersedes date** 29-Aug-2024

**Revision date** 10-Nov-2025  
**Revision Number** 2.02

1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol- 3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	66 mg/kg (Rat)	LD50 = 8141 mg/kg (Rat) OECD 402	= 0.33 mg/L (Rat) 4h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** Based on available data, the classification criteria are not met.

### 11.2.2. Other information

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
---------------	----------------------	------	----------------------------	-----------	----------	----------------------

# SAFETY DATA SHEET

**SIROFLEX INSTANT PAINTABLE CAULK WHITE**  
**Supersedes date** 29-Aug-2024

**Revision date** 10-Nov-2025  
**Revision Number** 2.02

Sodium hydroxide 1310-73-2	-	LC50: =45.4mg/L (96h, Oncorhynchus mykiss)	-	-		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Quartz (14808-60-7)			
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	Not readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts	-2.68
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7

## 12.4. Mobility in soil

**Mobility in soil** No information available.

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)

Method	Value	Results
OECD Test No. 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC)	14.13 Koc	
OECD Test No. 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC)	1.15 log Koc	Very mobile

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Sodium hydroxide	Not PBT/vPvB
Benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts	Not PBT/vPvB

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

1,2-benzisothiazol-3(2H)-one [BIT]	Not PBT/vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	Not PBT/vPvB

## 12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

## 12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.  
PMT or vPvM properties Based on available data, the classification criteria are not met.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

Note: Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

### IMDG

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special precautions for user  
Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated

# SAFETY DATA SHEET

**SIROFLEX INSTANT PAINTABLE CAULK WHITE**  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Biocidal Products Regulation (EU) No 528/2012 (BPR)**

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

##### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

##### **Ozone-depleting substances (ODS) regulation (EC) 2024/590**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

##### **REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**

Not applicable

##### **Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)**

This product does not contain any substance(s) on the Drug Precursors list.

# SAFETY DATA SHEET

SIROFLEX INSTANT PAINTABLE CAULK WHITE  
Supersedes date 29-Aug-2024

Revision date 10-Nov-2025  
Revision Number 2.02

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH071 - Corrosive to the respiratory tract  
H290 - May be corrosive to metals  
H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H310 - Fatal in contact with skin  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H330 - Fatal if inhaled  
H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H411 - Toxic to aquatic life with long lasting effects

#### **Notes relating to the identification, classification and labelling of substances**

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

#### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

#### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 10-Nov-2025

#### Indication of changes

**Revision Note** Not applicable.  
**Training Advice** No information available  
**Further information** No information available

# SAFETY DATA SHEET

**SIROFLEX INSTANT PAINTABLE CAULK WHITE**  
**Supersedes date** 29-Aug-2024

**Revision date** 10-Nov-2025  
**Revision Number** 2.02

---

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**