



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH210 - Safety data sheet available on request
EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supercedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Ethylene glycol 107-21-1	0.1- <1	01-2119456816-28-XXXX	203-473-3 (603-027-00-1)	Acute Tox. 4 (H302) STOT RE 2 (H373)	-	-	-	-
Titanium dioxide 13463-67-7	0.1- <1	01-2119489379-17-XXXX	236-675-5 (022-006-00-2)	[C]	-	-	-	V,W,10
Diethylene glycol monobutyl ether 112-34-5	0.1 - <0.5	01-2119475104-44-XXXX	203-961-6 (603-096-00-8)	Eye Irrit. 2 (H319)	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.01 < 0.036	01-2120761540-60-XXXX	220-120-9 (613-088-00-6)	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.036%	1	1	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	<0.0015	No data available	611-341-5	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1A :: C>=0.0015%	100	100	B

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring
Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Ethylene glycol	203-473-3 (603-027-00-1)	107-21-1	-	-	-	-	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
Diethylene glycol monobutyl ether	203-961-6 (603-096-00-8)	112-34-5	-	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21 +	0.21 +
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	66	141	0.17	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
Effects of Exposure	No information available.

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical No information available.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from frost. Keep away from food, drink and animal feedingstuffs. Keep from

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

freezing.

Recommended storage temperature

Keep at temperatures between 5 and 35 °C. Do not freeze. Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Magnesium carbonate 546-93-0	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Ethylene glycol 107-21-1	TWA: 20 ppm; TWA: 52 mg/m ³ ; STEL: 40 ppm; STEL: 104 mg/m ³ ; pSk	TWA: 10 mg/m ³ ; particulate TWA: 20 ppm; vapour TWA: 52 mg/m ³ ; vapour STEL: 40 ppm; vapour STEL: 104 mg/m ³ ; vapour STEL: 30 mg/m ³ ; particulate pSk
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ ; total inhalable TWA: 4 mg/m ³ ; respirable STEL: 30 mg/m ³ ; total inhalable STEL: 12 mg/m ³ ; respirable
Diethylene glycol monobutyl ether 112-34-5	TWA: 10 ppm; TWA: 67.5 mg/m ³ ; STEL: 15 ppm; STEL: 101.2 mg/m ³ ;	TWA: 10 ppm; TWA: 67.5 mg/m ³ ; STEL: 15 ppm; STEL: 101.2 mg/m ³ ;

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Ethylene glycol (107-21-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	35 mg/m ³	

Titanium dioxide (13463-67-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
------	----------------	--------------------------------	---------------

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

worker Long term Local health effects	Inhalation	10 mg/m ³	
---	------------	----------------------	--

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m ³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Ethylene glycol (107-21-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	7 mg/m ³	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m ³	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Ethylene glycol (107-21-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l
Freshwater - intermittent	10 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	During spraying wear suitable respiratory equipment. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.
Recommended filter type:	Brown. White.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	White
Odour	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	0 °C	
Initial boiling point and boiling range	100 °C	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	
Autoignition temperature	420 °C	
Decomposition temperature		None known
pH	7 - 9	
pH (as aqueous solution)	No data available	
Kinematic viscosity	> 21 mm²/s	@ 40 °C
Dynamic viscosity	No data available	
Water solubility	Miscible in water.	
Solubility(ies)	No data available	
Partition coefficient	No data available	

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

Vapour pressure	No data available
Relative density	1.50 - 1.60
Bulk density	No data available
Density	ca. 1.50 - 1.60 g/cm ³
Relative vapour density	No data available
Particle characteristics	
Particle Size	No information available
Particle Size Distribution	No information available

9.2. Other information

Solid content (%)	No information available
VOC content	approx 22.7 g/L

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None under normal processing.
------------------------------------	-------------------------------

10.4. Conditions to avoid

Conditions to avoid	Protect from frost. Do not freeze.
---------------------	------------------------------------

10.5. Incompatible materials

Incompatible materials	None known based on information supplied.
------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Based on available data, the classification criteria are not met.
------------	---

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/L
ATEmix (inhalation-vapour) >20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene glycol	LD50 > 3200 mg/kg	= 10600 mg/kg (Rattus) = 9530 µL/kg (Oryctolagus cuniculus)	> 2.5025 mg/L (Rat) 6 h
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Diethylene glycol monobutyl ether	LD50: 2410 mg/kg (mouse) OECD 401	LD50: 2764 mg/kg (Oryctolagus cuniculus) OECD 402	-
1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol 1-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	66 mg/kg (Rat)	LD50 = 8141 mg/kg (Rat) OECD 402	= 0.33 mg/L (Rat) 4h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye	Rabbit	Eye			Non-irritant

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

Irritation/Corrosion					
----------------------	--	--	--	--	--

Respiratory or skin sensitisation May produce an allergic reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide	Carc. 2

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Ethylene glycol 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneriella subcapitata)	LC50 96 h = 16000 mg/L (Poecilia reticulata static)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50: =46300mg/L (48h, Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Diethylene glycol	EC50: >100mg/L	LC50:	-	EC50:		

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

monobutyl ether 112-34-5	(96h, Desmodemus subspicatus)	=1300mg/L (96h, Lepomis macrochirus)		=2850mg/L (24h, Daphnia magna) EC50: >100mg/L (48h, Daphnia magna)		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Ethylene glycol	-1.36
Diethylene glycol monobutyl ether	1
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7

12.4. Mobility in soil

Mobility in soil No information available.

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)

Method	Value	Results
OECD Test No. 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC)	14.13 Koc	
OECD Test No. 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC)	1.15 log Koc	Very mobile

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Ethylene glycol	Not PBT/vPvB
Titanium dioxide	Not PBT/vPvB
Diethylene glycol monobutyl ether	Not PBT/vPvB
1,2-benzisothiazol-3(2H)-one [BIT]	Not PBT/vPvB

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	Not PBT/vPvB
--	--------------

12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.
PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diethylene glycol monobutyl ether	112-34-5	55 75

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

National regulations

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H301 - Toxic if swallowed
H302 - Harmful if swallowed
H310 - Fatal in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation

Notes relating to the classification and labelling of mixtures

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 10-Nov-2025

Indication of changes

SAFETY DATA SHEET

SIROFLEX RAINPROOF EXTERIOR CAULK WHITE
Supersedes date 27-Mar-2023

Revision date 10-Nov-2025
Revision Number 1.01

Revision Note	SDS sections updated, 11, 12.
Training Advice	No information available
Further information	No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet