

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

#### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK Supercedes date 30-Oct-2024

Revision date 22-Dec-2023 Revision Number 1.01

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

Reason why uses advised against Restricted substance per REACH Annex XVII

#### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

#### E-mail address

SDS.box-EU@bostik.com

#### 1.4. Emergency telephone number

**United Kingdom** 

Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### Signal word

None

#### Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **EU Specific Hazard Statements**

### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Revision date 22-Dec-2023 Revision Number 1.01

EUH210 - Safety data sheet available on request

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine &

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine & Dioctyltinbis(acetylacetonate). May produce an allergic reaction

#### 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

#### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	concentration	M-Factor	M-Factor (long-ter m)	Notes
Diisononyl phthalate 28553-12-0		01-2119430798 -28-XXXX		[1]	-	-	-	-
Trimethoxyvinylsilane 2768-02-7	1 - <2.5	01-2119513215 -52-XXXX	220-449-8 (014-049-00-0)	Acute Tox. 4 (H332) Skin Sens. 1B (H317) Flam. Liq. 3 (H226)	-	-	-	-
N-(3-(trimethoxysilyl) propyl)ethylenediami ne 1760-24-3	0.1- <1	01-2119970215 -39-XXXX	217-164-6	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)	-	-	-	-
Dioctyltinbis(acetylac etonate) 54068-28-9	0.1 - <0.5	01-0000020199 -67-XXXX	483-270-6	STOT SE 2 (H371) Skin Sens. 1 (H317)	Skin Sens. 1 :: C>=5%	-	-	-
N-[3-(Dimethoxymet hylsilyl)propyl]-ethyle nediamine 3069-29-2	0.1 - <0.5	01-2119963926 -21-xxxx	221-336-6	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317)	-	-	-	-

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[I] - Restricted substance per REACH Annex XVII

#### Full text of H- and EUH-phrases: see section 16

#### Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index	Classification	Specific	M-Factor	M-Factor	REACH
	No)	according to	concentration		(long-term)	registration

#### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK Supercedes date 30-Oct-2024

#### Revision date 22-Dec-2023 Revision Number 1.01

		Regulation (EC) No. 1272/2008 [CLP]	limit (SCL)			number
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

#### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Diisononyl phthalate	249-079-5	28553-12-0	-	-	-	-	-
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
N-(3-(trimethoxysilyl)pr opyl)ethylenediamine	217-164-6	1760-24-3	-	-	1.5	-	-
Dioctyltinbis(acetylacet onate)	483-270-6	54068-28-9	-	-	-	-	-
N-[3-(Dimethoxymethyl silyl)propyl]-ethylenedia mine	221-336-6	3069-29-2	500	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Small amounts of toxic methanol are released by hydrolysis. Call a doctor immediately. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water.

#### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK Supercedes date 30-Oct-2024

4.2. Most important symptoms and	effects, both acute and delayed
Symptoms	None known.
Effects of Exposure	No information available.
4.3. Indication of any immediate me	edical attention and special treatment needed
Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.
5.2. Special hazards arising from the second s	he substance or mixture
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Silicon dioxide.
5.3. Advice for firefighters	
Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, protecti	ve equipment and emergency procedures
Personal precautions	Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.
SECTION 7: Handling and st	orage

### 7.1. Precautions for safe handling

### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Advice on safe handling	Ensure adequate ventilation.			
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.			
7.2. Conditions for safe storage, inc	cluding any incompatibilities			
Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture. Keep away from food, drink and animal feedingstuffs.			
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.			
7.3. Specific end use(s)				
<b>Specific use(s)</b> Adhesives and/or sealants.				
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.			
Other information	Observe technical data sheet.			
SECTION 8: Exposure controls/personal protection				

#### 8.1. Control parameters

**Exposure Limits** 

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Diisononyl phthalate	-	TWA: 5 mg/m <sup>3</sup>
28553-12-0		STEL: 15 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>	TWA: 266 mg/m <sup>3</sup>
	*	STEL: 250 ppm
		STEL: 333 mg/m <sup>3</sup>
		Sk*
Carbon black	-	TWA: 3.5 mg/m <sup>3</sup>
1333-86-4		STEL: 7 mg/m <sup>3</sup>
Dioctyltinbis(acetylacetonate)	-	TWA: 0.1 mg/m <sup>3</sup>
54068-28-9		STEL: 0.2 mg/m <sup>3</sup>
		Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

#### Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)						
Diisononyl phthalate (28553-1	Diisononyl phthalate (28553-12-0)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Long term Systemic health effects	Inhalation	51.72 mg/m³				
worker Long term	Dermal	366 mg/kg bw/d				

### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Systemic health effects			
Trimethoxyvinylsilane (2768	-02-7)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Inhalation	35.5 mg/m³			
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d			

Dioctyltinbis(acetylacetonat	Dioctyltinbis(acetylacetonate) (54068-28-9)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	0.07 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	84 mg/m³	
Short term Systemic health effects worker	Inhalation	84 mg/m³	
Long term Short term Local health effects worker	Inhalation	0.091 mg/m³	

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)			
Туре		Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	12 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	1.7 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768	Trimethoxyvinylsilane (2768-02-7)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	

### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Consumer Systemic health effects	Oral	0,3 mg/kg bw/d	
Long term			

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d	
Consumer Systemic health effects Long term	Inhalation	8.7 mg/m³	
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d	

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Inhalation	2.9 mg/m <sup>3</sup>	
Long term			
Systemic health effects			
Consumer	Dermal	0.83 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Oral	0.83 mg/kg bw/d	
Long term			
Systemic health effects			

### Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l
N-(3-(trimethoxysilyl)propyl)ethylenediamine	(1760-24-3)
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Sewage treatment plant	25 mg/l
Dioctyltinbis(acetylacetonate) (54068-28-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	26 µg/l
Marine water	2.6 µg/l
Freshwater - intermittent	260 µg/l

Freshwater - intermittent	260 µg/l	
Sewage treatment plant	1 mg/l	
Freshwater sediment	0.155 mg/kg dry weight	
Marine sediment	0.0155 mg/kg dry weight	
Soil	0.0158 mg/kg dry weight	

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.006 mg/l

SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Sewage treatment plant	25 mg/l
Freshwater sediment	0.24 mg/kg dry weight
Marine sediment	0.024 mg/kg dry weight
Soil	0.01 mg/kg dry weight

#### 8.2. Exposure controls

Personal protective equipment Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use:. Neoprene <sup>™</sup> . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

#### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical Physical state Appearance Colour Odour	and chemical properties Solid Paste White Characteristic.	
Property_	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling	No data available	None known
range	NI 17 11	
Flammability	No data available	Nana kaawa
Flammability Limit in Air	No data available	None known
Upper flammability or explosive limits	No data avaliable	
Lower flammability or explosive	No data available	
limits		
Flash point	> 60 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
рН		
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm²/s	
Dynamic viscosity	No data available	
Water solubility	Reacts with water. Product cures with moisture	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.58 g/cm <sup>3</sup>	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Revision date 22-Dec-2023 Revision Number 1.01

9.2. Other information	
Solid content (%)	
VOC content	

No information available

No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

### SECTION 10: Stability and reactivity 10.1. Reactivity Product cures with moisture. Reactivity 10.2. Chemical stability Stability Stable under normal conditions. **Explosion data** Sensitivity to mechanical None. impact Sensitivity to static discharge None. 10.3. Possibility of hazardous reactions Possibility of hazardous reactions None under normal processing. 10.4. Conditions to avoid Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition. 10.5. Incompatible materials Incompatible materials None known based on information supplied. 10.6. Hazardous decomposition products Hazardous decomposition None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. products SECTION 11: Toxicological information 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on likely routes of exposure

#### Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Ingestion

Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	722.00 mg/l

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diisononyl phthalate	>9750 mg/kg (Rattus)	>3160 mg/Kg (Oryctolagus	>4.4 mg/L (Rattus) 4 h
		cuniculus)	
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
	(Rattus) OECD 401	cuniculus)	OECD TG 403
N-(3-(trimethoxysilyl)propyl)eth	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44
ylenediamine			mg/L air
Dioctyltinbis(acetylacetonate)	LD50 =2500 mg/kg (Rattus)	LD50 >2000 mg/kg (Rattus)	= 5.1 mg/L (Rat) 4 h
N-[3-(Dimethoxymethylsilyl)pro	=200 - 2000 mg/Kg (Rattus)	>5000 mg/Kg (Oryctolagus	> 5.2 mg/L (Rattus) 4 h
pyl]-ethylenediamine	(OECD 401)	cuniculus)	(OECD 403)
		(OECD 402)	

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit				Mild skin irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant	
Acute Eye						
Irritation/Corrosion						

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	еуе			Eye Damage
Acute Eye					

#### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Revision date 22-Dec-2023 Revision Number 1.01

	Irritation/Corrosion					
--	----------------------	--	--	--	--	--

Respiratory or skin sensitisation

OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information				
Method	S	pecies	Exposure route	Results
OECD Test No. 406	: Skin Gu	iinea pig	Dermal	No sensitisation responses
Sensitisation		-		were observed
OECD Test No. 406	: Skin Gu	iinea pig	Dermal	No sensitisation responses
Sensitisation				were observed

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)				
Method Species Results				
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic		

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Method	Species	Results		
OECD Test No. 471: Bacterial Reverse	Mammalian cells in vitro	Negative		
Mutation Test				
OECD Test No. 476: In Vitro Mammalian Cell	Mammalian cells in vitro	Negative		
Gene Mutation Tests using the Hprt and xprt				
genes				

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Method	Species	Results		
OECD Test No. 422: Combined Repeated Dose	Rat	NOAEL >500 mg/Kg		
Toxicity Study with the	Oral			
Reproduction/Developmental Toxicity Screening				
Test				

#### STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)	
-----------------------------------	--

#### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK Supercedes date 30-Oct-2024

#### Revision date 22-Dec-2023 Revision Number 1.01

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation Toxicity: 90-day Study					

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422:	Rat	Sub-acute oral		28 days	NOAEL >500 mg/kg
Combined Repeated Dose		toxicity gavage			
Toxicity Study with the					
Reproduction/Developme					
ntal Toxicity Screening					
Test					

Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

#### Endocrine disrupting properties

#### 11.2.2. Other information

Other adverse effects

No information available.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

#### Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Diisononyl phthalate 28553-12-0	EC50: >500mg/L (72h, Desmodesmus subspicatus) EC50: >1.8mg/L (96h, Pseudokirchneri	mg/L (Brachydanio rerio semi-static)		EC50: >500mg/L (48h, Daphnia magna) EC50: >0.06mg/L (48h, Daphnia magna)		(iong-term)
Trimethoxyvinylsilane 2768-02-7	ella subcapitata) EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
N-(3-(trimethoxysilyl)pr opyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Dioctyltinbis(acetylacet onate) 54068-28-9	-	LC50 (96h) =86 mg/L (Static)	-	EC50 (48h) =58.6 mg/L (Daphnia magna)		

#### 12.2. Persistence and degradability

Persistence and degradability No information available.

### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric	-		biodegradable
Respirometry Test (TG 301 F)			-

#### 12.3. Bioaccumulative potential

#### **Bioaccumulation**

#### **Component Information**

Chemical name	Partition coefficient
Diisononyl phthalate	9.7
Trimethoxyvinylsilane	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3

#### 12.4. Mobility in soil

### Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

#### PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Diisononyl phthalate	The substance is not PBT / vPvB
Trimethoxyvinylsilane	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB
Dioctyltinbis(acetylacetonate)	The substance is not PBT / vPvB
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	The substance is not PBT / vPvB

#### 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

#### 12.7. Other adverse effects

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

### **SECTION 14: Transport information**

# Land transport (ADR/RID)14.1 UN number or ID number14.2 UN proper shipping nameNot regulated

SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK Supercedes date 30-Oct-2024 Revision date 22-Dec-2023 Revision Number 1.01

<ul> <li>14.3 Transport hazard class(es)</li> <li>14.4 Packing group</li> <li>14.5 Environmental hazards</li> <li>14.6 Special precautions for user</li> </ul>	Not regulated Not regulated Not applicable	
Special Provisions	None	
IMDG		
14.1 UN number or ID number	Not regulated	
14.2 UN proper shipping name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Marine pollutant	NP	
14.6 Special precautions for user		
Special Provisions	None	
14.7 Maritime transport in bulk		
according to IMO instruments		
Transport in bulk according to	Annex II of MARPOL and the IBC Code	Not applicable
Air transport (ICAO-TI / IATA-DGR)		
14.1 UN number or ID number	- Not regulated	
14.2 UN proper shipping name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Environmental hazards	Not applicable	

14.5 Environmental hazardsNot ap14.6 Special precautions for userSpecial ProvisionsNone

### Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diisononyl phthalate	28553-12-0	Use restricted. See entry 52[a].
Dioctyltinbis(acetylacetonate)	54068-28-9	Use restricted. See entry 20.

20 (6) DOT. 52. Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK

Supercedes date 30-Oct-2024

Revision date 22-Dec-2023 Revision Number 1.01

#### Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

### REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors Not applicable

National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

#### **SECTION 16: Other information**

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

I un text of II-Statements referred	to dilder section 5	
H226 - Flammable liquid and vapour		
H302 - Harmful if swallowed		
H315 - Causes skin irritation		
H317 - May cause an allergic skin reaction		
H318 - Causes serious eye damage		
H332 - Harmful if inhaled		
H335 - May cause respiratory irritation	n	
H371 - May cause damage to organs	3	
Legend		
TWA	TWA (time-weighted average)	
STEL	STEL (Short Term Exposure Limit)	
Ceiling	Ceiling Limit Value	
Sk*	Skin designation	
SVHC	Substance(s) of Very High Concern	
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals	
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals	
STOT RE	Specific target organ toxicity - Repeated exposure	
STOT SE	Specific target organ toxicity - Single exposure	
EWC	European Waste Catalogue	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by	
	Road	
IMDG	International Maritime Dangerous Goods (IMDG)	
ΙΑΤΑ	International Air Transport Association (IATA)	
RID	Regulations concerning the International Transport of Dangerous Goods by Rail	

Key literature references and sources for data No information available

SIROFLEX MIGHTY STRENGTH SEAL AND FIX BLACK Supercedes date 30-Oct-2024 Revision date 22-Dec-2023 Revision Number 1.01

Prepared By Revision date Indication of changes	Product Safety & Regulatory Affairs 22-Dec-2023
Revision Note	Not applicable.
Training Advice	When working with hazardous materials, regular training of operators is required by law
Further information	No information available

#### This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**