



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY**

**Supersedes date** 31-Oct-2022

**Revision date** 02-Jan-2025

**Revision Number** 2.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT GREY

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Fillers, putties, plasters, modelling clay

**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **Signal word**

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **EU Specific Hazard Statements**

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction

EUH210 - Safety data sheet available on request

# SAFETY DATA SHEET

**SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY**  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

## Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

## 2.3. Other hazards

No information available.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Quartz 14808-60-7	40 - <80	[5]	238-878-4	[B]	-	-	-	-
Titanium dioxide 13463-67-7	0.1 - <1	01-2119489379 -17-XXXX	236-675-5 (022-006-00-2)	[C]	-	-	-	V,W,10
Quartz (fine fraction) 14808-60-7	0.1 - <1	[5]	238-878-4	STOT RE 1 (H372)	-	-	-	-
Ethylene glycol 107-21-1	0.1 - <0.5	01-2119456816 -28-XXXX	203-473-3 (603-027-00-1)	Acute Tox. 4 (H302) STOT RE 2 (H373)	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.0025 - <0.01	01-2120761540 -60-XXXX	220-120-9 (613-088-00-6)	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.036%	1	1	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	<0.0015	No data available	611-341-5	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1A :: C>=0.0015%	100	100	B

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and,

# SAFETY DATA SHEET

**SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY**  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

**Full text of H- and EUH-phrases: see section 16**

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Quartz	238-878-4	14808-60-7	-	-	-	-	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
Quartz (fine fraction)	238-878-4	14808-60-7	-	-	-	-	-
Ethylene glycol	203-473-3 (603-027-00-1)	107-21-1	500	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21 +	0.21 +
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	66	141	0.17	-	-

This product does not contain candidate substances of very high concern at a concentration ≥0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.

# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Call a doctor or poison control centre immediately.

## **4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

**Effects of Exposure** No information available.

## **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** No information available.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Full water jet.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Product itself does not burn.

### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.

**For emergency responders** Use personal protection recommended in Section 8.

### **6.2. Environmental precautions**

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### **6.4. Reference to other sections**

**Reference to other sections** See section 8 for more information. See section 13 for more information.

# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY  
Supercedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from frost. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 5 and 35 °C. Do not freeze.

### 7.3. Specific end use(s)

**Specific use(s)**  
Fillers, putties, plasters, modelling clay.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	European Union	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.3 mg/m <sup>3</sup>
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Ashes (residues), cenospheres 93924-19-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.3 mg/m <sup>3</sup>
Ethylene glycol 107-21-1	TWA: 20 ppm TWA: 52 mg/m <sup>3</sup> STEL: 40 ppm STEL: 104 mg/m <sup>3</sup> *	TWA: 10 mg/m <sup>3</sup> TWA: 20 ppm TWA: 52 mg/m <sup>3</sup> STEL: 40 ppm STEL: 104 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> Sk*

# SAFETY DATA SHEET

**SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY**  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

**Derived No Effect Level (DNEL)** No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>Quartz (14808-60-7)</b>			
<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>Ethylene glycol (107-21-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	35 mg/m <sup>3</sup>	

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

<b>Derived No Effect Level (DNEL)</b>			
<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

<b>Ethylene glycol (107-21-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	7 mg/m <sup>3</sup>	

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Ethylene glycol (107-21-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l
Freshwater - intermittent	10 mg/l

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

#### Hand protection

Wear protective gloves. Recommended Use: Nitrile rubber. Neoprene™. Glove thickness > 0.4 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374

#### Skin and body protection

Wear suitable protective clothing.

#### Respiratory protection

None under normal use conditions. During spraying wear suitable respiratory equipment.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Grey
Odour	Characteristic.

Property	Values	Remarks • Method
Melting point / freezing point	0 °C	

# SAFETY DATA SHEET

**SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY**  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

Initial boiling point and boiling range	100 °C	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	Not applicable	
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	7 - 9	
pH (as aqueous solution)	No data available	
Kinematic viscosity	> 21 mm <sup>2</sup> /s	@ 40 °C
Dynamic viscosity	No data available	
Water solubility	Partially soluble.	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	120	hPa @ 50 °C
Relative density	No data available	
Bulk density	No data available	
Density	1.66 g/cm <sup>3</sup>	
Relative vapour density	No data available	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

## 9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity Not applicable.

### 10.2. Chemical stability

Stability Stable under normal conditions.

#### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Protect from frost. Do not freeze.



# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY  
Supercedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

## 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >2000 mg/kg  
ATEmix (dermal) >2000 mg/kg  
ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) >5 mg/l  
ATEmix (inhalation-vapour) >20 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-
Ethylene glycol	ATE 500 mg/kg	= 10600 mg/kg (Rattus) = 9530 µL/kg (Oryctolagus cuniculus)	> 2.5 mg/L ( Rat ) 6 h
1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol- 3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	66 mg/kg ( Rat )	LD50 = 8141 mg/kg (Rat) OECD 402	= 0.33 mg/L (Rat) 4h

# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

**Respiratory or skin sensitisation** May produce an allergic reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Titanium dioxide	Carc. 2

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

# SAFETY DATA SHEET

**SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY**  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

## 12.1. Toxicity

### Ecotoxicity

Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Ethylene glycol 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneriella subcapitata)	LC50 96 h = 16000 mg/L (Poecilia reticulata static)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50: =46300mg/L (48h, Daphnia magna)		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

## 12.2. Persistence and degradability

### Persistence and degradability

No information available.

Quartz (14808-60-7)			
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	Not readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Ethylene glycol	-1.36
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7

## 12.4. Mobility in soil

### Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

### PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY  
Supercedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB
Ethylene glycol	The substance is not PBT / vPvB
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None

### 14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated

# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY  
Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Biocidal Products Regulation (EU) No 528/2012 (BPR)**

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

##### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

##### **Ozone-depleting substances (ODS) Regulation (EU) 2024/590**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

##### **REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**

Not applicable

##### **National regulations**

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

# SAFETY DATA SHEET

SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT

GREY

Supersedes date 31-Oct-2022

Revision date 02-Jan-2025

Revision Number 2.01

## Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H372 - Causes damage to organs through prolonged or repeated exposure

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

### **Notes relating to the identification, classification and labelling of substances**

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation

### **Notes relating to the classification and labelling of mixtures**

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 02-Jan-2025

### Indication of changes

**Revision Note** SDS sections updated, 1, 15.  
**Training Advice** No information available  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

# SAFETY DATA SHEET

**SIROFLEX CONTACTRACT MORTAR REPAIR CEMENT  
GREY**  
**Supersedes date** 31-Oct-2022

**Revision date** 02-Jan-2025

**Revision Number** 2.01

---

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**